

Index

- AAS, *see* atomic absorption spectrophotometer
- acid number, 122, 126, 129, 138, 142–43
- activated carbon, 348, 357, 372, 392
- activated sludge processes, conventional, 398
- additives, 205, 207, 213, 219, 221–23, 239, 241–42
- common WBDF, 241
- conventional, 205, 220
- natural, 239
- organic, 95
- regular, 206–7, 220
- safe, 224
- adsorption, 79, 95, 109, 144, 346, 348, 359, 372, 379, 382–83, 392, 400
- metal, 382
- physical, 348, 400
- alkaline-surfactant-alternated-gas (ASAG), 123–24, 126
- alkalinity, 320, 322, 324–25, 328–29, 331–33
- alkali-surfactant-polymer (ASP), 77–78, 81, 83, 85–86, 88, 125
- alpha olefin sulphonate (AOS), 103–4, 106–7, 111, 115–16, 118
- American Petroleum Institute (API), 121, 126, 138
- American Standard for Testing of Materials (ASTM), 38, 129, 193–202, 263, 301, 324–25
- AOS, *see* alpha olefin sulphonate
- API, *see* American Petroleum Institute
- API gravity, 122, 124, 137–39, 144, 240
- aqueous phase, 79, 88–89, 95, 106, 108, 114, 118, 149, 177, 388
- Ardatovskiy formation, 291
- areal displacement, 81
- aromatic hydrocarbons, 160, 347
- biodegraded petroleum-derived, 310
- polycyclic, 344, 371, 387
- soluble, 320
- aromatics, 142, 310, 351, 402
- ASAG, *see* alkaline-surfactant-alternated-gas
- ASAG flooding, 123, 125–26, 144
- ASP, *see* alkali-surfactant-polymer
- ASP flooding, 78, 81–84, 87, 90
- ASP floods, 125
- asphaltene, 105, 122, 126, 129, 138, 140–41, 145, 351
- ASP slug, 78, 80–81, 85, 87, 89–90
- Assam Shelf, 2–3
- ASTM, *see* American Standard for Testing of Materials
- atomic absorption spectrophotometer (AAS), 326
- average angle method, 275–76, 278–82, 284, 286

- backwash, 357, 392
- backwashing, 352, 357, 395
- bacteria, 158, 164–65, 173, 178,
 - 182, 186, 188–90, 312, 333, 350, 389, 394, 399, 411
- aerobic, 167
- anaerobic, 314
- dead, 390, 410–12
- facultative, 166
- facultative BS-producing, 160
- live, 410
- sulphate-reducing, 166, 394
- Barail and Disang Groups, 29–30, 47
- Barail Group, 29–30, 33, 38, 43–47, 51, 53, 59, 62, 75
- Barails, 5–6, 11, 13, 30–34, 36, 38, 40, 42, 44, 46, 51–52
- Barail sandstone, 39–40, 49–50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72, 74
- base mud, 206, 209–10, 214, 220, 224–25, 244–47, 249–50
- bentonite, 206, 208, 210, 212, 214, 216, 224–25, 242–44, 246–49, 372
- Bhogpara oilfields, 200
- biochemical oxygen demand (BOD), 342, 344, 351, 393, 402
- biocompatibility, 169
- biodegradability, 157, 177, 313
- biodegradation, 176, 310–12, 315, 317–18, 351, 401, 403
 - contaminant, 318
 - rapid, 351
- bioemulsification, 176
- bioequivalence, 157
- biofilm, 174–75, 353, 398–401, 406, 410–12
 - bacterial, 399
- biofouling, 353, 398–99, 412
- biogases, 158, 164, 167, 169, 182
- biological treatment, 350–51, 402
- biopolymers, 158, 164, 167–69, 182, 185
- bioproducts, best, 186, 189
- bioreactors, 179, 182, 390, 401–2
 - batch mode, 179
 - integrated, 179
 - stirred tank, 179
- bioremediation, 309, 311–12, 315, 389
- biosolvents, 158, 164, 167–69
- biosurfactant (BS), 157–61, 164–65, 167–79, 181–82, 185, 312–13, 315–16, 318
- BL, *see* black liquor
- black liquor (BL), 78, 103–7, 110–11, 116, 118
- BOD, *see* biochemical oxygen demand
- boiling point, 194–95, 243, 245
- borehole, 239–41
- Bragg angle, 136
- brine, 31, 77, 80, 82, 84–85, 87, 107–10, 113–14, 117–18, 135, 163, 301, 368, 385–86
 - laboratory-prepared, 103, 108, 113–14
 - optimum salinity, 101
 - synthetic soft, 107
- brine flooding, 78, 81, 83, 87, 109
- BS, *see* biosurfactant
 - lipopeptide, 172
 - microbial, 160
 - microbial-origin, 169, 177
- bulk volume (BV), 128, 131
- BV, *see* bulk volume
- by-products, 158, 164–66, 169, 182, 191, 319, 321–22, 394
 - bacterial, 167
 - disinfection, 358
- CaCO₃, 320, 322–24, 326, 328–30, 333–35, 349, 368
- carbonaceous shale, 30, 33–34

- cationic exchange capacity (CEC), 208, 217, 219
- CEC, *see* cationic exchange capacity
- CEOR, *see* chemical enhanced oil recovery
- CFV, *see* crossflow velocity
- Champhai district, 51, 224, 227
- Champhai–Zokhawthar Road, 49, 51, 53, 56–58, 60, 75
- chemical enhanced oil recovery (CEOR), 77–84, 86–88, 90, 104–5, 110, 118, 125, 163
- chemical oxygen demand (COD), 342, 349, 393, 402
- chemical slugs, 77, 99, 101
- Chittagong–Mizoram–Tripura fold thrust belt, 49
- chlorinated polyethylene (CPE), 398, 401, 403–5, 407, 409, 412
- CI, *see* correlation index
- clay, 2, 7, 50, 52, 121–22, 125–27, 136–37, 144, 217, 220, 222–23, 235, 302, 305, 307
- CMC, *see* critical micelle concentration
- CMC mud, 225, 227–28, 235–36
- CMC-PEG4000 mud, 225, 227
- COD, *see* chemical oxygen demand
- confocal scanning laser microscopy (CSLM), 401, 407
- copolymers, 348
- core analysis, 121, 126, 128, 130, 144
- core flooding, 80–83, 94, 97, 101, 104–6, 109, 117–18, 126, 144, 148, 174–75
- core floods, 77, 118, 175
- core plugs, 79, 81, 122, 126–28, 130–35, 144
- core, 1, 4, 11–27, 55–56, 79–81, 83–85, 101, 106–7, 109, 117–18, 130–31, 136–37, 174–75, 186–90, 301–7
- bare, 118
- dry, 118
- porous, 144
- whole/conventional, 130
- correlation index (CI), 193, 326
- corrosion, 143, 166, 240, 242, 319–22, 328, 333–36, 339, 342, 344, 389, 394
- metallic, 334
- CPE, *see* chlorinated polyethylene
- critical micelle concentration (CMC), 89, 94–98, 103, 105, 107, 111–12, 148–49, 151–53, 156, 159, 171–73, 177, 222–25, 227–36
- crossflow, 357, 391, 398, 400, 406, 410
- crossflow velocity (CFV), 401
- crude oil, 94, 99–100, 104–8, 121–22, 125–29, 138–45, 158, 160–61, 176–77, 185–86, 193–96, 198, 200–202, 259–72, 310
- CSLM, *see* confocal scanning laser microscopy
- DAF, *see* dissolved air flotation
- Darcy's equation, 303
- Darcy's law, 109
- Darcy's velocity, 162
- Daubert's method, 196–97
- DBPs, *see* disinfection by-products
- de-emulsification, 185, 348
- de-emulsifiers, 195, 348–49
- oil-soluble, 195
- degradation, 90, 125, 164–65, 312, 317–18, 344
- alkylaromatic, 310
- thermal, 214
- denser-than-water non-aqueous-phase liquids (DNAPL), 149
- depleted reservoirs, 158–60, 162–63, 167, 169, 176, 182

- depletion, 78, 127
 - continuous, 397
 - primary, 141
- deposition, 8, 40, 49, 59, 141, 208, 261
 - particulate, 399
 - wax, 260–62, 389
- depositional environment, 28–30, 38–41, 51, 57, 59, 134, 137, 345
- desalination, 357–58, 391–92
- Digboi oilfield, 2, 32
- Dihing Group, 33
- directional drilling, 241, 275–78, 280, 286
- Disang sandstone, 39–40
- Disang sediment, 30
- Disang shale, 42, 46–47
- disinfection by-products (DBPs), 358
- disposal pit (DP), 362–64, 366–67, 369
- disposal wells, 355–56
- dissolution, 50, 68–69, 72, 362
- dissolved air flotation (DAF), 372
- distilled water (DW), 96, 98–99, 101, 108, 113, 144, 147, 151, 208, 224–25, 242, 324–26
- DMF, *see* *N,N*-dimethylformamide
- DNAPL, *see* denser-than-water non-aqueous-phase liquids
- DP, *see* disposal pit
- drilling, 2, 123, 206, 213–15, 220–24, 237, 239–41, 244, 275–76, 282, 286, 289, 355, 368, 386
 - horizontal, 276
 - salt dome, 277
- drilling fluids, 205–8, 212–15, 217, 219–20, 222–23, 228–29, 232, 235–36, 239–40, 242–44, 246–47, 256–57, 368
 - bentonite-based, 208
 - conventional, 206–7
 - gaseous, 240
 - ideal, 223
 - liquid, 240
 - smart, 207, 220
 - sustainable, 242
- drilling mud, 207, 220–22, 225–26, 229, 239–43, 245, 247, 249, 254, 256–57
 - improvised, 221, 223
 - nanoenhanced, 206–7
 - stable, 214, 220
 - water-based, 224, 239
- DW, *see* distilled water
- EC, *see* electrical conductivity
- edge water encroachment, 305, 307
- EDLs, *see* electrical double layer
- Edmister's method, 193–94, 196, 198
- EDR, *see* electrodialysis reversal
- EFV, *see* equilibrium flash vaporisation
- electrical conductivity (EC), 323, 331–32, 339, 374–75, 380
- electrical double layer (EDL), 87, 89
- electrochemistry, 392–94, 396
- electrodeposition, 393–94, 396
- electrodialysis reversal (EDR), 392
- emulsification, 174–75, 177, 185, 351
- enhanced oil recovery (EOR), 78–79, 93–94, 96, 102–8, 116–18, 121–23, 137–38, 147–50, 154, 156–58, 160–65, 182, 185–86, 191, 315
- EOR, *see* enhanced oil recovery
- EPS, *see* extracellular polymeric substance
- equilibrium flash vaporisation (EFV), 196, 200–202

- ex situ MEOR, 158, 160, 167, 175, 182, 187
- extracellular polymeric substance (EPS), 353
- extraction, 160, 164, 243, 245, 374, 385
- farmland (FL), 362, 366, 368–69
- FBP, *see* final boiling point
- FESEM, *see* field emission scanning electron microscopy
- FID, *see* flame ionisation detector
- field emission scanning electron microscopy (FESEM), 121–22, 126, 136–37, 144
- filtrate loss, 206, 208, 214–19, 222–23, 226, 232–33, 235, 243, 245–47, 249–51, 256, 368
- filtration, 206, 214–15, 219–22, 232, 235–36, 242, 346, 353, 368, 373, 375, 379–83, 390–91, 412
 - dead-end, 391
 - low-pressure, 399
 - low-pressure membrane, 399
- final boiling point (FBP), 195
- FL, *see* farmland
- flame ionisation detector (FID), 44
- flat sheet membrane (FSM), 352
- flooding, 77–78, 81, 84, 87, 90, 109, 123, 125–26, 160, 162, 174–75, 302
 - alkaline, 122–23, 142, 145
 - chemical, 110, 125
 - microemulsion, 95–96, 102
 - miscible, 162, 164
 - stream, 162
- floods, 125
 - chemical, 125
 - prechemical, 109
- flotation, 347, 372
- fluid flow, 148–49, 369
- fluid loss, 223–24, 236, 242
- flux, 353–54, 357
- foam, 103, 105, 108–9, 115–16, 123
 - surfactant-containing, 179
- formation water (FW), 86, 103–8, 113–14, 118, 121–22, 125–27, 129, 143–45, 188–89, 320, 368, 371, 386
- fouling, 353–54, 357, 359, 395, 398–99, 406, 412
 - colloidal, 353
 - irreversible, 354
 - organic, 353
 - reversible, 353
- Fourier transform infrared (FTIR), 129, 142–43, 398, 401, 404–5, 408–9
- fracturing, 50, 70, 88, 299, 355
- FSM, *see* flat sheet membrane
- FTIR, *see* Fourier transform infrared
- FW, *see* formation water
- gas, 32–33, 123, 133–35, 139, 143–44, 158–59, 164–65, 206–7, 240–41, 277, 288–91, 319–22, 341–44, 355–57, 385–87
- gas chromatography–mass spectrometry (GC-MS), 374–79, 383
- gas fields, 94, 299, 361
- gas–oil contact (GOC), 289
- gas permeability, 122, 128–29, 132–35, 144
- GC-MS, *see* gas chromatography–mass spectrometry
- gel strength (GS), 206–7, 212–14, 219, 229, 231–32, 241–44, 246, 250, 256
- geochemistry, 321, 386
- Geoscience software, 288, 296, 298

- Girujan clay, 31, 33–34
- Global Mapper software, 35
- GOC, *see* gas–oil contact
- grains, 7, 30, 50, 59, 68, 73, 75
 - constituent, 50
 - detrital, 68
 - fine, 303
 - framework, 50, 63, 68, 72
 - unconsolidated, 300
- grain size, 1–4, 7–9, 28, 38, 40, 59, 133, 188
- grain size analyses, 1, 4, 10–27, 30, 55
- greywacke, 31, 75
- GS, *see* gel strength

- hardness, 125, 320, 322, 324, 331–33, 339
- HC degradation, 309, 317
- HCPV, *see* hydrocarbon pore volume
- HCs, *see* hydrocarbons
 - aliphatic, 320, 388
 - free, 44
 - heavy-molecular-weight, 167
 - high-molecular-weight, 140, 165
 - low-molecular-weight, 167
 - recoverable, 289
 - toxic, 309
 - volatile, 344
- heavy metals, 320, 349, 371–74, 381–83, 388, 392, 402–3
- HFM, *see* hollow fibre membrane
- high-molecular-weight BSs, 169
- high-pressure high-temperature (HPHT), 205–7
- hollow fibre membrane (HFM), 352
- HPHT, *see* high-pressure high-temperature
- hydrocarbon pore volume (HCPV), 297
- hydrocarbons (HCs), 2, 29, 32–33, 44–47, 49–51, 288–89, 291, 297, 309–10, 312–14, 317–20, 342–43, 348, 351, 361–62, 372, 374–75, 379, 385–87
 - complex, 309
 - high-molecular-weight petroleum, 320
 - large, 188
 - prolific, 49
 - residual, 361
- hydrocyclones, 347
- hydrogen index, 33
- hydrolysis, 86, 89

- IBP, *see* initial boiling point
- IFT reduction, 79, 98, 107, 113, 164, 168–69, 172, 174–75, 177
- IFT, *see* interfacial tension
 - base, 108, 113
 - high, 167
 - low, 105, 110
 - oil/water, 113
 - ultra-low, 107
- illite, 136–37, 305
- immiscible phases, 348, 362
- inclination, 276, 278–79, 282, 284
- industrial wastewater, 402
- initial boiling point (IBP), 195
- interfacial tension (IFT), 78–79, 81, 89–90, 93–99, 103–8, 110–14, 118, 147–49, 151–53, 155–157, 159, 162–63, 169, 171, 173–74, 177, 185, 188, 312, 344, 362
 - high, 149
- iron NPs, 205–6, 208–17, 219–20

- JBN, *see* Johnson, Bossler and Neumann
- JN, *see* Jorajan

- Johnson, Bossler and Neumann (JBN), 109
- Jorajan (JN), 4, 6, 10, 199–200
- kaolinite, 136–37, 305
- kink bed, 35
- Klinkenberg effect, 133
- Klinkenberg principle, 129, 134
- kurtosis, 1, 7, 9, 39–41, 59
- Langelier saturation index (LSI), 320, 322, 328–30, 334–35
- Laplace equation, 163
- Leontaritis criterion, 141
- lipopeptides, 168–69, 172–73, 175, 316
- liquefied petroleum gas (LPG), 164
- liquid permeability, 128–29, 132–33, 135
- lithocolumn, 55, 57–58
- lithofacies, 49
- lithology, 30, 33, 52, 130
- litho unit, 33, 38, 43, 45
- LOBS, *see* lube oil base stock
- low-molecular-weight BSs, 169
- low-pressure low-temperature (LPLT), 206, 224, 243, 245
- LPG, *see* liquefied petroleum gas
- LPLT, *see* low-pressure low-temperature
- LSI, *see* Langelier saturation index
- lube oil base stock (LOBS), 194
- macroporous polymer extraction (MPPE), 395
- mango leaf extract (MLE), 240–41, 249–57
- marine conditions, 40, 59
- marine ecosystem, 331
- marine environment, 30, 35, 42, 47, 50, 62, 75
- marine sediments, 31, 310
- mass spectrometry, 374
- matrix, 28, 63–65, 72–73, 137, 207, 301, 304
- MBR, *see* membrane bioreactor
- MBR biofouling, 399–400
- MBR fouling, 399
- MBT, *see* methylene blue test
- MCCF, *see* mobility-controlled caustic flood
- MCT, *see* mud cake thickness
- measurement while drilling (MWD), 278, 286
- medium-gravity oil reservoirs, 125
- membrane antibiofouling, 398, 406
- membrane antifouling, 406
- membrane biofouling, 397, 401, 411–12
- membrane bioreactor (MBR), 397–99, 401–3
- membrane fouling, 353, 357–58, 391, 395, 399, 402
- membranes, 341, 343, 352–54, 357–59, 390–91, 395, 398–407, 409–12
- ceramic, 359
- composite, 352
- dense, 352
- flat sheet, 352
- fouled, 354
- hollow fibre, 352
- hydrophobic, 359
- ideal, 352
- nonporous, 391
- polymeric, 359
- porous, 352
- unmodified, 400–401, 406, 410–12
- membrane separation, 342, 352, 372, 390
- MEOR, *see* microbial enhanced oil recovery
- mesokurtic, 5, 9

- methylene blue test (MBT), 206, 217, 243
- microbial degradation, 309–10, 312, 314, 316–18, 351
- microbial enhanced oil recovery (MEOR), 157–58, 160, 162, 164–70, 172, 174, 176–78, 180, 182, 185–91
- microemulsions, 93–97, 99, 101–2, 109
- microfiltration, 390, 398–99
 - low-pressure, 341
- microfluidics, 148, 154
- microorganisms, 165, 167, 169–70, 182, 185–87, 189, 310–13, 315–17, 322, 390, 398, 402
 - anaerobic, 312
 - biosurfactant-producing, 309
 - indigenous, 165, 318
 - indigenous reservoir, 187, 189
- Microsoft Excel, 263, 275–76, 280–86
- mineralogy, 121, 126, 132, 136
- minerals, 136–37, 189, 335, 339, 351, 368, 386, 388
 - constituent, 53
 - detrital, 63
 - dissolved, 321, 388
 - dominant, 136
 - heavy, 63
 - micaceous, 63
 - radioactive, 320
 - secondary, 50
 - trace, 186, 189
- Miocene, 2, 31, 33, 52
- Mio-Pliocene, 4, 31
- mixed liquor suspended solids (MLSS), 406
- MLE, *see* mango leaf extract
- MLSS, *see* mixed liquor suspended solids
- mobility, 82, 87, 95, 162–64, 176, 358
- mobility-controlled caustic flood (MCCF), 112
- mobility ratio (MR), 77–78, 81–88, 90, 123, 163, 169
 - unfavourable, 163
- Mohr's method, 367
- MPPE, *see* macroporous polymer extraction
- MR, *see* mobility ratio
- mud, 73, 208–9, 213–14, 221, 223, 225–29, 232, 235–36, 240–41, 244–45, 247, 254, 278
 - bentonite-based, 209, 214
 - cone-shaped, 225
 - conventional, 215
 - efficient, 214
 - nanobased, 209
 - non-aqueous, 240
 - oil-based, 206, 240
 - reactive, 217
 - stable, 214
 - synthetic-based, 206
- mud balance, 208, 225, 242, 244, 246
- mud cake, 226, 232, 245
 - tough, 215, 217, 219, 223, 235–36
- mud cake thickness (MCT), 206, 214–16, 218–19, 226, 234–35, 243, 245–46, 249–51, 256
- MWD, *see* measurement while drilling
- Naharkatiya (NH), 4, 6, 12–13, 78, 90, 107
- nanobased mud (NBM), 209, 214, 217, 220
- nanoemulsions, 149
- nanofiltration (NF), 341, 352, 357, 390–91
- nanomud, 212–13
- nanoparticles (NPs), 149, 205–10, 212, 214, 217–20

- nanophotocatalysts, 394
- natural gases, 161, 164, 239, 241, 341, 386
- naturally occurring radioactive minerals (NORM), 319–20, 388, 392
- NBM, *see* nanobased mud
- neem leaf extract (NLE), 240, 249–57
- net-to-gross (NTG), 288, 290, 296–97
- Newtonian flow behaviour, 260, 272
- Newtonian fluid behaviour, 262
- Newtonian profile, 272
- NF, *see* nanofiltration
- NH, *see* Naharkatiya
- NLE, *see* neem leaf extract
- N,N*-dimethylformamide (DMF), 403–5, 409, 411–12
- non-Newtonian fluid
 - characteristics, 262
- non-Newtonian viscosity
 - behaviour, 259
- NORM, *see* naturally occurring radioactive minerals
- NPs, *see* nanoparticles
- NTG, *see* net-to-gross

- OBM, *see* oil-based mud
- OFAT, *see* one factor at a time
- OFPW, *see* oilfield produced water
 - carbonate, 329
 - high-quality, 356
 - saline, 333
 - treated, 343, 352, 355, 357–58
- OFPW-to-oil ratio (WOR), 342, 355, 387
- O&G, *see* oil and grease
- oil, 80–82, 93–95, 109–10, 115–16, 159–63, 185–88, 288–91, 310–11, 318–21, 347–48, 351, 355–57, 361–63, 386–89, 391–92
- oil and gas, 32–33, 94, 143, 159, 206, 240, 277, 288, 310, 319, 342, 355, 371, 385–86
- oil and grease (O&G) 319–20, 325–26, 331, 333, 357
- oil and water, 95, 159, 163, 167, 169, 174, 188, 344, 347, 362, 389
- oil-based mud (OBM), 206–7, 240
- cumulative, 177
- dense, 347
- dispersed, 343–45, 347, 371, 388
- displaces, 355
- dissolved, 320, 345, 387–88
- emulsified, 372
- entrapped, 174
- existing, 167
- extra, 175
- free, 372
- heavy, 158, 161, 164, 277
- kitchen waste, 178
- left, 185–86, 189–90
- liberate, 188
- light paraffin, 109
- lower, 357
- maximum, 163
- medium-gravity, 138
- producing, 342
- productive, 355
- recoverable, 290, 297
- releasing, 188
- silicon, 179
- soybean, 182
- soybean waste frying, 178
- stock tank, 290
- total, 300
- unburned, 162
- waste frying coconut, 178
- waxy, 262
- witnessed significant, 2

- oil-dispersed-in-water (o/w), 95, 345
- oil droplets, 149, 388
 - discrete, 343
- oilfield produced water (OFPW), 319–26, 328–31, 333, 335–39, 341–59, 371–72, 382, 385–95
- oilfields, 2–4, 126–27, 186, 299–300, 302, 304, 306, 308, 318–21, 323, 339–42, 360–62, 369, 385–86, 388–89
 - ageing, 300, 321
 - crude, 78
- oil flood, 110, 117
- oil industry, 123, 138, 164–65, 167, 191, 202, 205, 220, 320, 356
- oil recovery, 88, 94, 96, 100–102, 105, 121, 158–60, 162, 164, 166, 169, 174–76, 182, 185–89, 191
 - crude, 94, 158
 - enhanced, 157, 185–86
 - residual, 105, 117, 166
 - secondary, 78, 94
 - tertiary, 94, 161, 182
- oil reservoirs, 122, 126, 144, 148, 165, 312
 - carbonate, 190
 - depleted, 93
 - heavy, 162
 - high pour-point, 176
- oil spills, 311, 315
- oil viscosity, 125, 139, 162–63, 165
 - crude, 99, 139, 260
 - dead, 122, 129
- o/w, *see* oil-dispersed-in-water
- oil–water contact (OWC), 289, 294, 296
- oil/water interface, 105, 108
- oil–water interfacial tension, 123, 348
- oil wells, 2, 343
 - mature, 191
- oleic phases, 85, 98, 149, 153
- one factor at a time (OFAT), 178–79
- OOIP, *see* original oil in place
- optimum surfactant combination, 154
- organic compounds, 194, 312, 315, 357–58, 372, 374, 387–88
 - dissolved, 344, 351
- organic matter, 30, 33, 46–47, 350, 391, 399
 - mature-source, 46
- original oil in place (OOIP), 84, 87, 149, 161, 176, 185–86
- overburden pressure, 101, 132
- OWC, *see* oil–water contact
- oxidation, 349–52, 410
- PAHs, *see* polycyclic aromatic hydrocarbons
- particle size analyser (PSA), 206, 208–9, 373
- particle sizes, 40, 94, 97, 99–102, 149, 209, 211, 242, 345–46, 352, 372–73, 375, 379, 381–83
- Pashiyskiy formation, 291
- PC, *see* potassium carbonate
- PCPs, *see* physicochemical parameters
- PEG, *see* polyethylene glycol
- PEG4000, 224–25, 227–29, 232, 235–36
- PEG mud, 229–31, 233–34
- permeability, 117, 121–22, 126, 130, 132–35, 144, 157, 164, 167, 188, 191, 303, 307
 - absolute, 109
 - air, 106, 109
 - effective, 110, 163
 - high retained, 301
 - horizontal, 130, 276
 - increased, 303

- initial, 354
- low, 241
- poor, 167
- vertical, 276
- permeate flux, 353, 357, 359, 399
- petroleum, 158, 161, 164, 182, 187–88, 193–95, 200, 202, 287–89, 309–10, 315, 318–19, 323–25, 351, 354–55
- petroleum and natural gas (PNG), 161
- petroleum HCs, 310, 389
- phase behaviour, 94, 97, 99, 101, 144
- phospholipids, 169, 173, 316
- photocatalysis, 393
- photocatalyst, 349
- photoelectrocatalysis, 393
- photoelectrochemistry, 393, 395–96
- photoelectrolysis, 393–94
- photoelectron catalysis, 349
- physicochemical parameters (PCPs), 374, 379–80
- physicochemical properties, 126, 138, 159
- PI, *see* production index
- plant extracts, 239, 242, 245, 249–50, 254, 256–57
- plastic viscosity, 206, 210–14, 219, 226, 229–30, 232, 244, 246–47, 249–57
- platykurtic, 5–6, 8–9, 30
- plugs, 82, 128
- PNG, *see* petroleum and natural gas
- pollutants, 313, 321, 348, 350–51, 359
 - common HC, 309
 - inorganic, 341–42, 372
 - organic, 309–10, 312, 372
 - organic toxic, 312
 - petroleum HC, 310
- pollution, 164, 315, 321, 354, 356, 372
 - environmental, 313
 - secondary, 158, 164
- polycyclic aromatic hydrocarbons (PAHs), 313, 344, 371, 379, 387–88
- polyethylene glycol (PEG), 179, 221–25, 230–34, 236
- polymer flooding, 84, 87–88, 90
- polymers, 77–78, 80, 83, 87–90, 149, 158, 163, 169, 205, 207, 222–23, 228, 232, 235, 240
 - alkali or/and, 79
 - water-soluble, 188
- polysaccharides, 169, 187–88, 353, 407, 410–11
- pores, 148–49, 159, 353, 386
- pore sizes, 352, 391
- pore spaces, 32, 71–73, 128, 130, 223
- pore volume (PV), 77, 80, 87, 118, 128, 206, 212–13, 290, 297
- porosity, 49–50, 53, 56, 62–63, 68–75, 106, 109, 121–22, 126, 128, 130–34, 144, 288, 290, 296–97
 - average, 50–51, 62, 75, 291
 - effective, 130
 - fracture, 68
 - high, 132, 352
 - interconnected, 2
- potassium carbonate (PC), 403–12
- Precambrian rocks, 4
- produced water (PW), 163, 309, 318–21, 331, 340, 357, 360–63, 368–69, 371–75, 382, 385–87, 390, 393–96
- production index (PI), 45–47
- propan-2-ol, 94, 96–102
- PSA, *see* particle size analyser
- pseudomatrix, 68–69, 73–75
- PSI, *see* Puckorius scaling index

- Puckorius scaling index (PSI), 320, 322, 336–37
- PV, *see* pore volume
- PW, *see* produced water
- QS, *see* quorum sensing
- QSI, *see* quorum sensing inhibiting
- quorum sensing (QS), 397, 399, 401, 410
- Quorum sensing inhibiting (QSI), 397–98, 401, 412
- R/A, *see* resin-to-asphaltene
- Raman shift, 407
- Raman spectra, 405, 407
- Raman spectroscopy, 407–11
- raw effluent, 375, 379–83
- recovery, 77–79, 81, 83–84, 87, 110, 137, 139–40, 148–49, 162–64, 167, 169, 182, 339–40, 360, 395–96
 - effective, 159
 - maximum, 78, 87, 90
 - metal, 395
 - poor, 163
 - primary, 94, 161
 - secondary, 83, 94, 104, 141
 - significant, 162
 - tertiary, 94
- reduction, 75, 78–79, 108, 111, 113, 163, 165, 168, 206, 351, 353, 355, 357, 395, 411–12
- regulations, 352, 354, 368
 - environmental, 354, 398
 - re-injection, 352
- relative permeability, 82, 110, 123, 130, 163
- removal, 342, 351, 357, 372, 383, 391–92, 409
 - complete, 312
- reservoir conditions, 82, 126, 158–60, 164, 186–87, 189, 191
 - anaerobic, 166
 - extreme, 191
- reservoir pressure, 127, 161, 165, 169, 188, 320, 355
- reservoir rocks, 1–2, 4, 6, 8, 10, 12, 28–29, 75, 104–5, 121–24, 126, 130, 136–38, 144, 368
 - carbonate, 368
 - moderate-quality, 50
 - sandstone, 125
- reservoirs, 78–79, 121–23, 141–43, 160–63, 165–69, 176, 187–89, 276–77, 287–89, 291, 293–94, 296–97, 299–300, 319–20, 385–86
- reservoir temperature, 90, 104, 111–13, 115, 117–18, 125, 138–39, 141, 291
- residual oil, 78, 94, 105, 109–10, 112, 117–18, 123, 162
- resins, 121, 126, 129, 137–38, 140–41, 300–301, 348, 351
 - epoxy, 301
 - formaldehyde, 301
 - furan, 301
 - polyester, 301
 - urethane, 301
- resin-to-asphaltene (R/A), 122, 137–38, 141, 145
- resistance, 235, 259, 272, 301, 411
 - bacterial, 399
 - corrosion, 322
 - mechanical, 352
- response surface methodology (RSM), 179–80
- retention, 63, 112, 372, 379, 382, 401, 404
- reverse osmosis (RO), 341, 352, 357–58, 390–91, 400
 - polyamide, 400

- rhamnolipids, 170–71, 173–75, 177, 181–82, 315
- rheological properties, 206, 208, 210, 212–13, 219–20, 222, 226, 229, 232, 235, 240–41, 246, 256–57, 263
- Riazi–Daubert method, 196–97
- RO, *see* reverse osmosis
- rock-eval pyrolysis, 33, 42, 46
- rock fragments, 50, 63, 65, 68, 304
 - sedimentary, 65
- rock plugs, 132, 159, 162–63
- rocks, 29–30, 32–33, 44–45, 47, 50–51, 55, 59, 62–64, 75, 122–23, 130, 136–37, 185–86, 345, 386
 - low-grade metamorphic, 73
 - native, 223
 - porous, 122, 133, 320
 - sedimentary, 345
- rock–water interaction, 345
- RO membranes, 357, 391
- rRNA sequencing, 311–12
- RS, *see* Rudrasagar
- RSI, *see* Ryznar stability index
- RSM, *see* response surface methodology
- Rudrasagar (RS), 6, 17–18
- Ryznar index, 336
- Ryznar stability index (RSI), 320, 322, 328, 330, 335–36

- salinity, 97, 99, 105, 108, 113–15, 143–45, 176–77, 180, 186, 188–89, 191, 320–21, 323–24, 331–33, 402
 - high, 339
 - optimal, 112
- sand, 3, 5–6, 9, 299–302, 304–7, 344, 372–73, 375, 381–82, 389
 - coarse-grained, 7
 - dry, 302
 - fine, 300
 - fine-grained, 1, 7
- sand control method, 300
- sand filtration, 371, 374, 382
- sand pack, 174–75, 301–3, 307
- sandstone, 30–31, 33, 35, 38, 47, 49–50, 52–54, 57–58, 63, 125, 127, 134, 137, 304, 307
 - gritty, 33
 - massive, 34
 - wacke-type, 50
- SBM, *see* synthetic-based mud
- Schuppen Belt, 3, 29, 32
- SFB, *see* synthetic formation brine
- synthetic-based mud (SBM), 206–7
- synthetic formation brine (SFB), 143–44

- Taguchi method, 179–80
- TBP, *see* true boiling point
- TBP distillation, 194, 196–97, 202
- TDS, *see* total dissolved solids
- tectonics, 31, 51
- TGA, *see* thermogravimetric analysis
- thermogravimetric analysis (TGA), 82, 90, 106, 109
- thixotropy, 262
- Tipam Group, 32–33
- Tipam oilfield, 300–301
- Tipam reservoir sandstone, 305
- Tipam sand, 127
- Tipam sandstone, 31, 33–34
- TMP, *see* transmembrane pressure
- TOC, *see* total organic carbon
- total dissolved solids (TDS), 114, 129, 143, 320, 322–24, 328, 330–32, 339, 357, 362, 367
- total organic carbon (TOC), 30, 42–45, 47, 358, 392
- total petroleum hydrocarbons (TPH), 371–76, 378–83

- toxic compounds, 319–20, 349, 358, 402–3
 - undetected, 358
 - unknown, 358
- toxicity, 159, 164, 223, 346, 349, 351, 358
 - combined chronic, 357
 - low, 157, 167, 169, 313
 - potential chronic, 357
- TPH, *see* total petroleum hydrocarbons
- transmembrane pressure (TMP), 353, 391, 399
- trapped oil, 105, 158, 161–62, 164–65, 182, 186
- treatment, 110, 177, 341–54, 356–60, 371–72, 385–88, 390, 392, 394–97, 406
 - additional physicochemical, 403
 - biological, 350–52, 402
 - chemical consolidation, 300, 307
 - improper, 369
 - industrial waste, 350
 - poor, 391
 - preliminary, 319
 - primary, 372
 - sand filter, 346
- true boiling point (TBP), 193–202
- Tuli–Mokokchung Road, 29, 33
- Tunisian standards, 371–72, 374, 382–83
- turbidity, 59, 62, 114, 320, 323–24, 331–32, 339, 374–75, 380–81, 391, 402
- UF, *see* ultrafiltration
- ultrafiltration (UF), 341, 352, 357, 390–91, 399
- ultralow interfacial tensions, 93, 95, 98, 102, 105, 108, 111–12
- ultraviolet (UV), 349
- undersaturated water, 328, 330, 334–35
- Upper Assam, 51, 77, 79, 94, 103, 107, 110, 121, 126, 131, 133, 139, 144, 262, 299
- Upper Assam Basin, 1–4, 6, 8, 10, 12, 14, 28–29, 77–80, 90–91, 93, 102–3, 156, 299–302, 319, 339
- Upper Cretaceous, 31
- Upper Jurassic, 31
- Upper Paleocene, 4
- Urals Basin, 290–91
- UV, *see* ultraviolet
- UV-visible spectrophotometer, 206, 208–9
- VA, *see* vanillin
- VA-modified membranes, 398, 400, 406, 410
- vanillin (VA), 398–401, 403–12
- viscosity, 89–90, 93–94, 99, 132, 139, 162–64, 169, 188, 222–23, 225–26, 228, 241–43, 251–53, 259–66, 269–72
 - apparent, 82, 123, 206, 226, 228, 235, 244, 246–47, 262
 - dead-oil, 144
 - dynamic, 138–40, 263
 - effective, 226, 228, 235, 244
 - high, 140, 167
 - kinematic, 97
- Visual Basic, 276, 280–81, 285
- VOCs, *see* volatile organic compounds
- volatile organic compounds (VOCs), 348, 402
- volatile suspended solids (VSS), 406
- VSS, *see* volatile suspended solids
- WAG, *see* water-alternating gas

- wastewater, 390, 392–93, 398
 - industrial, 391
 - municipal, 402
 - polluted, 382
 - strong, 402
- wastewater treatment plants,
 - 397–98, 412
 - industrial, 399
- water
 - condensed, 320
 - conductive, 322
 - dense, 347
 - emulsified, 195
 - excess, 93
 - free, 195
 - fresh, 223, 356, 386, 395
 - ground, 223, 321
 - high, 321
 - hot, 158, 162
 - ice, 245
 - irrigation, 358
 - meteoric, 345
 - oilfield, 339, 343, 360
 - saline, 160, 163
 - saturated salt, 223
 - supersaturated, 335
 - surface, 386
 - treated, 351, 356
 - warm, 331
- water-alternating gas (WAG), 123
- water analyser, 129, 243, 245–46, 323
- water backwashing, 353
- water-based drilling fluid (WBDF),
 - 221, 223, 239, 241
- water-based drilling mud, 224,
 - 239, 242, 244–45
- water-based mud (WBM), 206,
 - 217, 221–24, 226, 228, 230, 232, 234, 236, 240–42
- water bodies, 321, 331, 354, 356
- water desalination, 391
- water-dispersed-in-oil (w/o), 95
- water electrolysis, 393, 395
- water flooding, 140, 174, 188, 320
 - field-scale, 110
- water floods, 109, 117–18
- water phase, 89, 95, 105, 348
 - excess, 95
- water quality, 321–22, 333, 353,
 - 356, 358, 362, 392
 - filtered, 346
 - high effluent, 397
 - stable effluent, 399
 - treated, 398
- water resources, 322, 342
- water saturation, 290, 296, 305, 307
 - connate, 110
 - increased, 304
 - irreducible, 80, 109
- water-to-gas ratio (WGR), 387
- water treatment, 363, 410
 - oily, 390
- wax content, 122, 126, 129, 138, 140–41, 144
- wax crystallisation, 260
- wax crystals, 259
- waxes, 259–62, 389
- WBDF, *see* water-based drilling fluid
- WBM, *see* water-based mud
- well, 176, 222, 259, 262, 277, 288, 299, 355, 362–63, 367
 - freshwater, 362
 - marginal, 190
 - relief, 277
 - vertical injection, 162
- wellbore, 88, 141, 190, 222, 236, 239, 275–77, 279–81, 286, 299–300, 344
 - stable, 223
- wettability, 79, 81, 90, 94, 97, 104, 130, 157, 162, 167, 174–75, 177
- WGR, water-to-gas ratio

- WHO, *see* World Health Organization
- Williamson ether reaction, 398, 401, 403–4, 407
- Winsor classification, 94–95, 97
- Winsor type I, 95
- Winsor type II, 95
- Winsor type III, 93, 95, 97, 99
- Winsor type IV, 95
- w/o, *see* water-dispersed-in-oil
- WOR, *see* OFPW-to-oil ratio
- World Health Organization (WHO), 322, 330–31, 333, 339

- X-ray diffraction (XRD), 121–22, 126, 136, 144, 302, 306, 373
- XRD, *see* X-ray diffraction

- Yellow River Delta of China, 379

- yield point (YP), 206, 212–14, 219, 226, 229–32, 244, 246, 250, 254–57
- yield stress, 241, 259, 262
- YP, *see* yield point

- zeolites, 348, 372, 392
- Zepuhu formation, 31
- zone, 127, 276, 289–90
 - higher-pressure, 247
 - higher-to lower-permeability, 123
 - high-permeable, 182
 - low-permeable, 182
 - nonpay, 320
 - oil-producing, 127
 - permeable, 159, 214
 - permeable non-HC-bearing, 355
 - sand-prone, 301
 - transitional, 33

“Advances in Petroleum Technology is a book suitable for researchers, students, academicians and oilfield personnel who are interested in knowing the progress in basic and applied research work on various topics in petroleum engineering, ranging from developments in petroleum geology, drilling fluids and produced water treatment and re-injection to flow assurance issues, enhanced oil recovery techniques with carbon dioxide, surfactants and microemulsions. I am confident that the results presented in the book will be useful for field applications, too.”

Prof. Tarkeshwar Kumar

Indian Institute of Technology (Indian School of Mines), India

An impending energy crisis is looming globally, which has led to the use of effluents from paper mills for enhanced oil recovery (EOR), CO₂ flooding and wastewater treatment by biosurfactants, and the current market demand for cost-competitive and environment-friendly alternatives to synthetic chemicals. This up-to-date book on petroleum technology provides a comprehensive review of the background and recent advances in the field of petroleum technology and highlights various facets of the fascinating world of upstream, midstream and downstream petroleum technologies. It comprises 25 chapters, each representing the progress, prospects and challenges in petroleum research, and focuses on the tremendous progress made by the scientific community in this research field. The book covers in detail EOR processes, reservoir engineering, production operation and optimisation, pipeline transportation and storage, CO₂ capture and sequestration, wastewater management and innovative treatment, refining technologies, environmental chemistry, and biochemistry and biotechnology for the petroleum industry.



Subrata Borgohain Gogoi is professor of petroleum technology at Dibrugarh University, India, since 1994, before which she served as technical services engineer at Bongaigoan Refinery and Petrochemicals Limited, Assam. She obtained her MTech in chemical engineering and PhD in petroleum technology.

She successfully completed four major research projects as principal investigator (PI), the most prestigious of which was the Indo–U.S. 21st Century Knowledge Initiative project with the Department of Petroleum Engineering, University of Louisiana at Lafayette, USA. Currently, she is also working as the Indian PI for three international projects and three national projects funded by the Government of India. Prof. Gogoi is a reviewer for 12 international journals and has authored 1 book. Her current research interests include EOR leading to CO₂ sequestration and application of nanotechnology for oilfield-produced water (OPFW) treatment. Her EOR group is engaged in characterising reservoir fluids and rocks for formulating EOR slugs for application in depleted reservoirs, both nationally and globally, and in validating experimental findings of the research through simulation and modelling. Her OPFW group is developing membrane-based treatment technologies and working on bioremediation and the evaluation of the corrosion and scaling potential of OPFW.



JENNY STANFORD
PUBLISHING

