

# Index

- abrupt depletion approximation 310–11, 318
- access resistance 17, 276, 288, 297
- ACL (amorphous carbon layer) 34–35, 42, 44, 48–49, 53
- advanced transport modelling 330–31, 333, 335
- ALD (atomic layer deposition) 62, 64–65, 98, 106, 129, 139, 142, 147, 235
- ALD TiN electrode 124, 127–28, 133
- amorphous carbon layer *see* ACL
- annealing 95, 97, 162, 165, 381
- atomic layer deposition *see* ALD
- atomic vapor deposition *see* AVD
- AVD (atomic vapor deposition) 94, 139–40
  
- ballistic current 346–47, 349, 351, 353, 355–56
- ballistic transport in ultrashort thin junctionless nanowires 325, 327, 329
- band alignment 117–18, 123–24, 127, 130–31, 136
- band alignment dependence 128, 130, 133, 135
- band edge 366, 403–4
- BARC (bottom anti-reflective coating) 32–33, 50
- basic ESD protection devices 264
  
- bipolar mode 269–74, 277–78, 281–86, 289–91, 293–96
  - parasitic 268–69
- boron 17, 59, 79–81, 145, 162, 165, 172, 275, 277, 290
- bottom anti-reflective coating *see* BARC
- breakdown voltage 123, 279–80
- bulk FinFETs 10–11, 152–53, 157–58
- bulk mobility 306, 317–18
- bulk tri-gate device 11
  
- capacitive coupling, characteristics
  - gate channel 373
- capping layer 92–93, 105–8, 110, 146
- caps, rare-earth oxide-based 105
- CB (Coulomb blockade) 363, 367, 369, 372–73
- CD (critical dimension) 12, 14, 29, 33, 35–38, 41–42, 46, 49–50, 52, 67, 385
- cells, galvanic 69–70
- channel
  - homogenous 334–35
  - long 130, 310, 366
  - parasitic 155
  - short 85, 235, 334
  - undoped 185, 362, 370, 384
- channel barrier height 372, 378
- channel confinement 57, 177
- channel control 13, 250

- channel dopants 155, 158
- channel doping 15, 59, 77–78, 81, 124, 134, 151, 155
- channel implants 15, 19
- channel mobility 19, 103, 117, 151
  - low-field 77, 79–80, 88, 91, 101, 107–8, 110
- channel orientation 178, 378, 381, 396
- channel resistance 156, 297
- channel strain 156, 176–77, 179
- channel tapering 212–13
- CMOS (complementary-metal-oxide-semiconductor) 151, 261, 401
- CMOS devices 28, 409
  - dual-gate 141
- complementary-metal-oxide-semiconductor *see* CMOS
- conductance 364–66, 370, 376
  - differential 363–64, 366–67, 371, 404–5
  - ohmic channel 334–35
- conduction 125, 202, 207–8, 214, 217, 222–23, 320, 375, 379
- conformal doping 159, 162–63, 181
- contact resistance 17, 171–73, 288–89
- Coulomb blockade *see* CB
- crystal orientation 19, 61, 136, 167, 177–78, 186, 188, 190, 206–7, 222, 292, 294
  
- DARC (dielectric anti-reflective coating) 32, 35, 42
- decoupled plasma nitridation *see* DPN
- device failure 267, 269
- device threshold 196, 200, 205, 225–26
- device threshold voltage 185
  
- devices
  - complementary 159, 163
  - doped 239, 243, 363, 372
  - double gate 9
  - long-channel 6, 89, 124, 235
  - multiple-gate 24, 136, 228, 236, 239, 241
  - nanowire 21, 306, 312, 346
  - parasitic 264
  - pFET 91, 104, 127–28
  - pi-gate 5
  - planar bulk 16, 19–20
  - resist-defined 199–200
  - short-channel 6–7, 254
  - simulated 375, 386
  - single-fin 217, 220, 223, 226
  - tri-gate 5
  - triple-gate 238
  - ultra-scaled 362, 379
- DIBL (drain-induced barrier lowering) 5–6, 101, 150–51, 154, 156, 158
- dielectric anti-reflective coating *see* DARC
- dielectric capping 91–92, 147
- dielectric caps 92–93, 104–5, 127
- donors, ionized 306–7, 310, 343, 345
- dopant atoms 152, 162, 164–65, 187
- dopants 156, 158–59, 162–65, 172–73, 400–1, 409
- doped FinFET devices 363
- doping 77–81, 141, 149–50, 152, 154–56, 158, 160, 162, 164, 166, 168, 170, 172–74, 176, 317–18
  - vapor phase 18, 162
- doping density 306, 310, 312, 317–18, 327–28
- dot/gate capacitance 368–69
- DPN (decoupled plasma nitridation) 86–92, 139

- drain-induced barrier lowering *see* DIBL
- drift-diffusion approximations 334–35
- effective oxide thickness *see* EOT
- effective work function 65, 82, 85, 91–92, 111, 125, 141, 145–46
- electrolytic solution 70, 72
- electromagnetic field 341–42, 357
- electron density 82, 315, 320–22, 327, 359
- electronegativity 69–70, 82, 91–93, 106, 142
- electrostatic discharge *see* ESD
- EOT (effective oxide thickness) 98–99, 119–25, 127, 129, 235
- EOT independence 127–29
- epitaxial growth 163, 168, 170, 173–74
- epitaxy 163, 168–69, 174, 176
- ESD (electrostatic discharge) 261–66, 295, 298
- ESD protection device 267
- ESD robustness 261, 268, 274–75, 282, 285, 288, 292, 294
- ESD stress 263, 266, 269
- experiments, carrier separation 123, 126, 131–32
- extension concentrations 194, 209–10
- extension doping 208–9, 226
- extension regions 151, 158, 165, 170, 176, 212
- extension resistance 151, 155, 214
- Fermi level 82, 137–38, 307, 320–21
- FET (field-effect transistor) 26–27, 75, 105, 131, 134, 139, 141, 251, 336, 341, 346, 362, 382, 391–92, 400
- FET, short channel 58, 130
- field-effect transistor *see* FET
- fin patterning 11–13, 19, 33, 35, 37–39, 41, 43, 45, 47, 49–53, 136
- fin pitch 10, 14, 32–33, 36, 38–39, 49–50, 52–53, 86, 160–62, 176, 290
- fin profile 36, 38, 46–47, 52
- fin sidewalls 38, 44, 61, 67–68, 169, 191, 226
- fin spacing 13, 175, 262, 278, 290–91
- fin width 13, 17–19, 59, 79, 155, 165–66, 172, 200–1, 234–42, 248–49, 255–56, 277–78, 280–81, 287–92, 295–96
- FinFET architecture 29, 38, 149, 157
- FinFET-based multi-gate devices 4, 10, 22
- FinFET design 190, 206
- FinFET devices 9, 25, 32, 147, 189, 215, 232, 252, 261, 268, 277–78, 281, 294–95, 297–98, 402–3
  - narrow N-type 296
  - undoped 370
  - wide fin 273–74
  - wide fin N-type 271
  - wide fin P-type 272
- FinFET SRAM 217, 220–21, 230, 232
- FinFET SRAM cells 229–30
- FinFET threshold voltage 202, 204
- FinFET variability 189–90, 214
- FinFETs 4–5, 26, 153–54, 162–63, 173–75, 179–82, 185–86, 194–95, 225–29, 236–37, 239–42, 247–56, 380–84, 386, 388–94
  - doped channel 369
  - narrow-fin 217, 247, 254
  - p-type 208

- FinFETs (*Contd.*)
  - undoped 370, 374–75, 377–79
  - undoped channel 369, 372
- fins 9–15, 17–22, 32–33, 44–48, 136–37, 159–61, 166–69, 197–99, 207–11, 217–18, 226, 268–74, 277–79, 282–85, 287–97
- fixed and trapped charge *see* FTC
- flat-band voltage 119, 121, 133
- flat-band voltage extraction in SOI MuGFETs 117, 119, 121, 123, 125, 127, 129, 131, 133, 135, 137, 139
- floating body devices 123, 156
- floating body effect, gate-induced 137
- FTC (fixed and trapped charge) 188–89
  
- galvanic corrosion 69–70, 144
- gate bias 123, 125, 305, 310, 389–90, 395
- gate capacitance 15, 63, 80, 90, 102, 109–10, 133, 368
- gate dielectric composition 65
- gate dielectric integrity 62, 105
- gate dielectric nitridation 76, 86
- gate dielectrics, ultra-thin 117, 129–30
- gate electrodes 16, 59, 61, 86–87, 100, 102, 108, 118, 124–28, 147, 235, 240, 288
  - dielectrics/metal 57
- gate electrodes in MuGFETs 58–59, 61, 63, 65, 67, 69, 71, 73
- gate hardmask 163, 169–70
- gate-induced drain leakage *see* GIDL
- gate leakage 72, 84, 90, 92, 112, 122–24, 127–28, 130, 133, 135–37, 286
- gate leakage dependence 99, 123
- gate leakage evolution 122, 124
- gate oxide 60, 72–73, 75, 82–83, 87, 90, 97, 105, 112, 120, 122, 136, 138, 141, 145
  - ultra-thin 137, 140
- gate-oxide breakdown 273, 283, 293
- gate oxide integrity 75, 83, 91, 105
- gate patterning 5, 22, 63, 73, 152, 157–58, 163
- gate plane 153, 171
- gate sidewall 163
- gate stacks, high-k/metal 153, 233
- gate-to-channel coupling 375
- gate voltage 6, 21, 80, 90, 102, 114, 124–26, 129, 131–32, 249, 306–10, 316–17, 363–66, 370, 403
- gated diodes 262, 268–69, 273, 276, 279–80, 285–87, 297
- geometrical dependencies 269, 271, 273, 275, 277, 279, 281, 283, 285, 287
- geometry, triple-gate 362, 365
- GIDL (gate-induced drain leakage) 17–18, 25, 156, 173, 180, 299
- gradual channel approximations 310, 312
- grounded-gate NMOS 264–66
  
- halo formation 158–59, 161, 163, 165, 167
- hard mask 10, 13, 32–36, 39, 49, 54, 66–69, 71, 74–75, 195, 288, 402
- hard mask removal 68, 70–71, 73–74
- HDD (highly doped drain) 150–51, 170–73, 175–76, 235
- HDD regions 151, 156, 169–70, 173–76
- HF-diluted solutions 69, 71–72, 74
- highly doped drain *see* HDD

- holding voltage 264, 270, 273, 276, 278, 296
- hole mobility 27, 174, 176, 178–79, 195, 337
- interface states 113–14, 136, 374, 378, 395
- interface traps 380, 384–87, 389–90, 395–96, 400
- inversion charge 244–45, 390
- inversion mode MOSFET
  - nanowires 303–4, 325, 328–29
- ion deflection 46–49, 52
- ion implantation 75, 77, 80, 85, 94, 145, 158, 161–62, 169, 180
- ionized impurity scattering 155, 323–25
- JFET (junction Field Effect Transistor) 304–6
- junction field effect transistor *see* JFET
- junctionless nanowire 307, 319, 321–22, 325, 329–30, 337
- junctionless nanowire POFET 333–35
- junctionless nanowire transistor 303–4, 306–10, 312–14, 316–18, 320, 322, 324, 326, 328, 330–36
- Lambert W-function 312, 314–15, 336
- LDD (lightly doped drain) 151, 262
- leakage, gate-induced drain 17, 25, 156, 173, 180
- leakage current 156, 267, 293–94, 347, 359
- LER (line-edge roughness) 186–97, 200, 203, 206, 208–10, 214–15, 217, 223, 225–26, 228, 231
- LER-induced variability 193, 204, 206–8, 226
- lightly doped drain *see* LDD
- line-edge roughness *see* LER
- line width roughness *see* LWR
- lithography 5, 32–36, 39, 49, 51, 54, 66–67
- long-channel approximations 310, 319
- LWR (line width roughness) 14, 191–92
- metal gate deposition 61, 137
- metal gate electrodes 61, 75, 83, 104, 107, 110, 115, 141, 145, 153
- metal gates 15–16, 20, 23, 26–27, 58, 61, 63, 69–71, 73, 75, 92–93, 97–98, 126–27, 132, 134
- metal-organic chemical vapor deposition *see* MOCVD
- metal-oxide-semiconductor field-effect transistor *see* MOSFET
- MLDA (modified local density approach) 348, 357
- mobility variation 195, 334–35
- MOCVD (metal-organic chemical vapor deposition) 62, 94, 98, 129, 139, 235
- MOCVD TiN 62, 83, 85, 98–100, 102, 135, 145
- MOCVD TiN gate electrode 83, 101–2, 104, 135
- MOS capacitors 63–64, 98–99, 118
- MOS devices 147, 268–69, 286
  - grounded gate 297
- MOS diode 286–87

- MOSFET (metal-oxide-semiconductor field-effect transistor) 3, 5, 25, 58, 125, 133, 138, 150, 231, 236, 246, 306, 329, 346, 385
- MOSFET devices, short channel 304
- MOSFET nanowire 328–30
- MOSFET transistor 138, 316
- MuGFET devices 15, 19–20, 26, 60, 66–67, 70, 81, 83, 99, 112, 118
- MuGFET fabrication 12, 70, 105, 108
- MuGFETs (multiple gate FETs) 3–4, 16, 57–61, 65–67, 71–73, 76–79, 86–93, 98–102, 104–5, 108–11, 117–18, 122–23, 133–37, 233–34, 242
- MuGFETs, narrow 74, 78, 81, 133, 135, 142
- multi-finger devices 235, 282
- multi-gate devices 3, 5–6, 13, 19, 22, 24, 26, 188, 298
  
- nanowire MOSFET 304, 317, 333–35
- nanowires 21–22, 317, 325, 329, 336
  - gated silicon 337, 412
- narrow fin devices 17, 101, 162, 269, 272, 276, 288, 291–94, 297
- narrow fin NMOS devices 272, 275–76
- nitridation 86–87, 89, 91
- nitrogen 63, 92, 116–17, 141, 143
- NMOS 6, 16–17, 20, 154, 156, 159, 171, 178–79, 271, 273–78, 281–85, 288, 290–92, 294–96
  - narrow fin 271, 273–74
- NMOS devices 18–19, 154, 177, 275–76, 278–79, 283, 295–96
- NMOS FinFET devices 294
  
- OTV (oxide thickness variation) 187–89
- oxide thickness variation *see* OTV
  
- photoresist 66–67, 76–77, 91, 187, 190
- physical vapor deposition *see* PVD
- planar CMOS technologies 156–58, 170
- planar devices 8–9, 15, 117, 135, 267, 277
- planar MOSFETs 59, 65, 67, 71, 76, 82–83, 87, 93, 104, 133, 135, 188–89
- planar pFETs 129, 135–36
- plasma doping 18, 162, 181
- PMOS 16–17, 19–20, 156, 159, 178–80, 271, 275–76, 278, 282–85, 288, 290, 294–95
  - narrow fin 273–74
  - wide fin 273–74
- PMOS FinFET devices 269, 288
- pMOSFET 126, 132
- PNA (post-nitridation anneal) 87–88
- poly-silicon granularity *see* PSG
- polysilicon 18, 66–68, 70–72, 74, 98, 125, 129, 135, 187–88
- polysilicon corrosion 69–71, 73–74
- polysilicon degradation 72
- polysilicon films 61, 67, 69, 71, 75
- polysilicon gates 58–59, 64, 69–70, 75, 127
- polysilicon layers 69–70
- polysilicon patterning 66–67, 70–71, 74
- polysilicon spacers 67–68
- post-nitridation anneal *see* PNA
- PSG (poly-silicon granularity) 187–89
- PVD (physical vapor deposition) 62, 94–96

- QTBM (quantum transmitting boundary method) 326–28, 337  
 quantum dots 367, 403–4  
 quantum transmitting boundary method *see* QTBM  
  
 random discrete dopants *see* RDD  
 rapid thermal annealing *see* RTA  
 RDD (random discrete dopants) 187–89  
 RTA (rapid thermal annealing) 146, 165, 167  
  
 salicidation 153, 170–71, 173, 175  
 SB *see* silicide blocking  
 scanning electron microscope *see* SEM  
 SCEs (short-channel effects) 4–5, 8–9, 29, 188, 233, 281, 372–73  
 SEG (selective epitaxial growth) 12, 17–18, 26, 74, 118, 153, 163, 169–71, 173–77, 235, 262, 275, 288–93, 297–98  
 selective epitaxial growth *see* SEG  
 SEM (scanning electron microscope) 47–48, 191–92, 371, 378  
 semiconductors 7–8, 118–19, 138, 140, 156, 158, 337, 343, 357, 359  
 sensitivity analysis 186, 196, 200–1, 205–7, 215, 225–26  
 shallow-trench-isolation *see* STI  
 short-channel effects 29, 57, 59, 209, 362  
   *see* SCEs  
 side wall roughness *see* SWR  
 silicidation, self-aligned 157, 170  
 silicide 17, 154, 170–74, 187, 262, 275, 286, 292–94  
 silicide blocking (SB) 164, 181, 262, 275, 285, 288, 292–94, 297  
 silicon on insulator *see* SOI  
 SNM (static noise margin) 215–16, 218–24, 226  
 softlanding 40, 42–49, 52, 54  
 SOI (silicon on insulator) 4, 11–12, 20, 34, 50, 57–58, 118, 122–23, 133–35, 153, 157, 181, 233, 299  
 SOI FinFET 152–53, 156–57, 170–71, 175  
 SOI FinFET device architectures 152  
 solid-phase epitaxy *see* SPE  
 SPE (solid-phase epitaxy) 18, 166  
 SRAM (static random access memory) 13, 19, 159, 186, 214, 217, 220, 224, 226, 229  
 SRAM stability 220, 222–23  
 static noise margin *see* SNM  
 static random access memory *see* SRAM  
 STI (shallow-trench-isolation) 5, 10, 152, 174, 265–66  
 strain 12, 19–20, 22, 24, 26, 117, 156, 176, 178–79, 182, 187, 262, 285–86, 294–97, 330–32  
 strain architectures 149–50, 152, 154, 156, 158, 160, 162, 164, 166, 168, 170, 172, 174, 176, 178  
 strain in NMOS devices 177  
 strain tensors 177, 332  
 structures, multiple-gate 185, 188  
 SWR (side wall roughness) 38, 40–41, 43, 45–46  
  
 TaCN-based metals 94–95, 97  
 TEM (transmission electron microscopy) 40, 47, 49, 52, 72, 153, 170–71

- tensile strain 178
- thermionic emission 171–72, 361, 364–65, 382
- thermionic emission in doped FinFET devices 363
- thickness variations of ultra-thin TiN metal gates 63, 110
- TLP (transmission line pulsing) 266–67, 282–83, 292
- total gate-to-channel capacitance 130
- transistors, doping-less 173
- transmission electron microscopy *see* TEM
- twin boundary defects 18, 166–67
  
- ultra-thin TiN metal gates 63, 110
- ultrashort thin junctionless nanowires 325, 327, 329
  
- vacuum break 108–10
- vapor phase doping *see* VPD
- VPD (vapor phase doping) 18, 162
  
- wafers 34, 37, 42–43, 46, 66, 122, 154, 162, 187, 195, 282, 289–90, 295–96, 334
- WFV (work-function variation) 188–89
- wide fin NMOS devices 272–73, 275, 282, 293
- WNM (write noise margin) 215–17, 220–22, 224
- work-function variation (WFV) 188–89
  
- zero temperature coefficient *see* ZTC
- ZTC (zero temperature coefficient) 249