

Index

- active layers 159, 170, 242, 253
- active materials 3, 5, 13, 34, 39, 58, 125, 139–142, 144–146, 159, 164, 208, 242, 247, 291
 - electrodeposited 140
 - isolation of 164, 247
 - Sn/Ni 141
- active particles 192, 204, 275, 287
- active phase 163, 165, 185, 186, 246, 248, 268, 269
- additives 163, 246
 - reduced 74
- AFM *see* atomic force microscopy
- agglomerates 77, 185, 268
 - large 193, 276
 - very dense 194, 277
- agglomeration 182, 265
 - serious 193, 276
- alloy anodes 191, 194, 274, 277
- alloy electrode 154, 155, 157–159, 161, 163, 165, 167, 169, 171, 173–175, 177, 179, 237, 238, 240–242, 244, 256–258
 - commercialized 158, 241
- alloying 11, 18, 41, 110, 127, 151, 162, 166, 185, 214–218, 224, 232, 236, 297–301, 315
 - anodes 88, 103
 - elements 184, 267
 - mechanical 164, 165, 247, 248
- alloy systems 159, 162, 242, 245
 - representative 160, 243
- ambient temperature 73, 76, 214, 216, 217, 232, 236, 297, 299, 300, 315, 319
- amorphous films 84, 87, 91, 99, 102, 106, 202, 285
- anisotropic expansion 27, 29–31, 90, 105
- anodes
 - alloy-based 184, 267
 - carbon-based 155, 238
 - conventional carbon 69, 70
 - graphite carbon 202, 285
 - lithiated carbon 326
 - low-voltage 216, 299
 - nano-alloy 156, 239
- atomic force microscopy (AFM) 39, 140
- axial orientation 25, 28–31
- ball-milling 111, 164, 189, 247, 272
- battery system 156, 157, 169, 239, 240, 252
- BET *see* Brunauer-Emmett-Teller
- binary system 162, 224, 225, 228, 231, 245, 307, 308, 311, 314
- binders 4, 5, 13, 54, 56, 58, 59, 78, 131, 205, 288
- bond distortion 193, 276
- borosilicate micro-fiber 187
- capacity densities 158–160, 170, 241–243, 253
- capacity difference 235, 318
- capacity retention 51, 60, 91, 106, 161, 170–172, 185, 192, 244, 253–255, 268, 275
- carbonaceous anode 158

- new 155, 158, 238, 241
- carbonaceous materials 186
- carbon black (CB) 56
- carbon coating 55–57, 204, 287
- carbon cores 42, 49
- carbonization 42, 56
- carbon matrix 208, 291
- carbon nanofiber 47
- carbon nanotubes 204, 287
- carboxymethylcellulose (CMC) 3, 56, 57
- catalysts 6, 17, 55
- cathode materials 141, 184, 227–252, 259–300, 314, 376, 419
- CB *see* carbon black
- Celgard microporous separator 217, 300
- cell
 - bag 8
 - beaker 11, 12, 15
 - coffee bag pouch 8
 - coin-type 158, 171, 241, 254
 - conventional 23, 31
 - fuel 151
 - half 44, 202, 285
 - high temperature 183, 266
 - primary 157, 240
 - prismatic 170, 253
 - solid-state 90, 105
 - stainless coin 216, 299
- Century COE Program 151
- charge
 - differential 9
 - elemental 77
 - first 18, 19, 34, 35, 38, 58, 114, 115, 122, 125, 126, 134, 219, 302
 - hour 14, 78
 - second 38, 39, 125
 - tenth 131, 132
- charge capacity 14, 85, 100, 218, 220, 221, 223, 226, 229, 301, 303, 304, 306, 309, 312
- charge-discharge 142, 149, 150
- charge/discharge, cycles 138, 157, 162, 166, 240, 245, 249
- charge potentials 17
- charge saturation 130
- charge storage 5
- charge-transfer 45
- charging curve 205, 288
- charging processes 129, 155, 238
 - initial 159, 163, 165, 168, 242, 246, 248, 251
- charging rates 163, 246
- charging voltage 198, 201, 205, 206, 281, 284, 288, 289
- chemical bonds 193, 233, 276, 316
- Chemical precipitation 165, 248
- chemical vapor deposition 6, 56, 74, 204, 205, 287, 288
- chemical vapor deposition (CVD)
- chi-square quality 131
- circuit
 - electric 327
 - open 145
- CMC *see* carboxymethylcellulose
- CNano 56
- CNF films 60
- CNF nanofiber films 61
- CNF networks 60
- CNFs
 - bare 61
 - dispersed 60
- CNF-SiNW nanocomposites 60, 61
- CNLS *see* complex nonlinear least-squares
- CNT *see* conductive carbon nanotube
- CNT backbone 51
- CNTs, coiled 204, 287
- CNT sponge 51, 52
- coaxial structure 51, 52
- coffee bag cell 8, 12
- cohesive film 39
- coulombic efficiency 78, 85, 100, 116, 197, 208, 280, 291

- high 197, 199, 219, 280, 282, 302
- initial 116
- low 80, 95, 205, 288
- stable 116
- commercialization 70, 154, 155, 159, 237, 238, 242
- commercial Li-ion batteries 183, 266, 332
- Commercial SiNPs 53
- complex nonlinear least-squares (CNLS) 132, 133
- components
 - decomposable 202, 204, 285, 287
 - electrical 131
 - passive 132
- composite electrodes 54, 56, 59, 159, 185, 242, 268
- composite film 13
- composite Si/Cu structure 31
- composition
 - bath 112, 125
 - chemical 157, 240
 - molecular 35
 - slurry 56
- conditions
 - equilibrium 326
 - gentle cycling 87, 102
 - imaging 23
 - quasi-equilibrium 9
 - slow-charge 329
 - stirring 194, 277
 - synthetic 330, 332
- conducting additives 5
- conducting agent 57
- conducting polymers 56
- conductive carbon nanotube (CNT) 51, 52, 58, 59, 204, 205, 287, 288
- conductivity 56, 168, 171, 251, 254
 - better 166, 171, 249, 254
 - good 59
 - inferior 166, 249
 - lower 166, 249
- confinement 216, 299
- confinement effect 335
- constant phase element (CPE) 131
- constraining layer 46
 - mechanical 43
- contact interface 139–141
- contiguous films 84, 99
- continuous channels 189, 272
- core-shell nanostructures 49
- core-shell nanowire structures 47
- coulombic efficiency 11, 12, 14, 15
 - low 42
 - poor 12
- CPE *see* constant phase element
- CPE exponent 132
- crack formation 28, 148
- C-rate 15, 217, 222, 228, 300, 305, 311
- crystalline phases 11, 17, 82, 88, 97, 103
 - transient 3
- crystalline Si core 25, 47
- crystalline Si grains 19
- crystalline Si nanopillars 28
- crystalline Si nanostructures 25, 28
- crystallinity 56, 122, 186, 187, 269, 270
- crystallite 78, 168, 251, 331
- crystallographic orientation 25, 26, 29
 - axial 26, 27
- crystallographic phase 82, 97
- crystallographic structures 72
- crystallography 25, 26
- crystals 6, 23, 24, 74
 - large metallic host 74
 - lyotropic liquid 112, 147
 - metastable Sn-Ni alloy 123
- crystal structure 71, 215, 298
- crystal-structure transformations 144

- current collector 1, 3–5, 7, 15, 16, 20, 22, 26, 39, 56, 57, 59, 60, 132, 159, 164–166, 242, 247–249
- current density 112, 114, 115, 117, 120–122, 124, 126, 128–130, 136, 137, 143, 148–150, 161, 169, 244, 252, 328
 - high-charge 144
- current peaks 9, 214, 217, 236, 297, 300, 319
- CV *see* cyclic voltammogram
- CV curve 9
- CVD *see* chemical vapor deposition
- CV measurement 9
- CV peaks 228, 311
- CV profiles 217, 229, 236, 300, 312, 319
- cyclability 111, 116
 - better 14
 - excellent 326
 - good 116
 - high 111
 - improved 111
 - insufficient long-term 58
 - poor 113
- cycle capacity 218–224, 226, 228–230, 234, 301–307, 309, 311–313, 317
- cycle durability 149
- cycle efficiency 157, 220, 222, 240, 303, 305
- cycle index 220, 221, 223, 226, 229, 230, 303, 304, 306, 309, 312, 313
- cycle life 58, 60, 74, 87, 88, 102, 103, 141, 157, 160, 171, 172, 215, 216, 240, 243, 254, 255, 298, 299
 - better 159, 242
 - enhanced 74
 - extended 216, 299
 - good 159, 242
 - improved 74
 - long 158, 241
 - poor 83, 98, 184, 267
 - reliable 158, 241
 - short 151
- cycle life plots 87, 102
- cycle number 45, 50, 78, 79, 117, 136, 149, 155, 161, 169, 172, 173, 190, 238, 244, 252, 255, 256
- cycle number profile 136
- cycle performance 116, 121, 123, 137, 155, 157, 159, 161–166, 171–173, 238, 240, 242, 244–249, 254–256
 - better 159, 242
 - lower 155, 162, 238, 245
 - poor 163, 246
 - stable 166, 168, 171, 249, 251, 254
- cycle properties 150, 151
- cyclic performance 197, 201, 204, 206, 280, 284, 287, 289
 - best 204, 287
 - better 192, 275
 - excellent 186, 197, 269, 280
 - good 196, 279
 - improved 185, 268
 - poor 191, 204, 274, 287
 - very poor 188, 271
- cyclic voltammetry 8, 50, 217, 300
- cyclic voltammogram (CV) 8, 9, 114, 214, 217–219, 228, 236, 297, 300–302, 311, 319
- dark-field image 24
- defect generation 75
- defects 90, 105, 182, 265
 - electrode crystal structure 216, 299
- planar 88, 103
- structural 335

- defects confinement 216, 299
- deflection 142, 143, 145, 146
- deflection profile 142, 144–146
- deflection response 142
- deformation 31
 - mechanical 27
- delithiation 3, 11, 20, 21, 23, 24,
 - 31, 41, 43, 71, 125, 145, 146,
 - 194, 196, 198, 224, 307
- delithiation process 140, 145
- delithiation reactions 22
- differential capacity curves 10, 11
- differential capacity plot 85, 86,
 - 100, 101
- diffraction patterns 23, 84, 99
- diffractions 147
- diffusion 23, 28, 75, 76, 234, 317
 - fast 145
 - homogeneous 132
 - radial 25
 - solid-state 75, 129, 131
 - various 328
- diffusion coefficient 133, 328
- diffusion dimensionality 329, 330
- diffusion element 45
- diffusion equation 325–327, 329
 - empirical 73
- diffusion impedance 129
- diffusion lengths 75, 76, 215, 298
 - long 329
- diffusion pathways 75, 133
- diffusion rate 73
- diffusion region 130
- diffusion resistance 121
- diffusivity 76
- digital cameras 154, 237
- distribution 17, 35, 334
 - core-shell phase 17
 - distorted angular bond 193, 276
 - narrow 333
 - narrow size 334
 - observed pore size 32
 - uniform particle-size 334
- EELS *see* electron energy-loss spectroscopy
- EIS *see* electrochemical impedance spectroscopy
- EIS measurements 44
- elastic matrix 208, 291
- electric vehicle application 156, 239
- electric vehicles 154, 156, 158, 237, 239, 241
 - hybrid 69, 326
- electric vehicles applications 215, 298
- electrochemical impedance spectroscopy (EIS) 44, 45, 131
- electrochemical lithiation 72, 83, 86, 98, 101, 193, 276
- electrochemical lithiation/delithiation 214, 297
- electrochemical measurements 8, 9, 11, 13, 15
- electrochemical performance 78, 79, 81, 83, 85, 87, 96, 98, 100, 102
- electrochemical performance of silicon nanoparticles 274
- electrochemical plating 165, 248
- electrochemical potential spectroscopy (EPS) 9–11
- electro-chemical window 183, 266
- electrode architecture 13, 54
- electrode bulk 132
- electrode composition 142
- electrode crystallinity 122
- electrode deflection profile 145
- electrode degradation 113
- electrode fades 185, 268
- electrode failure 125
- electrode film thickness 133
- electrode kinetics 42
- electrode layer 204, 287
- electrode nanopores 234, 317
- electrodeposited film 139, 142

- electrodes 2–4, 7, 8, 34, 35, 56–58, 74–76, 78, 84–88, 99–103, 113–117, 122–138, 140–147, 159–161, 202–204, 242–244, 285–287
- aged 138
- as-deposited 134, 146
- battery 31
- conventional silicon powder 168, 251
- conversion 74
- copper-based nanofilm 222, 305
- counter 22, 78, 147
- cycled 204, 287
- electrical storage 62
- expanded 137
- high-capacity 69
- host 75, 326, 327
- improved 215, 298
- inner 121
- lithiated CBO 202, 285
- metal nanofilm 216, 299
- nanocrystalline 82, 97
- nanostructured 3, 15
- porous 138
- silicon powder 166, 249
- tin-base 168, 251
- vacuum-deposited 159, 242
- electrode stability 216, 299
- electrolyte 5, 11–13, 21–23, 34, 35, 41–43, 45, 125, 126, 161, 168–171, 173, 174, 216, 217, 244, 251–254, 256, 257, 299, 300
- ionic liquid 22, 32
- organic 34, 123, 155, 158, 160, 238, 241, 243
- solid oxide fuel cell 335
- solid-state 31
- electrolyte- electrode
 - heterointerface 326
- electrolyte materials 215, 298
- electromotive force 199, 282
- electron diffraction 89, 104, 122
- electron energy-loss spectroscopy (EELS) 88, 103
- electron flux 55, 58
- electronic devices 7, 151, 326
 - portable 111, 151
- electronic extension 132
- electronic industries 166, 249
- electronic insulation 132
- electronic interparticle contact
 - 160, 243
- elemental mapping 88, 103
- energy density 2, 60, 91, 106, 170, 182, 207, 215, 253, 265, 290, 298, 328
 - greatest 70
 - high 70, 155, 238
 - higher 183, 266
 - highest 111
 - lower 72
 - volumetric 2
- EPS *see* electrochemical potential spectroscopy
- FE-SEM *see* field emission scanning electron microscope
- field-effect transistors 7
- field emission scanning electron microscope 114
- film 5, 13, 34, 37–39, 47, 58, 60, 86, 87, 101, 102, 115, 118, 120, 123, 124, 128, 202
- film mass 217, 300
- film separator 202, 285
- film thickness 3, 123, 130, 234, 236, 317, 319
- first cycle discharge 232, 315
- first discharge capacity 217, 300
- fracture 4, 5, 28, 29, 31, 42, 75
- fractured pillars 28, 29
- fracture locations 29, 30
- fracture properties 28, 29
- fracture toughness 75

- frequencies 130, 131, 133
 - phonon vibration 335
- Fujifilm Celltech 159, 242
- Fuji Film Co. 111, 186, 269

- galvanostatic 12, 44, 236, 319
- galvanostatic charge 214, 217, 228, 297, 300, 311
- galvanostatic cycle profile 218, 219, 221–223, 225, 229, 301, 302, 304–306, 308, 312
- galvanostatic cycling 11, 16
 - data 56
 - performance 49
 - results 12, 46
 - test 123, 125
- galvanostatic measurements 14
- galvanostatic mode 205, 236, 288, 319
- galvanostatic pulses 44
- galvanostatic voltage curves 42
- Gibbs phase rule 79
- Global Climate and Energy Project 62
- Global COE Program 151
- gradients 75
- grain boundaries 75, 84, 88, 99, 103, 214, 215, 233–235, 297, 298, 316–318
- grains boundary structure 233, 316
- grain size 115, 198, 281
- graphite 1, 2, 13, 14, 34, 58, 70, 73, 155, 158–161, 168, 169, 171, 183, 198, 238, 241–244, 251, 252
- graphite-base anode 170, 253
- graphite carbons 183, 266
- graphite electrodes 34, 35, 39, 156, 170, 239, 253
 - conventional 168, 251
 - lithiated 202, 285
- graphite system 168, 170, 171, 251, 253, 254
- gravimetric capacity 60, 70

- half-cells assembly 217, 300
- hard carbon spherules (HCS) 196, 197, 203, 205, 279, 280, 286, 288
- HCS *see* hard carbon spherules
- High-Capacity Anode Materials 112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 134, 136
- high-energy ball milling 56
- high-power Li-ion batteries 207, 290
- high-resolution TEM (HRTEM) 17, 19, 61, 189, 193, 272, 276
- high-resolution XPS 39
- high-voltage plateau 126–128
- HRTEM *see* high-resolution TEM
- hydrothermal method 199, 200, 282, 283, 325, 332–336

- ICP *see* inductively coupled plasma
- impedance 46, 73, 130, 132, 133, 138
 - complex 130
 - low reaction 171, 254
- impedance spectra 129–132
- impedance spectroscopy 62
- impedance spectrum 131
- implantable medical devices 91, 106
- In-based nanofilm electrode 229, 312
- inductively coupled plasma (ICP) 112
- infrared absorption spectroscopy 157, 240

- insertion capacitance 131, 132
- insertion capacity 184, 267
- insertion compounds 5
- insertion distances 5
- insertion electrodes 130
- interface 17, 35, 39, 54, 56, 60, 61, 131, 141, 160, 171, 243, 254
 - electrode/electrolyte 131
 - solid electrolyte 131
 - static 42
 - unstable 43
- intermetallic compounds 162, 164, 245, 247
- irreversibility 159, 161, 166, 200, 242, 244, 249, 283
- irreversible capacity 81, 96, 111, 236, 319
 - abnormal high-voltage 127
 - first-cycle 87, 102
 - high 78
 - high initial 111
 - large 72, 82, 97
- irreversible capacity losses 12, 34, 57, 60, 233, 234, 316, 317
- irreversible trapping 182, 265
- kinetic limitations 9
- kinetics 75, 76, 83, 98, 236, 319
 - rapid 75
 - slow 73, 83, 88, 98, 103
- kinetics effect 227, 310
- layer 8, 35, 37, 73, 185, 201, 202, 268, 284, 285
 - charge-storage 50
 - constraining surface 42
 - dense Si 193, 276
 - inorganic 35
 - insulating 54
 - mechanical clamping 42
 - passivating 202, 285
 - passivating surface 35
 - thin contamination 72
- LIBs *see* Lithium-ion batteries
- Li storage 186, 215, 233, 236, 269, 298, 316, 319
 - extra 200, 283
 - reversible 232, 315
- LiTFSI *see* lithium bis(trifluoromethylsulfonyl)imide
- lithiated phases 19, 71, 72, 80, 95
- lithiated SiNPS 193, 276
- lithiated SiNWs 19, 20, 193, 276
- lithiation 9–11, 16, 17, 20–32, 41–43, 73–75, 79, 80, 82, 83, 86, 88–90, 97, 98, 101, 103–105, 139, 140, 226, 227, 309, 310
 - complete 72
 - first 20, 226, 234, 309, 317
 - full 57, 125, 189, 272
 - gradual 144
 - incomplete 146
 - preferential 27, 29
 - two-phase 28
- lithiation process 20, 24, 25, 144–146
 - initial 145
 - two-phase 27
- lithiation reactions 47, 119
- lithium
 - active 208, 291
 - compounds of 183, 266
 - dead 157, 240
 - elemental 156, 239
 - higher diffusivity of 82, 97
 - high ionic state of 186, 269
 - inserted 196, 200, 279, 283
- lithium alloy anodes 70, 74, 155, 158, 164, 166, 173, 238, 241, 247, 249, 256
- lithium alloy electrodes 70, 158–162, 164–166, 168, 170,

- 172, 241–245, 247–249, 251, 253, 255
- lithium alloys 72, 155, 159, 160, 164, 238, 242, 243, 247
 - composite 159, 242
 - conventional 161, 244
 - nanophase 76
- lithium alloy systems 156, 158, 160, 162, 173, 239, 241, 243, 245, 256
- lithium anodes 70, 71, 110
- lithium atoms 71, 81, 82, 96, 97, 155, 184, 238, 267
- lithium bis
 - (trifluoromethylsulfonyl) imide (LiTFSI) 22
- lithium cell 75, 90, 105, 188, 195, 271, 278
 - next-generation 91, 106
- lithium densities 69, 70
- lithium deposition 156, 239
- lithium diffusion 75, 76
- lithium insertion 79, 81, 86, 96, 101, 163, 185, 195, 199, 246, 268, 278, 282
 - first 81, 96
 - initial 163, 246
 - larger 162, 245
- lithium-ion batteries (LIBs) 1, 66, 69, 110, 154–156, 173, 174, 182, 214, 215, 237–239, 256, 257, 265, 297, 298, 325
- lithium metal 70, 71, 155, 157, 183, 238, 240, 266
 - deposit 170, 253
 - pure 70
- lithium metal electrode 155, 157, 238, 240
- local structure evolution 196, 279
- materials
 - amorphous shell 47
 - anode-active 186, 269
 - antireflection 7
 - battery 55, 183, 266
 - brittle 73, 74
 - composite 185, 186, 268, 269
 - conductive 166, 249
 - nanocrystalline 84, 86, 99, 101, 332, 335
 - nanorod 4
 - nanoscale 70, 74–76, 90, 105
 - nanosized 185, 186, 193, 268, 269, 276
 - photoelectrochemical 7
 - single-phase 195, 278
- matrix 111, 185, 268
 - amorphous Li₂O 189, 272
 - buffering 185, 268
 - carbonaceous 186, 269
 - composite 163, 164, 246, 247
 - ductile Sn 194, 277
 - inactive 185, 268
 - inert Li₂O 185, 268
- metal nanofilms 214, 215, 217, 219, 221, 223, 225, 227, 229, 231, 233, 235, 236, 297, 298, 300, 316, 318–320
- metastable phase 113, 117–121
- microstructures 201, 204, 284, 287
- miniaturization 90, 105
- nanocrystalline silicon 78–80, 82, 86, 87, 95, 97, 101, 102
- nanoelectrochemistry 90, 105
- nanoscale electrodes 69, 70, 74, 75, 87, 102
- nanoscale silicon electrodes 88, 103
- nanosized alloy anodes 191, 192, 194, 196, 274, 275, 277, 279
- native oxide 40–42, 54, 55
- native oxide layer 7, 72

- overpotentials 205, 288
- oxidation 17, 21, 217, 229, 300, 312
 - environmental 22
- oxide 182, 265
 - chromium-based 202, 285
 - composite 267
 - lithium cobalt 155, 156, 238, 239
 - native surface 82, 97
- passivation layer 80, 95
 - contiguous 80, 95
- peak intensity 20, 21, 89, 104, 119, 120
- peaks
 - anodic 114
 - cathodic 227, 310
 - crystalline 18
 - diffracting 17
 - sharp 82, 84, 97, 99
- PEEK *see* polyaryletheretherketone
- PEO-oligomers 35
- phase transformation 20, 145, 200, 283
 - complete 332
 - distinct 144
 - facile 2
 - similar 11
- phase transitions 79, 234, 317
- phenylsilane 55
- PHEV application 172, 255
- phonon-confinement effect 335
- pillars 26, 28–31
 - larger diameter 28
 - pristine 26
 - smaller 31
 - smaller lithiated 29
 - submicrometer 3
- PITT *see* potentiostatic intermittent titration technique
- planes 19, 26, 27, 29
 - crystallographic 27
- plateaus 10, 11, 34, 79, 125, 127, 144, 187, 217, 224, 230, 270, 300, 307, 313
 - descending 144
 - first 11, 144, 224, 307
 - flat 34, 224, 307
 - multiple 125
 - second 11, 144, 224, 307
 - short 219, 302
 - single 230, 313
 - third 224, 307
- polarizations 168, 205, 206, 251, 288, 289, 326
 - lower 205, 288
 - small 199, 282
- polyaryletheretherketone (PEEK) 18
- potential profiles 143
- potential range 114, 117, 120–122, 124, 126–128, 130, 134, 135, 148–150
- potentiostatic 206, 289
- potentiostatic intermittent titration technique (PITT) 206, 289
- power tools 154, 155, 170, 237, 238, 253
- precipitation 164, 247
 - massive 138
 - reductive 194, 277
- pseudo-plateau 224, 307
- rechargeable batteries 2, 157, 190, 240, 273
 - high-capacity 158, 241
 - higher-power 325
 - small 70
- rechargeable power sources 154, 237
- reduction 37, 80, 95, 147, 217, 229, 236, 300, 312, 319
 - considerable 76
 - electrode size 215, 298

- metal-oxygen 234, 317
- surface oxygen 234, 317
- robot 154, 237

- SAED *see* selected-area electron diffraction
- scanning electron microscope (SEM)
- scanning TEM 50
- scans 9, 17, 18, 90, 105
 - anodic 114
 - cathodic 114
 - high resolution 41
 - survey 39
- SEI *see* solid electrolyte interphase
- selected-area electron diffraction (SAED) 17, 19, 48
- SEM *see* scanning electron microscope
- SFLS *see* supercritical fluid-liquid-solid
- SiH₄ 6
- silicon nanoparticles (SiNPs) 51, 53, 54, 74, 89, 104, 191–193, 274–276
- silicon nanowire (SiNW) 4–7, 9–17, 20, 22–26, 28, 29, 31–33, 35, 37, 39, 40, 45, 46, 50, 51, 53, 54, 56–62, 191–193, 274–276
- SILX 168
- SILX system 170
- SiNPs *see* silicon nanoparticles
- SiNW *see* silicon nanowire
- SiNW electrodes 8, 9, 11, 15, 34, 47, 62
- SiNW growth 6, 7
- Sn electrode 125, 126, 128, 141, 143–146
- Sn nanograins 184, 267
- solid electrolyte interphase (SEI)
- SS *see* stainless steel
- stainless steel (SS) 7, 8, 16, 17, 227, 232, 310, 315
- STEM *see* scanning TEM
- supercritical fluid-liquid-solid (SFLS) 54

- TCO *see* tin composite oxide
- TEM *see* transmission electron microscopy
- TEM column 22
- TEM images 19, 23–25, 31, 32, 124, 147, 149, 333, 334, 336
- TEM microgrid 148
- TEM techniques 21
- thermogravimetry 202, 285
- Thin-Film Electrode Technologies 165, 248
- three-electrode configuration 44
- three-electrodes cell 114, 115, 119, 122, 126, 127, 129, 136, 137, 143, 148, 149
- tin-base alloys 164, 165, 247, 248
- tin-based anode 207, 290
- tin-based composite oxides 186, 269
- tin-based metallic host matrices 189, 272
- tin-based oxides 188, 189, 271, 272
- tin composite oxide (TCO) 159, 184–186, 242, 267–269
- transition metal compounds 199, 201, 282, 284
- transition metal oxides 198–202, 204–206, 281–285, 287–289
- transmission electron microscopy (TEM) 17, 22, 23, 29, 78, 88, 89, 103, 104, 123, 202, 285

- ultrasonic treatment 194, 277

- vapor-liquid-solid (VLS) 6, 31
- vehicles
 - all-electric 70
 - plug-in hybrid-electric 70, 156, 239
- VIF *see* volume increase factor
- VLS *see* vapor-liquid-solid
- VLS electrode design 59
- VLS-grown SiNWs 7, 23, 26
- VLS SiNW electrodes 58
- VLS SiNW growth process 60
- voltage plateaus 125, 218, 234, 236, 301, 317, 319
 - flat 224, 307
 - multiple 193, 276
- voltage profiles 10–12, 78–82, 84–86, 95–97, 99–101, 200, 224, 283, 307
- voltammograms 128
- volume expansion 3, 24–26, 28, 31, 37, 71, 80, 82, 95, 97, 139–141, 184, 188, 191, 267
 - concurrent 27
 - unit cell 236, 319
- volume increase factor (VIF) 139–141, 144
- Warburg diffusion impedance 129
- Warburg element 131
- Warburg impedance 131
- XPS *see* X-ray photoelectron spectroscopy
- XPS spectrum 40
- X-ray diffraction (XRD) 7, 17, 20, 21, 83, 88, 98, 103, 112, 113, 117, 118, 335
- X-ray diffraction analysis 335
- X-ray diffraction patterns 226, 309, 333
- X-ray diffractograms 227, 310
- X-ray photoelectron spectroscopy (XPS) 34, 36, 157, 236, 240, 319
- XRD *see* X-ray diffraction
- XRD patterns 88, 103, 119, 134
- Young's modulus 140, 141, 145