

Bibliography

1. Swedish Hip Arthroplasty Register: Annual Report 2008. Available at www.jru.orthop.gu.se.
2. Learmonth I, Young C, Rorabeck C. The operation of the century: total hip replacement. *Lancet*, 2007; **370**: 1508–1519.
3. Rahaman MN, Yao A, Sonny Bal B, Garino JP, Ries MD. Ceramics for prosthetic hip and knee joint replacement. *J. Am. Ceram. Soc.*, 2007; **90**: 1965–1988.
4. Bizot P, Banallec L, Sedel L, Nizard R. Alumina-on-alumina total hip prostheses in patients 40 years of age or younger. *Clin. Orthop. Relat. Res.*, 2000; **379**: 68–76.
5. National Joint Registry of England and Wales (NJR): 4th Annual Report 2008. Available at www.njcentre.org.uk.
6. Kurtz S, Mowat F, Ong K, Chan N, Lau E, Halpern M. Prevalence of primary and revision total hip and knee arthroplasty in the United States from 1990 through 2002. *J. Bone Joint Surg. (Am.)*, 2005; **87**: 1487–1497.
7. Tateiwa T, Clarke IC, Williams PA, Garino J, Manaka M, Shishido T, Yamamoto K, Imakiire A. Ceramic total hip arthroplasty in the United States: safety and risk issues revisited. *Am. J. Orthop.*, 2008; **37**: E26–E31.
8. Garino J, Rahaman MN, Sonny Bal B. The reliability of modern alumina bearings in total hip arthroplasty. *Semin. Arthroplasty*, 2006; **17**: 113–119.
9. Zhu YH, Chiu KY, Tang WM. Review article: Polyethylene wear and osteolysis in total hip arthroplasty. *J. Orthop. Surg.*, 2001; **9**: 91–99.
10. Li S, Burstein AH. Current concepts review: UHMW polyethylene. *J. Bone Joint Surg. (Am.)*, 1994; **76**: 1080–1090.
11. Gordon AC, D'Lima D, Colwell Jr. CV. Highly cross-linked polyethylene in total hip arthroplasty. *J. Am. Acad. Orthop. Surg.*, 2006; **14**: 511–523.
12. Jacobs CA, Christensen CP, Greenwald AS, McKellop H. Clinical performance of highly cross-linked polyethylenes in total hip arthroplasty. *J. Bone Joint Surg. (Am.)*, 2007; **89**: 2779–2786.
13. Mu Z, Tian J, Wu T, Yang J, Pei F. A systematic review of radiological outcomes of highly cross-linked polyethylene versus conventional polyethylene in total hip arthroplasty. *Int. Orthop.*, 2009; **33**: 599–604.

14. Fisher J, Hailey JL, Chan KL, Shaw D, Stone M. The effect of ageing following irradiation on the wear of UHMWPE. *Trans. Orthop. Res. Soc.*, 1995; **20**: 120–128.
15. Endo MM, Barbour PS, Barton DC, Fisher J, Tipper JL, Ingham E, Stone MH. Comparative wear and wear debris under three different counterface conditions of crosslinked and non-crosslinked ultra high molecular weight polyethylene. *Biomed. Mater. Eng.*, 2001; **11**: 23–35.
16. Premnath V, Harris WH, Jasty M, Merrill EW. Gamma sterilization of UHMWPE articular implants: an analysis of the oxidation problem. *Biomaterials*, 1996; **17**: 1741–1753.
17. Oparaugo PC, Clarke IC, Malchau H, Herberts P. Correlation of wear debris-induced osteolysis and revision with volumetric wear-rates of polyethylene: A survey of 8 reports in the literature. *Acta Orthop.*, 2001; **72**: 22–28.
18. Bradford L, Baker DA, Graham J, Chawa A, Ries MD, Pruitt LA. Wear and surface cracking in early retrieved highly cross-linked polyethylene acetabular liners. *J. Bone Joint Surg. (Am.)*, 2004; **86-A**: 1271–1282.
19. Bladen CL, Teramura S, Russell SL, Fujiwara K, Fisher J, Ingham E, Tomita N, Tipper JL. Analysis of wear, wear particles, and reduced inflammatory potential of vitamin E ultrahigh-molecular weight polyethylene for use in total joint replacement. *J. Biomed. Mater. Res. B: Appl. Biomater.*, 2013; **101**: 458–466.
20. Hannouche D, Nich C, Bizot P, Meunier A, Nizard R, Sedel L. Fractures of ceramic bearings: history and present status. *Clin. Orthop. Relat. Res.*, 2003; **417**: 19–26.
21. Allain J, Roudot-Thoraval F, Delecrin J, Anract P, Migaud H, Goutallier D. Revision total hip arthroplasty performed after fracture of a ceramic femoral head. A multicenter survivorship study. *J. Bone Joint Surg. (Am.)*, 2003; **85**: 825–830.
22. Maciowski T, Tepic S, Mann RW. Cartilage stresses in the human hip joint. *J. Biomech. Eng.*, 1994; **116**: 10–18.
23. von Eisenhart-Rothe R, Eckstein F, Muller-Gerbl M, Landgraf J, Rock C, Putz R. Direct comparison of contact areas, contact stress and subchondral mineralization in human hip joint specimens. *Anat. Embryol. (Berl.)*, 1997; **195**: 279–288.
24. von Eisenhart-Rothe R, Steinlechner M, Muller-Gerbl M, Eckstein F. Quantitative determination of joint incongruity and pressure distribution during simulated gait and cartilage thickness in the human hip joint. *J. Orthop. Res.*, 1999; **7**: 532–539.

25. Brown TD, Shaw DT. *In vitro* contact stress distributions in the natural human hip. *J. Biomech.*, 1983; **16**: 373–384.
26. Rushfeldt PD, Mann RW, Harris WH. Improved techniques for measuring *in vitro* the geometry and pressure distribution in the human acetabulum — I. Ultrasonic measurement of acetabular surfaces, sphericity and cartilage thickness. *J. Biomech.*, 1981; **14**: 253–260.
27. Shepherd DE, Seedhom BB. Thickness of human articular cartilage in joints of the lower limb. *Ann. Rheum. Dis.*, 1999; **58**: 27–34.
28. Konishi N, Mieno T. Determination of acetabular coverage of the femoral head with use of a single anteroposterior radiograph. A new computerized technique. *J. Bone Joint Surg. (Am.)*, 1993; **75**: 1318–1333.
29. Adams MA, Kerin AJ, Bhatia LS, Chakrabarty G, Dolan P. Experimental determination of stress distributions in articular cartilage before and after sustained loading. *Clin. Biomech. (Bristol, Avon)*, 1999; **14**: 88–96.
30. Adams D, Swanson SA. Direct measurement of local pressures in the cadaveric human hip joint during simulated level walking. *Ann. Rheum. Dis.*, 1985; **44**: 658–666.
31. Afoke NY, Byers PD, Hutton WC. Contact pressures in the human hip joint. *J. Bone Joint Surg. (Br.)*, 1987; **69**: 536–541.
32. Sparks DR, Beason DP, Etheridge BS, Alonso JE, Eberhardt AW. Contact pressures in the flexed hip joint during lateral trochanteric loading. *J. Orthop. Res.*, 2005; **23**: 359–366.
33. Rushfeldt PD, Mann RW, Harris WH. Influence of cartilage geometry on the pressure distribution in the human hip joint. *Science*, 1979; **204**: 413–415.
34. Rushfeldt PD, Mann RW, Harris WH. Improved techniques for measuring *in vitro* the geometry and pressure distribution in the human acetabulum. II Instrumented endoprosthesis measurement of articular surface pressure distribution. *J. Biomech.*, 1981; **14**: 315–323.
35. Shirazi R, Shirazi-Adl A, Hurtig M. Role of cartilage collagen fibrils networks in knee joint biomechanics under compression. *J. Biomech.*, 2008; **41**: 3340–3348.
36. Mononen ME, Julkunen P, Töyräs J, Jurvelin JS, Kiviranta I, Korhonen RK. Alterations in structure and properties of collagen network of osteoarthritic and repaired cartilage modify knee joint stresses. *Biomech. Model Mechanobiol.*, 2011; **10**: 357–369.

37. Wiederhorn SM. Brittle fracture and toughening mechanisms in ceramics. *Ann. Rev. Mater. Sci.*, 1984; **14**: 373–403.
38. Gilman J. *Electronic basis of the strength of materials*. Cambridge University Press, Cambridge; 2003.
39. Peterlik H. Relationship of strength and defects of ceramic materials and their treatment by Weibull theory. *J. Ceram. Soc. Jpn.*, 2001; **109**(8): 121–126.
40. Richter HG, Willmann G. Reliability of ceramic components for total hip endoprostheses. *Br. Ceram. Trans.*, 1999; **98**(1): 29–34.
41. Benninghoff A. Form und bau der gelenkknorpel in ihren beziehungen zur funktion. *Z. Zellforsch. Mikrosk. Anat.*, 1925; **2**: 814–819.
42. Hu JCY, Athanasiou KA. Structure and Function of articular cartilage. In *Handbook of histology methods for bone and cartilage*. An YH, Martin KL (Eds.). Humana Press Inc., New Jersey, Chapter 4, 2003.
43. Mansfield JC, Winlove CP, Moger J, Matcher SJ. Collagen fiber arrangement in normal and diseased cartilage studied by polarization sensitive nonlinear microscopy. *J. Biomed. Opt.*, 2008; **13**: 044020-1–8.
44. Owen GRh, Kääb M, Ito K. Scanning electron microscopy examination of collagen network morphology at the cartilage, labrum, and bone interfaces in the acetabulum. *Scann. Micr.*, 1999; **13**: 83–91.
45. Kääb M, Ap Gwynn I, Nötzli HP. Collagen fibre arrangement in the tibial plateau articular cartilage of man and other mammalian species. *J. Anat.*, 1998; **193** (Pt 1): 23–34.
46. Sutula LC, Collier JP, Saum KA, Currier BH, Currier JH, Sanford WM, Mayor MB, Wooding RE, Sperling DK, Williams IR. Impact of gamma sterilization on clinical performance of polyethylene in the hip. *Clin. Orthop.*, 1995; **319**: 28–40.
47. Bapst JM, Valentine RH, Vasquez R. Wear simulation testing of direct compression molded UHMWPE irradiated in oxygenless packaging. In: *Transactions of the 23rd annual meeting of the Society for Biomaterials*, 1997; New Orleans: pp. 72–78.
48. Streicher RM. Influence of ionizing irradiation in air and nitrogen for sterilization of surgical grade PE for implants. *Radiat. Phys. Chem.*, 1988; **31**: 693–698.
49. St John KR, Takeuchi MJ, Poggie RA. Effect of radiation dose and packaging conditions on the oxidation of UHMWPE. In: *Transactions of the 23rd annual meeting of the Society for Biomaterials*, 1997; New Orleans: pp. 46–51.

50. Trieu HH, Avent R. Effect of sterilization on shelf-aged UHMWPE tibial inserts. In: *Transactions of the 21st annual meeting of the Society for Biomaterials*, 1995; San Francisco: pp. 109–114.
51. Sun DC, Wang A, Stark C, Dumbleton JH. The concept of stabilization in UHMWPE. In: *Transactions of the Society for Biomaterials, 5th World Congress*, 1996; Toronto: pp. 195–201.
52. Visentin M, Stea S, Squarzone S, Reggiani M, Fagnano C, Antonietti B, Toni A. Isolation and characterization of wear debris generated in patients wearing polyethylene Hylamer inserts, gamma irradiated in air. *J. Biomater. Appl.*, 2005; **20**: 103–121.
53. Bargmann LS, Bargmann BC, Collier JP, Currier BH, Mayor MB. Current sterilization and packaging methods for polyethylene. *Clin. Orthop.*, 1999; **369**: 49–58.
54. Fisher J, Reeves EA, Isaac GH, Saum KA, Sanford WM. Comparison of the wear of aged and non-aged UHMWPE sterilized by gamma irradiation and by gas plasma. In: *Transactions of the Society for Biomaterials, 5th World Congress*, 1996; Toronto: pp. 971–976.
55. Clarke IC, Manaka M, Green DD, Williams P, Pezzotti G, Kim Y-H. Current status of zirconia used in total hip implants. *J. Bone Joint Surg. (Am.)*, 2003; **85**: 73–84.
56. Chevalier J. What future for zirconia as a biomaterial? *Biomaterials*, 2006; **27**: 535–546.
57. Tateishi T, Yunoki H. Research and development of advanced biocompatible materials and applications to the artificial hip joint. *Bull. Mech. Eng.*, 1987; **45**: 1–9.
58. Brown SS, Green DD, Pezzotti G, Donaldson TK, Clarke IC. Possible triggers for phase transformation in zirconia hip balls. *J. Biomed. Mater. Res. B: Appl. Biomater.*, 2008; **85**: 444–452.
59. Heros RJ, Willman G. Ceramic in total hip arthroplasty: history, mechanical properties, clinical results, and current manufacturing state of the art. *Semin. Arthroplasty*, 1998; **9**: 114–122.
60. Hasegawa M, Sudo A, Hirata H. Ceramic acetabular liner fracture in total hip arthroplasty with a ceramic sandwich cup. *J. Arthroplasty*, 2003; **18**: 658–661.
61. Boehler M, Plenck Jr. H, Salzer M. Alumina ceramic bearings for hip endoprotheses: The Austrian experiences. *Clin. Orthop. Relat. Res.*, 2000; **379**: 85–93.
62. Ha Y-C, Kim S-Y, Kim HJ, Yoo JJ, Koo K-H. Ceramic liner fracture after cementless alumina-on-alumina total hip arthroplasty. *Clin. Orthop. Relat. Res.*, 2007; **458**: 106–110.

63. Garino JP. Modern ceramic-on-ceramic total hip systems in the United States: early results. *Clin. Orthop. Relat. Res.*, 2000; **379**: 41–47.
64. Kelley SS, Lachiewicz PF, Hickman JM, Paterno SM. Relationship of femoral head and acetabular size to the prevalence of dislocation. *Clin. Orthop.*, 1998; **355**: 163–170.
65. Hedlundh U, Ahnfelt L, Hybbinette CH, Wallinder L, Wecksreom J, Fredin H. Dislocations and the femoral head size in primary total hip arthroplasty. *Clin. Orthop. Relat. Res.*, 1996; **333**: 226–233.
66. Bader R, Scholz R, Steinhauser E, Zimmermann S, Busch R, Mittelmeier W. The influence of head and neck geometry on stability of total hip replacement: A mechanical test study. *Acta Orthop. Scand.*, 2004; **75**: 415–421.
67. Beaulé P, Schmalzried T, Udomkiet P, Amstutz H. Jumbo femoral head for the treatment of recurrent dislocation following total hip replacement. *J. Bone Joint Surg. (Am.)*, 2002; **84**: 256–263.
68. Bartz RL, Noble PC, Kadakia NR, Tullos HS. The effect of femoral component head size on posterior dislocation of the artificial joint. *J. Bone Joint Surg. (Am.)*, 2000; **82**: 1300–1307.
69. Burroughs BR, Hallstrom B, Golladay GJ, Hoeffel D, Harris WH. Range of motion and stability in total hip arthroplasty with 28-, 32-, 38-, and 44-mm femoral head sizes. *J. Arthroplasty*, 2005; **20**: 11–19.
70. Pezzotti G, Yamada K, Porporati AA, Kuntz M, Yamamoto K. Fracture toughness analysis of advanced ceramic composite for hip prosthesis. *J. Am. Ceram. Soc.*, 2009; **92**: 1817–1822.
71. Pezzotti G, Munisso MC, Porporati AA, Lessnau K. On the role of oxygen vacancies and lattice strain in the tetragonal to monoclinic transformation in alumina/zirconia composites and improved environmental stability. *Biomaterials*, 2010; **31**: 6901–6908.
72. Lanyon LE, Rubin CT. Static vs dynamic loads as an influence on bone remodeling. *J. Biomech.*, 1984; **17**: 897–905.
73. Stein H, D'Ambrosia R. Wolff's law decoded. *Orthopedics*, 2008; **31**: 213.
74. Bradney M, Pearce G, Naughton G, Sullivan C, Bass S, Beck T, Carlson J, Seeman E. Moderate exercise during growth in prepubertal boys: Changes in one mass, size, volumetric density, and bone strength: A controlled prospective study. *J. Bone Miner. Res.*, 1998; **13**: 1814–1821.
75. Carter DR, Bouxsein ML, Marcus R. New approaches for interpreting projected bone densitometry data. *J. Bone Miner. Res.*, 1992; **7**: 137–145.

76. Hayes W, Gerhart T. Biomechanics of bone: Applications for assessment of bone strength. *J. Bone Miner. Res.*, 1985; **3**: 259–294.
77. Timlin JA, Carden A, Morris MD. Chemical microstructure of cortical bone probed by Raman transects. *Appl. Spectr.*, 1999; **53**: 1429–1435.
78. Kazanci M, Roschger P, Paschalis EP, Klaushofer K, Fratzl P. Bone osteonal tissues by Raman spectral mapping: Orientation-composition. *J. Struct. Biol.*, 2006; **156**: 489–496.
79. Morris MD. Raman spectroscopy of bone and cartilage. In *Emerging Raman applications and techniques in biomedical and pharmaceutical fields*. Motousek P, Morris M (Eds.). Springer, New York, Chapter 14, 2010.
80. Kazanci M, Wagner HD, Manjubala NI, Gupta HS, Paschalis E, Roschger, Fratzl P. Raman imaging of two orthogonal planes within cortical bone. *Bone*, 2007; **41**: 456–461.
81. Morris MD, Mandair GS. Raman assessment of bone quality. *Clin. Orthop. Relat. Res.*, 2011; **469**: 2160–2169.
82. Gourion-Arsiquaud S, Boskey AL. Fourier transform infrared and Raman microspectroscopy and microscopic imaging of bone. *Curr. Opin. Orthop.*, 2007; **18**: 499–504.
83. Carden A, Rajachar RM, Morris MD, Kohn DH. Ultrastructural changes accompanying the mechanical deformation of bone tissue: A Raman imaging study. *Calcif. Tissue Int.*, 2003; **72**: 166–175.
84. Dooley KA, McCormack J, Fyhrie DP, Morris MD. Stress mapping of undamaged, strained, and failed regions of bone using Raman spectroscopy. *J. Biomed. Opt.*, 2009; **14**: 044018-1–8.
85. Pezzotti G, Sakakura S. Study of the toughening mechanisms in bone and biomimetic hydroxyapatite materials using Raman microprobe spectroscopy. *J. Biomed. Mater. Res. A*, 2003; **65**: 229–236.
86. Falgayrac G, Facq S, Leroy G, Cortet B, Penel G. New method for Raman investigation of the orientation of collagen fibrils and crystallites in the Haversian system of bone. *Appl. Spectr.*, 2010; **64**: 775–780.
87. Sundgren J-E, Bodö P, Lundström I, Berggren A, Hellem S. Auger electron spectroscopic studies of stainless-steel implants. *J. Biomed. Mater. Res. A*, 1985; **19**: 663–671.
88. Tzaphlidou M, Berillis P, Matthopoulos D. Bone calcium, phosphorus detection by Auger electron spectroscopy. *Micron*, 2005; **36**: 706–709.
89. Griesshaber E, Neuser RD, Schmahl WW. The application of EBSD analysis to biomaterials: microstructural and crystallographic texture

- variations in marine carbonate shells. *Semin. Soc. Esp. Mineral.*, 2010; **7**: 20–30.
90. Tabb DL, Sevcik JJ, Koenig JL. FTIR study of the effects of irradiation on polyethylene. *J. Polym. Sci. Polym. Phys.*, 1975; **13**: 815–824.
 91. Shen F-W, Yu Y-J, McKellop H. Potential errors in FTIR measurement of oxidation in ultrahigh molecular weight polyethylene implants. *J. Biomed. Mater. Res.*, 1999; **48**: 203–210.
 92. James SP, Blazka S, Merrill EW, Jasty M, Lee KR, Bragdon CR, Harris WH. Challenge to the concept that UHMWPE acetabular components oxidize *in vivo*. *Biomaterials*, 1993; **14**: 643–647.
 93. Lipiński P, Bieliński D, Okrój W, Jakubowski W, Klimek L, Jagielski J. Biomedical aspects of ion bombardment of polyethylene. *Vacuum*, 2009; **83** (Suppl.): S200–S203.
 94. Stern T, Cohn D. Surface tailoring of biomedical polymers: An FTIR study. *J. Appl. Polym. Sci.*, 2001; **81**: 2203–2209.
 95. Dadsetan M, Christenson EM, Unger F, Ausborn M, Kissel T, Hiltner A, Anderson JM. *In vivo* biocompatibility and biodegradation of poly(ethylene carbonate). *J. Control. Release*, 2003; **93**: 259–270.
 96. Bruni P, Conti C, Corvi A, Rocchi M, Tosi G. Damaged polyethylene acetabular cups microscopy FT-IR and mechanical determinations. *Vibrat. Spectr.*, 2002; **29**: 103–107.
 97. Rocha MF, Mansur AAP, Mansur HS. FTIR investigation of UHMWPE oxidation submitted to accelerated aging procedure. *Macromol. Symp.*, (Special Issue: *Modern Trends in Polymer Science*) 2010; **296**: 487–492.
 98. Pezzotti G, Kumakura T, Yamada K, Tateiwa T, Puppulin L, Zhu W, Yamamoto K. Confocal Raman spectroscopic analysis of cross-linked ultra-high molecular weight polyethylene for application in artificial hip joints. *J. Biomed. Opt.*, 2007; **12**: 014011-1–14.
 99. Pezzotti G. Stress microscopy and confocal Raman imaging of load-bearing surfaces in artificial hip joints. *Expert Rev. Med. Devices*, 2007; **4**: 165–189.
 100. Pezzotti G. Raman piezo-spectroscopic analysis of natural and synthetic biomaterials. *Anal. Bioanal. Chem.*, 2005; **381**: 577–590.
 101. Kalin M, Novak S, Vizintin J. Wear and friction behavior of alumina ceramics in aqueous solutions with different pH. *Wear*, 2003; **254**: 1141–1146.
 102. Ramer BD. Characterization of biomaterial surfaces. *Cardiovasc. Pathol.*, 1993; **2**: 875–1005.

103. Hall SR, Fischer TE, Gruffel P, Carry C. Effect of grain boundary dopants an mean grain size on tribomechanical behavior of highly purified α -alumina in the mild wear regime. *Wear*, 1995; **181-183**: 165-167.
104. West GD, Perkins JM, Lewis MH. The effect of rare earth dopants on grain boundary cohesion in alumina. *J. Eur. Ceram. Soc.*, 2007; **27**: 1913-1918.
105. Raghavan S, Wang H, Porter WD, Dinwiddie RB, Mayo MJ. Thermal properties of zirconia co-doped with trivalent and pentavalent oxides. *Acta Mater.*, 2001; **49**: 169-179.
106. Guo X, Wang Z. Effect of niobia on the defect structure of yttria-stabilized zirconia. *J. Eur. Ceram. Soc.*, 1998; **18**: 237-240.
107. Hall RM, Siney P, Unsworth A, Wroblewski BM. The effect of surface topography of retrieved femoral heads on the wear of UHMWPE sockets. *Med. Eng. Phy.*, 1997; **19**: 711-719.
108. Puloski SKT, McCalden RW, MacDonald SJ, Bourne RB, Rorabeck CH. Surface analysis of posterior stabilized femoral components used in total knee arthroplasty. *J. Arthroplasty*, 2003; **18**: 822-826.
109. Lakdawala A, Todo S, Scott G. The significance of surface changes on retrieved femoral components after total knee replacement. *J. Bone Joint Surg. (Br.)*, 2005; **87-B**: 796-799.
110. Pezzotti G, Saito T, Padeletti G, Cossari P, Yamamoto K. Nano-scale topography of bearing surface in advanced alumina/zirconia hip joint before and after severe exposure in water vapor environment. *J. Orthop. Res.*, 2010; **28**: 762-766.
111. Williams SR, Wu JJ, Unsworth A, Khan I. Tribological and surface analysis of 38 mm alumina-as-cast Co-Cr-Mo total hip arthroplasties. *Proc. Inst. Mech. Eng. H*, 2009; **223**: 941-954.
112. Currier BH, Currier JH, Mayor MB, Kimberly AL, Collier JP, Van Citters DW. Evaluation of oxidation and fatigue damage of retrieved crossfire polyethylene acetabular cups. *J. Bone Joint Surg. (Am.)*, 2007; **89**: 2023-2029.
113. Currier BH, Van Citters DW, Currier JH, Collier JO. *In vivo* oxidation in remelted highly cross-linked retrievals. *J. Bone Joint Surg. (Am.)*, 2010; **92**: 2409-2418.
114. Taddei P, Affatato S, Fagnano C, Toni A. Oxidation in ultrahigh molecular weight polyethylene an cross-linked polyethylene acetabular cups tested against roughened femoral heads in a hip joint simulator. *Biomacromolecules*, 2006; **7**: 1912-1920.

115. Chenery DH. Detection of peroxy species in ultra-high-molecular weight polyethylene by Raman spectroscopy. *Biomaterials*, 1997; **18**: 415–419.
116. Kumakura T, Puppulin L, Yamamoto K, Takahashi Y, Pezzotti G. In depth oxidation and strain profiles in UHMWPE acetabular cups non-destructively studied by confocal Raman microprobe spectroscopy. *J. Biomater. Sci. Polym. Ed.*, 2009; **20**: 1809–1822.
117. Pezzotti G, Porporati AA. Raman spectroscopic analysis of phase-transformation and stress patterns in zirconia hip joints. *J. Biomed. Opt.*, 2004; **9**: 372–384.
118. Simon V, Popa C, Muresan D, Simon S. Vibrational investigation of sintered titanium biomaterials. *J. Optoelectron. Adv. Mater.*, 2006; **8**: 540–542.
119. Hill MR, Catledge SA, Konovalov V, Clem WC, Chowdhury SA, Etheridge BS, Stanishevsky A, Lemons JE, Vohra YK, Eberhardt AW. Tribological evaluation of nanostructured diamond coatings and CoCr against ultra-high molecular weight polyethylene. *J. Biomed. Mater. Res. B: Appl. Biomater.*, 2008; **85**: 140–148.
120. Pezzotti G, Tateiwa T, Zhu W, Kumakura T, Yamada K, Yamamoto K. Fluorescence spectroscopic analysis of surface and subsurface residual stress fields in alumina hip joints. *J. Biomed. Opt.*, 2006; **11**: 024009-1–09.
121. Tateiwa T, Clarke IC, Pezzotti G, Sedel L, Kumakura T, Shishido T, Yamamoto K. Surface micro-analyses of long-term worn retrieved “Osteal™” alumina ceramic total hip replacement. *J. Biomed. Mater. Res. B*, 2007; **83-B**: 562–570.
122. Pezzotti G, Munisso MC, Lessnau K, Zhu W. Quantitative assessments of residual stress fields at the surface of alumina hip joints. *J. Biomed. Mater. Res. B*, 2010; **95B**: 250–262.
123. Puppulin L, Takahashi Y, Zhu W, Sugano N, Pezzotti G. Polarized Raman analysis of the molecular and residual strain on the surface of retrieved polyethylene tibial plates. *Acta Biomater.*, 2011; **7**: 1150–1159.
124. Takahashi Y, Puppulin L, Zhu W, Pezzotti G. Raman tensor analysis of ultra-high molecular weight polyethylene and its application to study retrieved hip joint components. *Acta Biomater.*, 2010; **6**: 3583–3594.
125. Wan K, Zhu W, Pezzotti G. Determination of in-depth probe response function using spectral perturbation methods. *J. Appl. Phys.*, 2005; **98**: 113101-1–7.

126. Zhu W, Zhu JL, Ge WY, Pezzotti G. A photo-stimulated spectroscopic method for spatially resolved stress analysis in hetero-epitaxial films. *J. Phys. D: Appl. Phys.*, 2009; **42**: 015505-1-8.
127. Caspers PJ, Lucassen GW, Puppels GJ. Combined *in vivo* confocal Raman spectroscopy and confocal microscopy of human skin. *Biophys. J.*, 2003; **85**: 572-580.
128. Hirotani H, Ito T. Scanning electron microscopy of the articular surfaces of the hip joint disorders. *Anat. Anz.*, 1975; **138**: 29-38.
129. Cullen JC, Tietjens BR, Poon J, Gavin JB. A scanning electron microscopic study of wear in the plastic components of prosthetic knee and hip joints. *Aust. N. Zeal. J. Surg.*, 1977; **47**: 189-192.
130. McCall J. Scanning electron microscopy study of articular cartilage. *Lancet*, 1968; **2**: 1194.
131. Clarke IC. Surface characteristics of human articular cartilage — a scanning electron microscope study. *J. Anat.*, 1971; **108**: 23-30.
132. Cameron HU, Macnab I, Anderson W. Hemiarthroplasty: A histological and scanning electron microscope study. *J. Biomed. Mater. Res.*, 1974; **8**: 221-230.
133. Sammons R, Marquis P. Application of the low vacuum scanning electron microscope to the study of biomaterials and mammalian cells. *Biomaterials*, 1997; **18**: 81-86.
134. Curtis ASG. Cell reactions with biomaterials: the microscopies. *Eur. Cells Mater.*, 2001; **1**: 59-65.
135. Richards RG, Gwynn I. Backscattered electron imaging of the undersurface of resin-embedded cells by field emission scanning electron microscopy. *J. Microsc.*, 1995; **177**: 43-52.
136. Richards RG, Gwynn I, Bundy KJ, Rahn BA. Microjet impingement followed by scanning electron microscopy as a qualitative technique to compare cellular adhesion to various biomaterials. *Cell Biol. Int.*, 1995; **19**: 1015-1024.
137. Ramer BD. Surface characterization of Biomaterials, by electron spectroscopy for chemical analysis. *Ann. Biomed. Eng.*, 1983; **11**: 313-336.
138. Godec M, Kocijan A, Dolinar D, Mandrino D, Jenko M, Antolič V. An investigation of the aseptic loosening of an AISI 316L stainless steel hip prosthesis. *Biomed. Mater.*, 2010; **5**: 045012-1-08.
139. Gordin DM, Gloriant T, Bohn M, Guillou A, Thibon I, Ansel D. Characterization of a laser-nitride titanium alloy by electron backscattered diffraction and electron probe microanalysis. *Surf. Interf. Anal.*, 2005; **37**: 1161-1167.

140. Checa AG, Okamoto T, Ramirez J. Organization pattern of nacre in Pteriidae (Bivalvia: Mollusca) explained by crystal competition. *Proc. Biol. Sci.*, 2006; **273**: 1329–1337.
141. MacDonald J, Freer A, Cusack M. Alignment of crystallographic *c*-axis throughout the four distinct microstructural layers of the oyster *Crassostrea gigas*. *Cryst. Growth Des.*, 2010; **10**: 1243–1246.
142. Goetze J, Heimann RB, Hildebrandt H, Gburek U. Microstructural investigation into calcium phosphate biomaterials, by spatially resolved cathodoluminescence. *Mat.-wiss. u. Werkstofftech.* 2001; **32**: 130–136.
143. Sprio S, Pezzotti G, Celotti G, Landi E, Tampieri A. Raman and cathodoluminescence spectroscopies of magnesium-substituted hydroxyapatite powders. *J. Mater. Res.*, 2005; **20**: 1009–1016.
144. Gross KA, Phillips MR. Identification and mapping of the amorphous phase in plasma-sprayed hydroxyapatite coatings using scanning cathodoluminescence microscopy. *J. Mater. Sci. Mater. Med.*, 1998; **9**: 797–802.
145. Zhu W, Munisso MC, Matsutani A, Ge W, Pezzotti G. Stress perturbation method for the assessment of cathodoluminescence probe response functions. *Appl. Spectr.*, 2009; **63**: 185–191.
146. Boyde A, Reid SA. New methods for cathodoluminescence in the scanning electron microscope. *Scan. Electron Microsc.*, 1983; **4**: 1803–1814.
147. Ritter E, Greenspan DC, Palmer RA, Hench LL. Use of fracture mechanics theory in lifetime predictions for alumina and bioglass-coated alumina. *J. Biomed Mater. Res.*, 1979; **13**, 251–263.
148. Lychkovs'kyl EI. Evaluation of the service life of a hip joint made of 08Kh18N10T steel by the methods of fracture mechanics. *Mater. Sci.*, 2005; **41**: 247–252.
149. Ritchie RO. Fatigue and fracture of pyrolytic carbon: a damage-tolerant approach to structural integrity and life prediction in “ceramic” heart valve prostheses. *J. Heart Valve Dis.*, 1996; **5** (suppl. I): S9–S31.
150. McKellop H, Clarke IC, Markolf KL, Amstutz HC. Wear characteristics of UHMWPE polyethylene: A method for accurately measuring extremely low wear rates. *J. Biomed. Mater. Res.*, 1978; **12**: 895–927.
151. Bowsher JG. A hip simulator study of the influence of patient activity level on the wear of crosslinked polyethylene under smooth and roughened femoral conditions. *Wear*, 2001; **250**: 167–179.

152. Morrison DE. A prototype scanning stylus profilometer for rapid measurement of small surface areas. *Int. J. Machine Tools Manuf.*, 1995; **35**: 325–331.
153. Poon CY, Bhushan B. Comparison of surface roughness measurements by stylus profiler, AFM and non-contact optical profiler. *Wear*, 1995; **190**: 76–88.
154. Wyant JC, Koliopoulos CL, Bhushan B, Basila D. Development of a three-dimensional noncontact digital optical profiler. *ASME J. Tribol.*, 1986; **108**: 1–8.
155. Bhushan B, Wyant JC, Koliopoulos CL. Measurement of surface topography of magnetic tapes by Mirau interferometry. *Appl. Opt.*, 1985; **24**: 1489–1497.
156. Bhushan B, Wyant JC, Koliopoulos CL. A new three-dimensional digital optical profiler. *Wear*, 1988; **122**: 301–312.
157. Lange SR, Bhushan B. Use of two- and three-dimensional noncontact surface profiler for tribology application. *Surf. Topograp.*, 1988; **1**: 277–290.
158. Wang SH, Quan C, Tay CJ, Shang HM. Surface roughness measurement in the submicrometer range using laser scattering. *Opt. Eng.*, 2000; **39**: 1597–1601.
159. Tortonese M, Barrett RC, Quate CF, Edward L. Atomic resolution with an atomic force microscope using piezoresistive detection. *Appl. Phys. Lett.*, 1993; **62**: 834–836.
160. Giessibl FJ, Quate CF. Exploring the nanoworld with atomic force microscopy. *Phys. Today*, 2006; **59**: 44–50.
161. Wade LA, Shapiro IR, Ma Z, Quake SR, Collier CP. Correlating AFM probe morphology to image resolution for single-wall carbon nanotube tips. *Nano Lett.*, 2004; **4**: 725–731.
162. Velegol SB, Pardi S, Li X, Velegol D, Logan BE. AFM imaging artifacts due to bacterial cell height and AFM tip geometry. *Langmuir*, 2003; **19**: 851–857.
163. Emerson RJ, Camesano TA. On the importance of precise calibration techniques for an atomic force microscope. *Ultramicroscopy*, 2006; **106**: 413–422.
164. Wenzler LA, Moyes GL, Raikar GN, Hansen RL, Harris JM, Beebe Jr. TP. Measurements of single-molecule bond-rupture forces between self-assembled monolayers of organosilanes with the atomic force microscope. *Langmuir*, 1997; **13**: 3761–3768.

165. Butt H-J, Kappl M, Mueller H, Paiteri R, Meyer W, Ruhe J. Steric forces measured with the atomic force microscope at various temperatures. *Langmuir*, 1999; **15**: 2559–2565.
166. Burnham NA, Colton RJ. Measuring the nanomechanical properties and surface forces of materials using an atomic force microscope. *J. Vacuum Sci. Tech.*, 1989; **7**: 2906–2913.
167. Burnham NA, Colton RJ, Pollock HM. Interpretation of force curves in atomic force microscopy. *Nanotechnology*, 1993; **4**: 64–80.
168. Burnham NA, Gremaud G, Kulik AJ, Gallo P-J, Oulevey F. Materials' properties measurements: Choosing the optimal scanning probe microscope configuration. *J. Vacuum Sci. Tech.*, 1996; **14**: 1308–1312.
169. Landman U, Luedtke WD, Burnham NA, Colton RJ. Atomistic mechanisms and dynamics of adhesion, nanoindentation and fracture. *Science*, 1990; **248**: 454–461.
170. Todd BA, Eppell SJ, Zypman FR. Squeezing out hidden force information from scanning force microscopes. *Appl. Phys. Lett.*, 2001; **79**: 1888–1890.
171. Burnham NA, Kulik AJ. Surface forces and adhesion. In Bhushan B (Ed.) *Handbook of micro/nano tribology*, CRC Press, Boca Raton, 2nd Edition, pp. 247–271, 1999.
172. Lee S-W, Sigmund WM. AFM study of repulsive van der Waals forces between Teflon AFTM thin film and silica or alumina. *Colloids Surf. A*, 2002; **204**: 43–50.
173. Dufrene YF, Boonaert CJP, van der Mei HC, Busscher HJ, Rouxhet PG. Probing molecular interactions and mechanical properties of microbial cell surfaces by atomic force microscopy. *Ultramicroscopy*, 2001; **86**: 113–120.
174. Touhami A, Hoffmann B, Vasella A, Denis FA, Dufrene YF. Probing specific lectin-carbohydrate interactions using atomic force microscopy imaging and force measurements. *Langmuir*, 2003; **19**: 1745–1751.
175. Lee GU, Chrisey LA, Colton RJ. Direct measurement of the forces between complementary strands of DNA. *Science*, 1994; **266**: 771–773.
176. Li X, Logan BE. Analysis of bacterial adhesion using a gradient force analysis and colloid probe atomic force microscopy. *Langmuir*, 2004; **20**: 8817–8822.
177. Ong Y-L, Razatos A, Georgiou G, Sharma MM. Adhesion forces between *E. coli* bacteria and biomaterial surfaces. *Langmuir*, 1999; **15**: 2719–2725.

178. Razatos A, Ong Y-L, Boulay F, Elbert DL, Hubbell JA, Sharma MM, Georgiou G. Force measurements between bacteria and poly(ethylene glycol)-coated surfaces. *Langmuir*, 2000; **16**: 9155–9158.
179. Schwarz UD, Hoelscher H, Wiesendanger R. Atomic resolution in scanning force microscopy: Concepts, requirements, contrast mechanisms, and image interpretation. *Phys. Rev. B*, 2000; **62**: 13089–13097.
180. Burnham NA, Chen X, Hodges CS, Matei GA, Thoreson EJ, Roberts CJ, Davies MC, Tendler SJB. Comparison of calibration methods for atomic-force microscopy cantilevers. *Nanotechnology*, 2003; **14**: 1–6.
181. Cappella B, Dietler G. Force-distance curves by atomic force microscopy. *Surf. Sci. Rep.*, 1999; **34**: 1–104.
182. Cleveland JP, Manne S, Bocek D, Hansma PK. A nondestructive method for determining the spring constant of cantilevers for scanning force microscopy. *Rev. Sci. Instr.*, 1993; **64**: 403–405.
183. Torii A, Sasaki M, Hane K, Okuma S. A method for determining the spring constant of cantilevers for atomic force microscopy. *Meas. Sci. Technol.*, 1996; **7**: 179–184.
184. Ratner BD, Hoffman AS, Schoen FJ, Lemons JE. *Biomaterials, science: an introduction to materials in medicine*. Academic Press, California, 1996, p. 23–28, pp. 447–449.
185. Stout KJ, Blunt L. Applications of 3-D topography to bio engineering. *Int. J. Mach. Tools Manufact.*, 1995; **35**: 219–229.
186. Stout KJ, Blunt L. Nanometres to micrometres: three-dimensional surface measurement in bio-engineering. *Surf. Coating Tech.*, 1995; **71**: 69–81.
187. Tayebi N, Polycarpou AA. Modeling the effect of skewness and kurtosis on the static friction coefficient of rough surfaces. *Tribol. Int.*, 2004; **37**: 491–505.
188. Vahabi M, Jafari GR, Mansour N, Karimzadeh R, Zamiranvari J. Stochastic features of rough surfaces: analysis of laser-induced silicon surface modifications. *J. Stat. Mech.*, 2008; **2008**: 03002–1–6.
189. Dong WP, Sullivan PJ, Stout KJ. Comprehensive study of parameters for characterizing three-dimensional surface topography III: Parameters for characterizing amplitude and some functional properties. *Wear*, 1994; **178**: 29–35.
190. Long DA. *The Raman effect: A unified treatment of the theory of Raman scattering by molecules*. John Wiley & Sons. Ltd., New York (2002).

191. Penel G, Delfosse C, Descamps M, Leroy G. Composition of bone and apatitic Biomaterials, as revealed by intravital Raman micro-spectroscopy. *Bone*, 2005; **36**: 893–901.
192. Davies MC, Binns JS, Melia CD, Bourgeois D. Fourier transform Raman spectroscopy of polymeric Biomaterials, and drug delivery systems. *Spectrochim. Acta Part A: Molec. Spectr.*, 1990; **46**: 277–283.
193. Duraipandian S, Zheng W, Ng J, Low JJ, Ilancheran A, Huang Z. Simultaneous fingerprint and high wavenumber confocal Raman spectroscopy enhances early detection of cervical precancer *in vivo*. *Anal. Chem.*, 2012; **84**: 5913–5919.
194. Shin WS, Li XF, Schwartz B, Wunder SL, Baran GR. Determination of the degree of cure of dental resins using Raman and FT-Raman spectroscopy. *Dent. Mater.*, 1993; **9**: 317–324.
195. Swain RJ, Stevens MM. Raman microspectroscopy for non-invasive biochemical analysis of single cells. *Biochem. Soc. Trans.*, 2007; **35**: 544–549.
196. de Carmejane O, Morris MD, Davis MK, Stixrude L, Tecklenburg M, Rajachar RM, Kohn DH. Bone chemical structure response to mechanical stress studied by high pressure Raman spectroscopy. *Calcif. Tissue Int.*, 2005; **76**: 207–213.
197. Duncan D, Reintjes J, Manuccia TJ. Scanning coherent anti-Stokes Raman microscope. *Opt. Lett.*, 1982; **7**: 350–352.
198. Cheng J-X, Book LD, Xie XS. Polarization coherent anti-Stokes Raman scattering microscopy. *Opt. Lett.*, 2001; **26**: 1341–1343.
199. Kee TW, Cicerone MT. Simple approach to one-laser, broadband coherent anti-Stokes Raman scattering microscopy. *Opt. Lett.*, 2004; **29**: 2701–2703.
200. Kneipp, K., Wang Y, Kneipp H, Perelman LT, Itzkan I, Dasari RR, Feld MS. Single molecule detection using surface-enhanced Raman scattering (SERS). *Phys. Rev. Lett.*, 1997; **78**: 1667–1670.
201. Vannier C, Yeo B-S, Melanson J, Zenobi R. Multifunctional microscope for far-field and tip-enhanced Raman spectroscopy. *Rev. Sci. Instr.*, 2006; **77**: 023104-1–5.
202. Lipkin DM, Clarke DR. Sample-probe interactions: Sampling microscopic property gradients. *J. Appl. Phys.*, 1995; **77**: 1855–1863.
203. Atkinson A, Jain SC. Spatially resolved stress analysis using Raman spectroscopy. *J. Raman Spectrosc.*, 1999; **30**: 885–891.

204. Onorato RM, Muraki N, Knutsen KP, Saykally RJ. Chirped coherent anti-Stokes Raman scattering as a high-spectral- and spatial-resolution microscopy. *Opt. Lett.*, 2007; **32**: 2858–2860.
205. Tabaksblat R, Meier RJ, Kip BJ. Confocal Raman microspectroscopy: Theory and application to thin polymer samples. *Appl. Spectrosc.*, 1992; **46**: 60–68.
206. Williams KPJ, Pitt GD, Batchelder DN, Kip BJ. Confocal Raman microspectroscopy using a stigmatic spectrograph and CCD detector. *Appl. Spectrosc.*, 1994; **48**: 232–235.
207. Pezzotti G, Sueoka H, Porporati AA, Manghnani M, Zhu W. Raman tensor elements for wurtzitic GaN and their application to assess crystallographic orientation at film/substrate interfaces. *J. Appl. Phys.*, 2011; **110**: 013527-1-10.
208. Wan K, Tochino S, Zhu W, Ohtsuka S, Pezzotti G. Quantitative evaluation of probe response functions for Raman and fluorescence bands of single-crystalline and polycrystalline Al₂O₃. *J. Phys. D: Appl. Phys.*, 2010; **43**: 205501–205508.
209. Turrell G. Analysis of polarization measurements in Raman microspectroscopy. *J. Raman Spectrosc.*, 1984; **15**: 103–108.
210. Fukatsu K, Zhu W, Pezzotti G. Raman tensor analysis of baddeleyite single-crystal and its application to define crystallographic domains in polycrystalline zirconia. *Phys. Status Solidi (b)*, 2010; **247**: 278–287.
211. Munisso MC, Zhu W, Pezzotti G. Raman tensor analysis of sapphire single crystal and its application to define crystallographic orientation in polycrystalline alumina. *Phys. Status Solidi (b)*, 2009; **246**: 1893–1900.
212. Takahashi Y, Puppulin L, Pezzotti G. Raman tensor analysis of ultra-high molecular weight polyethylene and its application to study retrieved hip-joint components. *Acta Biomater.*, 2010; **6**: 3583–3594.
213. Jones JR, Vats A, Notingher L, Gough JE, Tolley NS, Polak JM, Hench LL. *In situ* monitoring of chondrocyte response to bioactive scaffolds using Raman spectroscopy. *Bioceramics*, 2005; **17**: 623–626.
214. Nalla RK, Kruzic JJ, Kirmey JH, Balooch M, Ager JW, Ritchie RO. Role of microstructure in the aging-related deterioration of the toughness of human cortical bone. *Mater. Sci. Eng. C*, 2006; **26**: 1251–1260.
215. Galetz MC, Glatzel U. Molecular deformation mechanisms in UHMWPE during tribological loading in artificial joints. *Tribol. Lett.*, 2010; **38**: 1–13.

216. Pezzotti G. Severe evaluation of mechanical properties and phase stability in advanced ceramic composite for artificial joints. *J. Bone Joint Surg. (Br.)*, 2010; **92-B** (Suppl. I): 167–172.
217. Pezzotti G, Takahashi Y, Takamatsu S, Puppulin L, Nishii T, Miki H, Sugano N. Non-destructively differentiating the roles of creep, wear and oxidation in long-term *in vivo* exposed polyethylene cups. *J. Biomater. Sci. Polym. Ed.*, 2011; **22**: 2165–2184.
218. Bertoluzza A, Fagnano C, Monti P, Simoni R, Tinti A, Tosi MR, Caramazza R. Raman spectroscopy in the study of biocompatibility. *Clin. Mater.*, 1992; **9**: 49–68.
219. Bertoluzza A, Monti P, Arciola R, Pizzoferrato A. Structural properties and biocompatibility of polymers used in ophthalmology. *Clin. Mater.*, 1991; **8**: 165–169.
220. Reggiani M, Tinti A, Taddei P, Visentin M, Stea S, De Clerico M, Fagnano C. Phase transformation in explanted highly crystalline UHMWPE acetabular cups and debris after *in vivo* wear. *J. Mol. Struct.*, 2006; **785**: 98–105.
221. Affatato S, Bersaglia G, Emiliani D, Foltran I, Taddei P, Reggiani M, Ferrieri P, Toni A. The performance of gamma- and EtO-sterilised UHMWPE acetabular cups tested under severe simulator conditions. Part 2: wear particle characteristics with isolation protocols. *Biomaterials*, 2003; **24**: 4045–4055.
222. Abbiss JB, Heeg B. Imaging piezospectroscopy. *Rev. Sci. Instr.*, 2008; **79**: 123105-1–9.
223. Zhu W, Pezzotti G. Raman analysis of three-dimensionally graded stress tensor components in sapphire. *J. Appl. Phys.*, 2011; **109**: 073502-1-13.
224. He J, Clarke DR. Determination of the piezospectroscopic coefficients for chromium-doped sapphire. *J. Am. Ceram. Soc.*, 1995; **78**: 1347–1353.
225. Gallas MR, Chu YC, Piermarini GJ. Calibration of the Raman effect in α -Al₂O₃ ceramic for residual stress measurements. *J. Mater. Res.*, 1995; **10**: 2817–2822.
226. Pezzotti G, Müller WH. Micromechanics of fracture in a ceramic/metal composite studied by *in situ* fluorescence spectroscopy I: Foundations and stress analysis. *Continuum Mech. Therm.*, 2002; **14**: 113–126.
227. Clarke DR, Adar F. Measurement of the crystallographically transformed zone produced by fracture in ceramics containing tetragonal zirconia. *J. Am. Ceram. Soc.*, 1982; **65**: 284–288.
228. Kalasinsky VF. Biomedical applications of infrared and Raman microscopy. *Appl. Spectr. Rev.*, 1996; **31**: 193–249.

229. Liza S, Haseeb ASMA, Masjuki HH, Abbas AA. The wear behavior of cross-linked UHMWPE under dry and bovine calf serum-lubricated conditions. *Tribol. Trans.*, 2013; **56**: 130–140.
230. Okubo Y, Teramura S, Niwa Y, Ibaraki K, Murata K, Hyon S-H, Pezzotti G, Tomita N. Strain-induced crystallization and orientation of vitamin E-blended ultrahigh molecular weight polyethylene. *Biomed. Mater. Eng.*, 2009; **19**: 431–439.
231. Puértolas JA, Martínez-Nogués V, Martínez-Morlanes MJ, Mariscal MD, Medel FJ, López-Santos C, Yubero F. Improved wear performance of ultra high molecular weight polyethylene coated with hydrogenated diamond like carbon. *Wear*, 2010; **269**: 458–465.
232. Bell LD, Kaiser WJ. Ballistic-electron-emission microscopy: a nanometer-scale probe of interfaces and carrier transport. *Annu. Rev. Mater. Sci.*, 1996; **26**: 189–222.
233. Pezzotti G. Spatially resolved Raman and cathodoluminescence probes in electronic materials: basics and applications. *Phys. Status Solidi (a)*, 2011; **208**: 976–999.
234. Fisher PJ, Wessels WS, Dietz AB, Prendergast FG. Enhanced biological cathodoluminescence. *Opt. Comm.*, 2008; **281**: 1901–1908.
235. Waychunas GA. Luminescence, X-ray emission and new spectroscopies. *Rev. Miner.*, 1988; **18**: 639–698.
236. Remond G, Cesbron F, Chapoulie R, Ohnenstetter D, Rouques-Carnes C, Schvoerer M. Cathodoluminescence applied to the microcharacterization of mineral materials: a present status in experimentation and interpretation. *Scanning Microsc.*, 1992; **6**: 23–69.
237. Marfunin AS. *Advanced Mineralogy. Vol. 2 — Methods and instrumentations: Results and recent developments*. Springer: Berlin, Heidelberg, New York (1995).
238. Marfunin AS. *Spectroscopy, luminescence and radiation centres in minerals*. Translated from Russian by Schiffer VV. Springer: Berlin (1979).
239. Richter DK, Goette Th, J. Goetze, Neuser RD. Progress in application of cathodoluminescence (CL) in sedimentary petrology. *Mineral. Petrol.*, 2003; **79**: 127–166.
240. Gillhaus A, Habermann D, Meijer J, Richter DK. Cathodoluminescence spectroscopy and micro-PIXE: combined high resolution Mn-analyses in dolomites — First results. *Nucl. Instr. Meth. Phys. Res. Section B*, 2000; **161–163**: 842–845.
241. Salh R, von Czarowski A, Fitting H-J. Cathodoluminescence of non-stoichiometric silica: The role of oxygen. *J. Non-Cryst. Solids*, 2007; **353**: 546–549.

242. Heimke G, Griss P. Ceramic implant materials. *Med. Biol. Eng. Comp.* 1980; **18**: 503–510.
243. Liu D, Robertson J. Oxygen vacancy levels and interfaces of Al_2O_3 . *Microelectr. Eng.*, 2009; **66**: 1668–1671.
244. Duwez P, Brown Jr. FH, Odell F. The zirconia-yttria system. *J. Electrochem. Soc.*, 1951; **98**: 356–362.
245. Lange FF. Transformation toughening: Part 3, experimental observations in the $\text{ZrO}_2\text{-Y}_2\text{O}_3$ system. *J. Mater. Sci.*, 1982; **17**: 240–247.
246. Fabris S, Paxton AT, Finnis MW. A stabilization mechanism of zirconia based on oxygen vacancies only. *Acta Mater.*, 2002; **50**: 5171–5178.
247. Suresh A, Mayo MJ, Porter D. Thermodynamics of the tetragonal-to-monoclinic phase transformation in fine and nanocrystalline yttria-stabilized zirconia powders. *J. Mater. Res.*, 2003; **18**: 2912–2921.
248. Badwal SPS. Zirconia-based solid electrolytes: microstructure, stability and ionic conductivity. *Solid State Ionics*, 1992; **52**: 23–32.
249. Jurado E, Bouvier P, Lucazeau G. Crystallite size effect on the tetragonal–monoclinic transition of undoped nano-crystalline zirconia studied by XRD and Raman spectrometry. *J. Solid State Chem.*, 2000; **149**: 399–407.
250. Pezzotti G, Saito T, Takahashi Y, Fukatsu K, Sugano N. Surface topology of advanced alumina/zirconia composite femoral head as compared with commercial femoral heads made of monolithic zirconia. *J. Am. Ceram. Soc.*, 2011; **94**: 945–950.
251. Chowdhury S, Vohra YK, Lemons JE, Ueno M, Ikeda J. Accelerating aging of zirconia femoral head implants: Change of surface structure and mechanical properties. *J. Biomed. Mater. Res. B*, 2007; **81B**: 486–492.
252. Adams BL, Wright SI, Kunze K. Orientation imaging: the emergence of a new microscopy. *Metall. Trans.*, 1993; **24A**: 819–831.
253. Dingley DJ. On-line determination of crystal orientation and texture determination in an SEM. *Proc. Royal Microsc. Soc.*, 1984; **19**: 74–75.
254. Dingley DJ. Progressive steps in the development of electron backscatter diffraction and orientation imaging microscopy. *J. Microsc.*, 2004; **213**: 214–224.
255. Humphreys FJ. Review: Grain and subgrain characterisation by electron backscatter diffraction. *J. Mat. Sci.*, 2001; **36**: 3833–3854.

256. Chen J, Browne M, Taylor M, Gregson PJ. Application of an interface failure model to predict fatigue crack growth in an implanted metallic femoral stem. *Computer Meth. Progr. Biomed.*, 2004; **73**: 249–256.
257. Wang SC, Browne M, Ubhi HS, Starink MJ. Determination of the fatigue fracture planes of Co–Cr–Mo biomedical alloys using electron backscatter diffraction. *J. Microsc.*, 2005; **217**: 118–121.
258. Randle V. A methodology for grain boundary plane assessment by single-section trace analysis. *Script Mater.*, 2001; **44**: 2789–2794.
259. Wang SC, Aindow M, Starink MJ. Effect of self-accommodation on α/α boundary populations in pure titanium. *Acta Mater.*, 2003; **51**: 2485–2503.
260. Wang SC, Starink MJ. A simple approach to the determination of the crystallographic orientation: applications and accuracy. *J. Microsc.*, 2003; **211**: 130–136.
261. Sun D, Wharton JA, Wood RJK. Micro-abrasion mechanisms of cast CoCrMo in simulated body fluids. *Wear*, 2009; **267**: 1845–1855.
262. Weibull W. A statistical distribution of wide applicability. *J. Appl. Mech.*, 1951; **18**: 293–297.
263. Kovarik RE, Ergle JW, Fairhurst CW. Effects of specimen geometry on the measurement of fracture toughness. *Dent. Mater.*, 1991; **7**: 166–169.
264. Taira M, Nomura Y, Wakasa K, Yamaki M, Matsui A. Studies on fracture toughness of dental ceramics. *J. Oral Rehab.*, 1990; **17**: 551–563.
265. Fujishima A, Ferracane JL. Comparison of four modes of fracture toughness testing for dental composites. *Dent. Mater.*, 1996; **12**: 38–43.
266. Brown WF, Srawley JE. Plane strain crack toughness testing of high strength metallic materials. *ASTM Spec. Tech. Publ.*, 1967; **410**: 13–14.
267. White SN, Luo W, Paine ML, Fong H, Sarikaya M, Snead ML. Biological organization of hydroxyapatite crystallites into a fibrous continuum toughens and controls anisotropy in human enamel. *J. Dent. Res.*, 2001; **80**: 321–326.
268. Nalla RK, Kinney JH, Ritchie RO. On the fracture of human dentin: Is it stress- or strain-controlled? *J. Biomed. Mater. Res. A*, 2003; **67A**: 484–495.
269. Kahler B, Swain MV, Moule A. Fracture-toughening mechanisms responsible for differences in work to fracture of hydrated and dehydrated dentine. *J. Biomech.*, 2003; **36**: 229–237.
270. Needleman A, van der Giessen E. Micromechanics of fracture: Connecting physics to engineering. *MRS Bull.*, 2001; **26**: 211–214.

271. De Aza AH, Chevalier J, Fantozzi G, Schehl M, Torrecillas R. Crack growth resistance of alumina, zirconia and zirconia toughened alumina ceramics for joint prostheses. *Biomaterials*, 2002; **23**: 937–945.
272. Nalla RK, Kruzic JJ, Ritchie RO. On the origin of the toughness of mineralized tissue: microcracking or crack bridging? *Bone*, 2003; **34**: 790–798.
273. Garvie RC, Hannink RH, Pascoe RT. Ceramic steel? *Nature*, 1975; **258**: 703–704.
274. Hannink RH, Kelly PM, Muddle BC. Transformation toughening in zirconia-containing ceramics. *J. Am. Ceram. Soc.*, 2000; **83**: 461–487.
275. Stevens R, Evans P. Transformation toughening by dispersed polycrystalline zirconia. *Br. Ceram. Trans. J.*, 1984; **83**: 28–31.
276. Steinbrech RW. Toughening mechanisms for ceramic materials. *J. Eur. Ceram. Soc.*, 1992; **10**: 131–142.
277. Becher PF. Microstructural design of toughened ceramics. *J. Am. Ceram. Soc.*, 1991; **74**: 255–269.
278. Li C-W, Lui S-C, Goldacker J. Relation between strength, microstructure, and grain-bridging characteristics in *in situ* reinforced silicon nitride. *J. Am. Ceram. Soc.*, 1995; **78**: 449–459.
279. Sanchis-Alfonso V. Severe metallosis after unicompartmental knee arthroplasty. *Knee Surg. Sports Traumatol. Arthrosc.*, 2007; **15**: 361–364.
280. Coleman RF, Herrington, J, Scales JT. Concentration of wear products in hair, blood, and urine after hip replacement. *Br. Med. J.*, 1973; **1**: 527–529.
281. Pandit H, Glyn-Jones S, McLardy-Smith P, Gundle R, Whitwell D, Gibbons CL, Ostlere S, Athanasou N, Gill HS, Murray DW. Pseudotumours associated with metal-on-metal resurfacings. *J. Bone Joint Surg. (Br.)*, 2008; **90**: 847–851.
282. Pezzotti G. *In situ* study of fracture mechanisms in advanced ceramics using fluorescence and Raman microprobe spectroscopy. *J. Raman Spectr.*, 1999; **30**: 867–875.
283. Fett T, Munz D, Kouna Njiwa AB, Rödel J, Quinn GD. Bridging stresses in sintered reaction-bonded Si_3N_4 from COD measurements. *J. Eur. Ceram. Soc.*, 2005; **25**: 29–36.
284. Padture NP. *In situ*-toughened silicon carbide. *J. Am. Ceram. Soc.*, 1994; **77**: 519–523.

285. ISO 13356:1997. Implants for surgery — Ceramic materials based on yttria-stabilized tetragonal zirconia (Y-TZP); 1997.
286. ISO 7206-10:2003. Implants for surgery — Partial and total hip prostheses — Part 10: Determination of resistance to static load of modular femoral heads; 2003.
287. Japanese Standards Association. *Test method for impact resistance of ceramic femoral head for hip-joint prostheses*. Japan Industrial Standard, JIS T 0308:2008. Japanese Standards Association, Tokyo, Japan, 2008.
288. Japanese Standards Association. *Testing methods for fracture toughness on high performance ceramics*. Japan Industrial Standard, JIS R 1607. Japanese Standards Association, Tokyo, Japan, 1990.
289. Munz D. Effect of specimen type on the measured values of fracture toughness of brittle ceramics. In *Fracture Toughness of Ceramics*, Bradt RC, Evans AG, Hasselman DPH, Lange FF (Eds.). Plenum Press, New York, Vol. 6. pp. 1–26, 1983.
290. Nishida T, Hanaki Y, Pezzotti G. Effect of notch-root radius on the fracture toughness of a fine grained alumina. *J. Am. Ceram. Soc.*, 1994; **77**: 606–608.
291. Kruzic JJ, Kim DK, Koester KJ, Ritchie RO. Indentation techniques for evaluating the fracture toughness of biomaterials and hard tissues. *J. Mech. Behav. Biomed. Mater.* 2008; **2**: 384–395.
292. Sakar-Deliormanli A, Guden M. Microhardness and fracture toughness of dental materials by indentation method. *J. Biomed. Mater. Res. B*, 2006; **76B**: 257–264.
293. Cook RF, Pharr GM. Direct observation and analysis of indentation cracking in glasses and ceramics. *J. Am. Ceram. Soc.*, 1990; **73**: 787–817.
294. Anstis GR, Chantikul P, Lawn BR, Marshall DB. A critical evaluation of indentation techniques for measuring fracture toughness. I. Direct crack measurements. *J. Am. Ceram. Soc.*, 1981; **64**: 533–538.
295. Lawn BR, Evans AG, Marshall DB. Elastic/plastic indentation damage in ceramics: The median/radial crack system. *J. Am. Ceram. Soc.*, 1980; **63**: 574–581.
296. Rödel J, Kelly JF, Lawn BR. *In situ* measurements of bridged crack interfaces in the SEM. *J. Am. Ceram. Soc.*, 1990; **73**: 3313–3318.
297. Fett T, Koungra AB, Rödel J. Stresses and stress intensity factor from COD of Vickers indentation cracks. *J. Mater. Sci.*, 2004; **39**: 2219–2221.

298. Fett T, Njiwa ABK, Rödel J. Crack opening displacements of Vickers indentation cracks. *Eng. Fract. Mech.*, 2005; **72**: 647–659.
299. Meschke F, Raddatz O, Kolleck A, Schneider GA. *R*-curve behavior and crack-closure stresses in barium titanate and (Mg,Y)-PSZ ceramics. *J. Am. Ceram. Soc.*, 2000; **83**: 353–361.
300. Marshall DB, Lawn BR. Residual stress effects in sharp-contact cracking: I. *J. Mater. Sci.*, 1979; **14**: 2001–2012.
301. Burghard Z, Zimmermann A, Rödel J, Aldinger F, Lawn BR. Crack opening profiles of indentation cracks in normal and anomalous glasses. *Acta Mater.* 2004; **52**: 293–297.
302. ISO 6474-1:2010. Implants for surgery — Ceramic materials — Part 1: Ceramic materials based on high purity alumina; 2010.
303. ISO 6474-2: under development. Implants for surgery — Ceramic materials — Part 2: Composite materials based on a high purity alumina matrix with zirconia reinforcement; June 2010 (Enquiry state, full report circulated).
304. Weisse B, Zahner M, Weber W, Rieger W. Improvement of the reliability of ceramic hip joint implants. *J. Biomech.*, 2003; **36**: 1633–169.
305. Willman G. Ceramic femoral head retrieval data. *Clin. Orthop. Relat. Res.*, 2000; **379**: 22–28.
306. Pfaff H-G. Ceramic component failure and the role of proof testing. *Clin. Orthop. Relat. Res.*, 2000; **379**: 29–33.
307. Weisse B, Affolter C, Koller RE, Stutz A. Proof testing of ceramic femoral heads for hip joint implants. *Proc. Inst. Mech. Eng. H*, 2010; **224**: 1051–1059.
308. Kuntz M. Validation of a new high performance alumina matrix composite for use in total joint replacement. *Semin. Arthroplasty*, 2006; **17**: 141–145.
309. Piconi C, Maccauro G, Muratori F, Brach del Prever E. Alumina and zirconia ceramics in joint replacements. *J. Appl. Biomater. Biomech.*, 2003; **1**: 19–32.
310. Maher SA, Lipman JD, Curley LJ, Gilchrist M, Wright TM. Mechanical performance of ceramic acetabular liners under impact conditions. *J. Arthroplasty*, 2003; **18**: 936–941.
311. Willmann G, Kramer U. Ceramic cups for hip endoprostheses: Consideration of designs. *Biomed. Tech. (Berl.)*, 1998; **43**: 342–349.
312. Hench LL. Bioceramics: from concept to clinic. *J. Am. Ceram. Soc.*, 1991; **74**: 1487–1510.

313. Nair RP, Griffin D, Randall NX. The use of the pin-on-disk tribology test method to study three unique industrial applications. *Wear*, 2009; **267**: 823–827.
314. Korres S, Dienwiebel M. Design and construction of a novel tribometer with online topography and wear measurement. *Rev. Sci. Instrum.*, 2010; **81**: 063904-1–7.
315. Zemzemi F, Bensalem W, Rech J, Dogui A, Kapsa P. New tribometer designed for the characterization of the friction properties at the tool/chip/workpiece interface in machining. *Tribotest*, 2008; **14**: 11–25.
316. Patton S, Zabinski JS. Advanced tribometer for *in situ* studies of friction, wear, and contact condition — Advanced tribometer for friction and wear studies. *Tribol. Lett.*, 2002; **13**: 263–273.
317. Saikko V. A 12-station anatomic hip joint simulator. *Proc. Inst. Mech. Eng. H*, 2005; **219**: 437–448.
318. Goldsmith AA, Dowson D. A multi-station hip joint simulator study of the performance of 22 mm diameter zirconia-ultra-high molecular weight polyethylene total replacement hip joints. *Proc. Inst. Mech. Eng. H*, 1999; **213**: 77–90.
319. Maletsky LP, Hillberry BM. Simulating dynamic activities using a five-axis knee simulator. *J. Biomech. Eng.*, 2005; **127**: 123–133.
320. McKellop HA, D’Lima D. How have wear testing and joint simulator studies helped to discriminate among materials and designs? *J. Acad. Orthop. Surg.* 2008; **16** (Suppl. 1): S111–S119.
321. Ramamurti BS, Estok DM, Jasty M, Harris WH. Analysis of the kinematics of different hip simulators used to study wear of candidate materials for the articulation of total hip arthroplasties. *J. Orthop. Res.* 1998; **16**: 365–369.
322. Harris SJ, Krauss GG. Improved technique for measuring the ball volume removed in a ball-on-disk test. *Tribol. Lett.*, 2001; **10**: 187–188.
323. Bragdon CR, O’Connor DO, Lowenstein JD, Jasty M, Biggs SA, Harris WH. A new pin-on-disk wear testing method for simulating wear of polyethylene on cobalt-chrome alloy in total hip arthroplasty. *J. Arthroplasty*, 2001; **16**: 658–665.
324. Cho HJ, Wei WJ, Kao HC, Cheng CK. Wear behavior of UHMWPE sliding on artificial hip arthroplasty materials. *Mater. Chem. Phys.* 2004; **88**: 9–16.
325. Wang A, Stark C, Dumbleton JH. Mechanistic and morphologic origins of ultra-high molecular weight polyethylene wear debris in total

- joint replacement prostheses. *Proc. Inst. Mech. Eng. H*, 1996; **210**: 141–155.
326. Livermore J, Ilstrup D, Morrey B. Effect of femoral head size on wear of the polyethylene acetabular component. *J. Bone Joint Surg.*, 1990; **72A**: 518–528.
327. Magnissalis EA, Xenakis TA, Zacharis C. Wear of retrieved ceramic THA components — four matched pairs retrieved after 5–13 years in service. *J. Biomed. Mater. Res. A*, 2001; **58**: 593–598.
328. Landy MM, Walker PS. Wear of ultra-high-molecular-weight polyethylene components of 90 retrieved knee prostheses. *J. Arthroplasty*, 1988; **3** (Suppl.): S73–S85.
329. Gunter J, Rose RM. Long-term performance and wear of ultrahigh-molecular-weight polyethylene in total joint replacement prostheses: a brief overview and perspective. *J. Long Term Eff. Med. Implants*, 1994; **4**: 157–175.
330. Goldsmith AA, Dowson D, Isaac GH, Lancaster JG. A comparative joint simulator study of the wear of metal-on-metal and alternative material combinations in hip replacements. *Proc. Inst. Mech. Eng. H*, 2000; **214**: 39–47.
331. Dowson D. New joints for the Millennium: wear control in total replacement hip joints. *Proc. Inst. Mech. Eng. H*, 2001; **215**: 335–358.
332. Kerkwijk B, Garcia M, van Zyl WE, Winnubst AJA, Mulder EJ, Schipper DJ, Verweij H. Friction behaviour of solid oxide lubricants as second phase in α -Al₂O₃ and stabilized ZrO₂ composites. *Wear*, 2004; **256**: 182–189.
333. Kerkwijk B, Winnubst AJA, Verweij H, Metselaar HSC, Mulder EJ, Schipper DJ. Tribological properties of nanoscale alumina-zirconia composites. *Wear*, 1999; **225–229**: 1293–1302.
334. Stachowiak GW, Stachowiak GB. Unlubricated wear and friction of toughened zirconia ceramics at elevated temperatures. *Wear*, 1991; **143**: 277–295.
335. Sasaki S. The effects of the surrounding atmosphere on the friction and wear of alumina, zirconia, silicon carbide and silicon nitride. *Wear*, 1989; **134**: 185–200.
336. Dey AK, Biswas K. Dry sliding wear of zirconia-toughened alumina with different metal oxide additives. *Ceram. Int.* 2009; **35**: 997–1002.
337. Conoci S, Melandri C, De Portu G. Wear of 3Y-TZP containing compressive residual stresses at the surface. *J. Mater. Sci.*, 1999; **34**: 1009–1015.

338. Agraït N, Rubio G, Vieira S. Plastic deformation in nanometer scale contacts. *Langmuir*, 1996; **12**: 4505–4509.
339. Guicciardi S, Sciti D, Melandri C, Pezzotti G. Dry sliding wear behavior of nano-sized SiC pins against SiC and Si₃N₄ discs. *Wear*, 2007; **262**: 529–535.
340. Nakayama K, Martin J-M. Tribochemical reactions at and in the vicinity of a sliding contact. *Wear*, 2006; **261**: 235–240.
341. Singer IL. Mechanics and chemistry of solids in sliding contact. *Langmuir*, 1996; **12**: 4486–4491.
342. Singer IL, Dvorak SD, Wahl KJ, Scharf TW. Third body processes and friction of solid lubricants studied by *in situ* optical and Raman tribometry. *Tribol. Series*, 2001; **40**: 327–336.
343. Belin M, Martin JM. Triboscopy, a new approach to surface degradations of thin films. *Wear*, 1992; **156**: 151–160.
344. Bair S, Green I, Bhushan B. Measurements of asperity temperatures of a read/write head slider bearing in hard magnetic recording disks. *J. Tribol.*, 1991; **113**: 547–554.
345. Cann PM, Spikes HA. In-contact IR spectroscopy of hydrocarbon lubricants. *Tribol. Lett.*, 2005; **19**: 289–297.
346. Cheng CU, Stair PC. *In situ* study of multialkylated cyclopentane and perfluoropolyalkyl ether chemistry in concentrated contacts using ultraviolet Raman spectroscopy. *Tribol. Lett.*, 1998; **4**: 163–170.
347. Berthier Y, Godet M, Brendle M. Velocity accommodation in friction. *Tribol. Trans.* 1989; **32**: 490–496.
348. Sliney H. Dynamics of solid lubrication as observed by optical microscopy. *ASLE Trans.* 1977; **21**: 109–117.
349. Jullien A, Meurisse MH, Berthier Y. Determination of tribological history and wear through visualisation in lubricated contacts using a carbon-based composite. *Wear*, 1996; **194**: 116–125.
350. Israelachvili JN, Tabor D. The shear properties of molecular films. *Wear*, 1973; **24**: 386–390.
351. Donnet C. In *Handbook of Surface and Interface Analysis*. Riviere JC, Myhra S. (Eds.). Marcel Dekker, Inc., Chapter 16, pp. 697–745, 1998.
352. Joly-Pottuz L, Martin JM, Belin M, Dassenoy F. Study of inorganic fullerenes and carbon nanotubes by *in situ* Raman tribometry. *Appl. Phys. Lett.* 2007; **91**: 153107–1–3.
353. Cherif K, Gueroult B, Rigaud M. Al₂O₃–ZrO₂ debris life cycle during wear: effects of the third body on wear and friction. *Wear*, 1997; **208**: 161–168.

354. DIN 50 324:1992. *Testing of friction and wear*; 1992.
355. ASTM G 133–195:1996. *Standard test method for linearly reciprocating ball-on-flat sliding wear* (re-approved), 2002.
356. ASTM G 99–05:2010. *Standard test method for wear testing with a pin-on-disk apparatus*, 2010.
357. Buescher R, Taeger G, Dudzinski W, Gleising B, Wimmer MA, Fisher A. Subsurface microstructure of metal-on-metal hip joints and its relationship to wear particle generation. *J. Biomed. Mater. Res. B*, 2004; **72B**: 206–214.
358. Wimmer MA, Loos J, Heitkemper M, Fischer A. The acting wear mechanisms on metal-on-metal hip joint bearings — *In vitro* results. *Wear*, 2001; **250**: 129–139.
359. Wimmer MA, Sprecher C, Hauert R, Taeger G, Fischer A. Tribochemical reactions on metal-on-metal hip joint bearings — A comparison between *in vitro* and *in vivo* results. *Wear*, 2003; **255**: 1007–1014.
360. Kinbrum A, Vasilliou K, Lee SM, Unsworth A. A tribological and particle debris study of as-cast and heat treated CoCrMo alloy. *J. Bone Joint Surg. (Br.)*, 2010; **92B** (Supp. 1): 101.
361. Sinnett-Jones PE, Wharton JA, Wood RJK. Micro-abrasion-corrosion of a CoCrMo alloy in simulated artificial hip joint environments. *Wear*, 2005; **259**: 898–909.
362. Bowsher JG, Nevelos J, Williams PA, Shelton JC. “Severe” wear challenge to “as-cast” and “double heat-treated” large-diameter metal-on-metal hip bearings. *Proc. Inst. Mech. Eng. H*, 2006; **220**: 135–143.
363. Bowsher JG, Hussain A, Williams PA, Shelton JC. Metal-on-metal hip simulator study of increased wear particle surface area due to “severe” patient activity. *Proc. Inst. Mech. Eng. H*, 2006; **220**: 279–287.
364. Suh NP. An overview of the delamination theory of wear. *Wear*, 1977; **44**: 1–16.
365. Rainforth WM. The wear behaviour of oxide ceramics — a review. *J. Mater. Sci.*, 2004; **39**: 6705–6721.
366. Zeng P, Inkson BJ, Rainforth WM, Stewart T. Characterisation of alumina hip-joint wear by FIB microscopy. *J. Phys.: Conf. Ser.*, 2006; **26**: 343–346.
367. Barceinas-Sanchez JDO, Rainforth WM. On the role of plastic deformation during the mild wear of alumina. *Acta Mater.*, 1998; **46**: 6475–6483.
368. Hockey BJ. Plastic deformation of aluminium oxide by indentation and abrasion. *J. Am. Ceram. Soc.*, 1971; **54**: 223–231.

369. Inkson BJ. Dislocations and twinning activated by the abrasion of Al_2O_3 . *Acta Mater.*, 2000; **48**: 1883–1895.
370. Lagerlöf KPD, Heuer AH. Slip and twinning in sapphire ($\alpha\text{-Al}_2\text{O}_3$). *J. Am. Ceram. Soc.*, 1994; **77**: 385–397.
371. Brown TD, Stewart KJ, Niemen JC, Pedersen DR, Callaghan JJ. Local head roughening as a factor contributing to variability of total hip wear: a finite element analysis. *J. Biomech. Eng.*, 2002; **124**: 691–698.
372. Callaghan JJ, Dysart SH, Savory CF, Hopkinson WJ. Assessing the results of hip replacement. A comparison of five different rating systems. *J. Bone Joint Surg. (Br.)*, 1990; **72-B**: 1008–1009.
373. Murray DW, Carr AJ, Bulstrode CJ. Which primary total hip replacement? *J. Bone Joint Surg. (Br.)*, 1995; **77-B**: 520–527.
374. Boutin P. The classic: Total hip arthroplasty using a ceramic prosthesis. *Clin. Orthop.*, 2000; **379**: 3–11.
375. Boutin P. Arthroplastie total de la hanche par prothese on alumine frittee. *Rev. Chirurgie Orthop.*, 1972; **58**: 229–246.
376. Hamadouche M, Meunier A, Nizard R, Hannouche D, Bizot P, Sedel L. Alumina-on-alumina articulation in total hip arthroplasty: from bench-side to bedside. *Semin. Arthroplasty*, 2006; **17**: 125–133.
377. Murphy SB, Ecker T, Tannast M, Bierbaum B, Garino J, Howe J, Hume E, Jones R, Keggi K, Kress K, Phillips D, Zann R. Experience in the United States with alumina ceramic-ceramic total hip arthroplasty. *Semin. Arthroplasty*, 2006; **17**: 120–124.
378. Sedel L, Raould A. Engineering aspect of alumina on alumina hip prosthesis. *Proc. Inst. Mech. Eng. H*, 2007; **221**: 21–27.
379. Antonov PI, Bakholdin SI, Galaktionov EV, Tropp EV, Nikanorov SP. Anisotropy of thermoelastic stresses in shaped sapphire single crystals. *J. Cryst. Growth*, 1981; **52** Part 1: 404–410.
380. Clarke DR. Microfracture in brittle solids resulting from anisotropic shape changes. *Acta Metall.*, 1980; **28**: 913–924.
381. Ortiz M, Suresh S. Statistical properties of residual stresses and intergranular fracture in ceramic materials. *J. Appl. Mech.*, 1993; **60**: 77–84.
382. Evans AG. Microfracture from thermal expansion anisotropy — I. Single phase systems. *Acta Metall.*, 1978; **26**: 1845–1853.
383. Krell A, Teresiak A, Schaefer D. Grain size dependent residual microstresses in submicron Al_2O_3 and ZrO_2 . *J. Eur. Ceram. Soc.*, 1996; **16**: 803–811.
384. Rice RW, Pohanka RC. Grain size dependence of spontaneous cracking in ceramics. *J. Am. Ceram. Soc.*, 1979; **62**: 559–563.

385. Pezzotti G. Internal friction of polycrystalline ceramic oxides. *Phys. Rev. B*, 1999; **60**: 4018–4029.
386. Gates RS, Hsu SM, Klaus EE. Tribochemical mechanism of alumina with water. *Tribol. Trans.*, 1989; **32**: 357–363.
387. Eshelby JD. The determination of the elastic field of an ellipsoidal inclusion and related problems. *Proc. Roy. Soc.*, 1957; **A241**: 376–396.
388. Sternitzke M. Structural ceramic nanocomposites. *J. Eur. Ceram. Soc.*, 1997; **17**: 1061–1082.
389. Evans AG, Clarke DR. Residual stresses and microcracking induced by thermal contraction inhomogeneity. In *Thermal stresses in severe environments*. Hasselman DPH, Heller RA (Eds.). Plenum Press, New York, 1980, pp. 629–648.
390. Mura T, Lin TY, Qin S. Thermal stress in triangular and rectangular inclusion. *Thermoelasticity*, 1995; **1**: 207–210.
391. Boutin P, Christel P, Dorlot J-M, Meunier A, de Roquancourt A, Blankaert D, Herman S, Sedel L, Witvoet J. The use of dense alumina-alumina ceramic combination in total hip replacement. *J. Biomed. Mater. Res. A*, 1988; **22**: 1203–1232.
392. Bennison SJ, Harmer MP. Effect of MgO solute on the kinetics of grain growth in Al_2O_3 . *J. Am. Ceram. Soc.*, 1983; **66**: C90–C92.
393. Bennison SJ, Harmer MP. Grain-growth kinetics for alumina in the absence of a liquid phase. *J. Am. Ceram. Soc.*, 1985; **68**: C22–C24.
394. Handwerker CA, Morris PA, Coble RL. Effects of Chemical Inhomogeneities on Grain Growth and Microstructure in Al_2O_3 . *J. Am. Ceram. Soc.*, 1989; **72**: 130–136.
395. Yoshida H, Ikuhara Y, Sakuma T, Sakurai M, Matsubara E. XAFS study on the fine structure of lutetium segregated at grain boundaries in fine-grained polycrystalline alumina. *Phil. Mag.*, 2004; **84**: 865–876.
396. Kara H, Roberts SG. Wet erosion behaviour of low SiC alumina-SiC nanocomposites. *J. Mat. Sci.*, 2002; **37**: 2421–2426.
397. Wu HZ, Roberts SG, Möbus G, Inkson BJ. Subsurface damage analysis by TEM and 3D FIB crack mapping in alumina and alumina/5 vol.% SiC nanocomposites. *Acta Mater.*, 2003; **51**: 149–163.
398. Pezzotti G, Mueller WH. Strengthening mechanisms in $\text{Al}_2\text{O}_3/\text{SiC}$ nanocomposites. *Comput. Mater. Sci.*, 2001; **22**: 155–168.
399. Ferroni LP, Pezzotti G. Evidence for bulk residual stress strengthening in $\text{Al}_2\text{O}_3/\text{SiC}$ nanocomposites. *J. Am. Ceram. Soc.*, 2002; **85**: 2033–2038.

400. Sternitzke M, Derby B, Brook RJ. Alumina/silicon carbide nanocomposites by hybrid polymer/powder processing: Microstructures and mechanical properties. *J. Am. Ceram. Soc.*, 1998; **81**: 41–48.
401. Perez-Rigueiro J, Pastor JY, Llorca J, Elices M, Miranzo P, Moya JS. Revisiting the mechanical behavior of alumina silicon carbide nanocomposites. *Acta Mater.*, 1998; **15**: 5399–5411.
402. Levin I, Kaplan WD, Brandon DG. Effect of SiC submicrometer particle-size and content on fracture toughness of alumina-SiC nanocomposites. *J. Am. Ceram. Soc.*, 1995; **78**: 254–256.
403. Pezzotti G, Sergo V, Ota K, Sbaizero O, Muraki N, Nishida T, Sakai M. Residual stresses and apparent strengthening in ceramic-matrix nanocomposites. *J. Ceram. Soc. Jpn.*, 1996; **104**: 497–503.
404. Bae SI, Baik S. Sintering and grain growth of ultrapure alumina. *J. Mater. Sci.*, 1993; **28**: 4197–4204.
405. Zhang S, Garofalini SH. Molecular dynamics simulations of the effect of the composition of calcium alumino-silicate intergranular films on alumina grain growth. *J. Phys. Chem. B*, 2006; **110**: 2233–2240.
406. Suárez M, Fernández A, Menéndez JL, Ramírez-Rico J, Torrecillas R. Blocking of grain reorientation in self-doped alumina materials. *Scripta Mater.*, 2011; **64**: 517–520.
407. Jung J, Baik S. Abnormal grain growth of alumina: CaO effect. *J. Am. Ceram. Soc.*, 2003; **86**: 644–649.
408. Bae SI, Baik S. Determination of critical concentration of silica and/or calcia for abnormal grain growth in alumina. *J. Am. Ceram. Soc.*, 1993; **76**: 1065–1067.
409. Brydson R, Chen S, Riley FL, Milne SJ, Pan X, Rühle M. Microstructure and chemistry of intergranular glassy films in liquid-phase-sintered alumina. *J. Am. Ceram. Soc.*, 1998; **81**: 369–379.
410. Baik S, White CL. Anisotropic Ca segregation to the surface of alumina. *J. Am. Ceram. Soc.*, 1987; **70**: 682–688.
411. Litton DA, Garofalini SH. Atomistic structure of sodium and calcium silicate intergranular films in alumina. *J. Mater. Res.*, 1999; **14**: 1418–1429.
412. West GD, Perkins JM, Lewis MH. The effect of rare earth dopants on grain boundary cohesion in alumina. *J. Eur. Ceram. Soc.*, 2007; **27**: 1913–1918.
413. Chantikul P, Bennison SJ, Lawn BR. Role of grain size in the strength and *R*-curve properties of alumina. *J. Am. Ceram. Soc.*, 1990; **73**: 2419–2427.

414. Burgos-Montes O, Moreno R, Baudin C. Effect of mullite additions on the fracture mode of alumina. *J. Eur. Ceram. Soc.*, 2010; **30**: 857–863.
415. Buban JP, Matsunaga K, Chen J, Shibata N, Ching WY, Yamamoto T, Ikuhara Y. Grain boundary strengthening in alumina by rare earth impurities. *Science*, 2006; **311**: 212–215.
416. Béguin B, Garbowski E, Primet M. Stabilization of alumina by addition of lanthanum, *Appl. Catal.*, 1991; **75**: 119–132.
417. Williams DF, Black J, Doherty PJ. Second consensus conference on definitions in biomaterials. in: *Biomaterials–tissue interfaces*. Doherty PJ, Williams RL, Williams DF, Lee AIJ (eds.). Elsevier, Amsterdam, pp. 525–533, 1992.
418. Williams DF. Biomaterials, and biocompatibility. *Med. Prog. Technol.*, 1976; **20**: 31–42.
419. Dörre E, Hübner H. Alumina. Springer Verlag (Heidelberg, Germany) 1984; p. 235.
420. Takami Y, Yamane S, Makinouchi K, Otsuka G, Glueck J, Benkowski R, Nose Y. Protein adsorption onto ceramic surfaces. *J. Biomed. Mater. Res.*, 1998; **40**: 24–30.
421. Christel P. Biocompatibility of surgical-grade dense polycrystalline alumina. *Clin. Orthop.*, 1992; **282**: 10–18.
422. Griss P, von Adrian-Werburg HV. Biological activity and histocompatibility of dense Al_2O_3 –MgO ceramic implants in rats. *J. Biomed. Mater. Res.*, 1973; **7**: 453–462.
423. Torricelli P, Verne E, Brovarone CV, Appendino P, Rustichelli F, Krajewski A, Ravaglioli A, Pierini G, Fini M, Giavaresi G, Giardino R. Biological glass coating on ceramic materials: *in vitro* evaluation using primary osteoblast cultures from healthy and osteopenic rat bone. *Biomaterials*, 2001; **22**: 2535–2543.
424. Novak S, Kalin M, Kosmac T. Chemical aspects of wear of alumina ceramics. *Wear*, 2001; **250**: 318–321.
425. Novak S, Kalin M. The effect of pH on the wear of water-lubricated alumina and zirconia ceramics. *Tribol. Lett.*, 2004; **17**(4), 727–732.
426. Mahoney OM, Dimon JH. Unsatisfactory results with a ceramic total hip prosthesis. *J. Bone Joint Surg. (Am.)*, 1990; **72**: 663–671.
427. Mittelmeier TH, Walter A. The influence of prosthesis design on wear and loosening phenomena. *Crit. Rev. Biocompat.*, 1987; **3**: 319.
428. Yoon TR, Sung MR, Sung TJ, Kwang JS, Maloney WJ. Osteolysis in association with a total hip arthroplasty with ceramic bearings surfaces. *J. Bone Joint Surg. (Am.)*, 1998; **80**: 1459–1468.

429. Charnley J, Halley DK. Rate of wear in total hip replacement. *Clin. Orthop. Relat. Res.* 1975; **112**: 170–179.
430. Tanaka K, Tamura J, Kawanabe K, Shimizu M, Nakamura T. Effect of alumina femoral heads on polyethylene wear in cemented total hip arthroplasty. *J. Bone Joint Surg. (Br.)*, 2003; **85-B**: 655–660.
431. Pattyn C, De Smet KA. Primary ceramic-on-ceramic total hip replacement versus metal-on-metal hip resurfacing in young active patients. *Orthopedics*, 2008; **31**: 1078.
432. Yamamoto K, Shishido T, Tateiwa T, Katori Y, Masaoka T, Imakiire A, Clarke IC. Failure of ceramic THR with liner dislocation — a case report. *Acta Orth. Scand.*, 2004; **75**: 500–502.
433. Hwang DS, Kim YM, Lee CH. Alumina femoral head fracture in uncemented total hip arthroplasty with a ceramic sandwich cup. *J. Arthroplasty*, 2007; **22**: 468–471.
434. Kircher J, Bader R, Schroeder B, Mittelmeier W. Extremely high fracture rate of a modular acetabular component with a sandwich polyethylene ceramic insertion for THA: a preliminary report. *Arch. Orthop. Trauma Surg.*, 2009; **129**: 1145–1150.
435. Heisel C, Silva M, Schmalzried TP. Bearing surface options for total hip replacement in young patients. *Instr. Course Lect.*, 2004; **53**: 49–65.
436. Masson B. Emergence of the alumina matrix composite in total hip arthroplasty. *Int. Orthop.*, 2009; **33**: 359–363.
437. Nevelos J, Ingham E, Doyle C, Streicher R, Nevelos A, Walter W, Fisher J. Microseparation of the centers of alumina-alumina artificial hip joints during simulator testing produces clinically relevant wear and patterns. *J. Arthroplasty*, 2000; **15**: 793–795.
438. Williams S, Steward TD, Ingham E, Stone MH, Fisher J. Influence of microseparation and joint laxity on wear of ceramic on polyethylene, ceramic on ceramic and metal on metal total hip replacements. *J. Bone Joint Surg. (Br.)*, 2003; **85-B** (Supp. I): 57.
439. Williams S, Butterfield M, Steward T, Ingham E, Stone M, Fisher J. Wear and deformation of ceramic-on-polyethylene total hip replacements with joint laxity and swing phase microseparation. *Proc. Inst. Mech. Eng. H*, 2003; **217**: 147–153.
440. Jin ZM, Dowson D, Fisher J. Analysis of fluid film lubrication in artificial hip joint replacements with surfaces of high elastic modulus. *Proc Inst. Mech. Eng. H*, 1997; **211**: 247–256.

- 441. Schaefer R, Soltesz U, Bernard P-F. Friction in hip-joint prostheses and its influence on the fixation of the artificial head. *J. Mater. Sci.: Mater. Med.* 1998; **9**: 687–690.
- 442. Wang A, Essner A, Klein, R. Effect of contact stress on friction and wear of ultra-high molecular weight polyethylene in total hip replacement. *Proc. Inst. Mech. Eng. H*, 2001; **215**: 133–139.
- 443. Tuke MA, Scott G, Roques A, Hu XQ, Taylor A. Design considerations and life prediction of metal-on-metal bearings: The effect of clearance. *J. Bone Joint Surg. (Am.)*, 2008; **90**: 134–141.
- 444. Clarke IC, Manley MT. How do alternative bearing surfaces influence wear behavior? *J. Am. Acad. Orthop. Surg.*, 2008; **16** (Supp. 1): S86–S93.
- 445. Kamali A, Daniel JT, Javid SF, Youseffi M, Band T, Ashton R, Hussain A, Li CX, Daniel J, McMinn DJW. The effect of cup deflection on friction in metal-on-metal bearings. *J. Bone Joint Surg. (Br.)*, 2008; **90-B** (Supp. 3): 552.
- 446. Nevelos JE, Ingham E, Doyle C, Nevelos AB, Fisher J. Wear of HIPed and non-HIPed alumina-alumina hip joints under standard and severe simulator testing conditions. *Biomaterials*, 2001; **22**: 2191–2197.
- 447. Nevelos JE, Ingham, Doyle C, Nevelos AB, Fisher J. The influence of acetabular cup angle on the wear of “BIOLOX Forte” alumina ceramic bearing couples in a hip joint simulator. *J. Mater. Sci.: Mater. Med.* 2001; **12**: 141–144.
- 448. Oonishi H, Clarke IC, Good V, Amino H, Ueno M. Alumina hip joints characterized by run-in wear and steady-state wear to 14 million cycles in hip-simulator model. *J. Biomed. Mater. Res. A*, 2004; **70-A**: 523–532.
- 449. Widmer KH, Zurfluh B. Compliant positioning of total hip components for optimal range of motion. *J Orthop Res.*, 2004; **22**: 815–821.
- 450. Murray DW. The definition and measurement of acetabular orientation. *J. Bone Joint Surg. (Br.)*, 1993; **75**: 228–232.
- 451. Shishido T, Clarke IC, Williams P, Boehler M, Asano T, Shoji H, Masaoka T, Yamamoto K, Imakiire A. Clinical and simulator wear study of alumina ceramic THR to 17 years and beyond. *J. Biomed. Mater. Res. B*, 2003; **67-B**: 638–647.
- 452. Manaka M, Clarke IC, Yamamoto K, Shishido T, Gustafson A, Imakiire A. Stripe wear rates in alumina THR — comparison of microseparation simulator study with retrieved implants. *J. Biomed. Mater. Res. B*, 2004;

- 69-B:** 149–157.
453. Chen Y, Huang W. Numerical simulation of the geometrical factors affecting surface roughness measurements by AFM. *Meas. Sci. Tech.*, 2004; **15**: 2005–2010.
 454. Barbour PSM, Stone MH, Fisher J. A hip joint simulator study using new and physiologically scratched femoral heads with ultra-high molecular weight polyethylene acetabular cups. *Proc. Inst. Mech. Eng. H*, 2000; **214**: 569–576.
 455. Eberhardt AW, McKee RT, Cuckler JM, Peterson DW, Beck PR, Lemons JE. Surface roughness of CoCr and ZrO₂ femoral heads with metal transfer: A retrieval and wear simulator study. *Int. J. Biomater.*, 2009; **2009**: 185456-1–6.
 456. Dowson D, Hardaker C, Flett M, Isaac GH. A hip joint simulator study of the performance of metal-on-metal joints, Part II: design. *J. Arthroplasty*, 2004; **19** (Suppl. 3): 124–130.
 457. Stewart TD, Tipper J, Streicher R, Ingham E, Fisher J. Long-term wear of HIPed alumina on alumina bearings for THR under microseparation conditions. *J. Mater. Sci.: Mater. Med.*, 2001; **12**: 1053–1056.
 458. Affatato S, Traina F, Toni A. Microseparation and stripe wear in alumina-on-alumina hip implants. *Int. J. Artif. Organs*, 2011; **34**: 506–512.
 459. Muller U, Gautier E, Roeder C, Busato A. The relationship between cup design and the radiological signs of aseptic loosening in total hip arthroplasty. *J. Bone Joint Surg. (Br.)*, 2003; **85-B**: 31–36.
 460. Duisabeau L, Combrade P, Forest B. Environmental effect on fretting of metallic materials for orthopaedic implants. *Wear*, 2004; **256**: 805–816.
 461. Sundfeldt M, Carlsson LV, Johansson CB, Thomsen P, Gretzer C. Aseptic loosening, not only a question of wear: a review of different theories. *Acta Orthop.*, 2006; **77**: 177–197.
 462. Affatato S, Spinelli M, Zavalloni M, Mazzega-Fabbro C, Viceconti M. Tribology and total hip joint replacement: Current concepts in mechanical simulation. *Med. Eng. Phys.*, 2008; **30**: 1305–1317.
 463. Grabner L. Spectroscopic technique for the measurement of residual stress in sintered Al₂O₃. *J. Appl. Phys.*, 1978; **49**: 580–583.
 464. Munisso MC, Zhu W, Leto A, Pezzotti G. Stress dependence of sapphire cathodoluminescence from optically active oxygen defects as a function of crystallographic orientation. *J. Phys. Chem. A*, 2007; **111**: 3526–3533.

465. Leto A, Munisso MC, Porporati AA, Zhu W, Pezzotti G. Stress dependence of paramagnetic point defects in amorphous silicon oxide. *J. Phys. Chem. A*, 2008; **112** (17): 3927–3934.
466. Leto A, Porporati AA, Zhu W, Green M, Pezzotti G. High-resolution stress assessments of interconnect/dielectric electronic patterns using optically active point defects of silica glass as a stress sensor. *J. Appl. Phys.*, 2007; **101**: 093514-1–14.
467. McClure DS. Optical spectra of transition-metal ions in corundum. *J. Chem. Phys.*, 1962; **36**: 2757–2779.
468. Poole Jr. CP. The optical spectra and color of chromium containing solids. *J. Phys. Chem. Solids*, 1964; **25**: 1169–1182.
469. Porto SPS, Krishnan RS. Raman effect of corundum. *J. Chem. Phys.*, 1967; **47**: 1009–1012.
470. Krishnan RS. Raman spectrum of alumina and the luminescence of ruby. *Proc. Math. Sci. (Indian Acad. Sci. A)*, 1947; **26**: 450–459.
471. Lee KH, Krawford JH. Luminescence of the F center in sapphire. *Phys. Rev. B*, 1979; **19**: 3217–3221.
472. Draeger BG, Summers GP. Defects in unirradiated α - Al_2O_3 . *Phys. Rev. B*, 1979; **19**: 1172–1177.
473. Wan KS, Tochino S, Zhu W, Ohtsuka S, Pezzotti G. Quantitative evaluation of probe response functions for Raman and fluorescence bands of single-crystalline and polycrystalline Al_2O_3 . *J. Phys. D: Appl. Phys.*, 2010; **43**: 205501-1–10.
474. Fitting H-J, Glaefcke H, Wild W. Electron penetration and energy transfer in solid targets. *Phys. Status Solidi (a)*, 1977; **43**: 185–190.
475. Kanaya K, Okayama S. Penetration and energy-loss theory of electrons in solid targets. *J. Phys. D: Appl. Phys.*, 1972; **5**: 43–58.
476. Grellner F, Hoescheler S, Greil P, Sindel J, Petschelt A. Residual stress measurements of computer aided design/computer aided manufacturing (CAD/CAM) machined dental ceramics. *J. Mater. Sci.*, 1997; **32**: 6235–6242.
477. Sparks RG, Paesler MA. Depth profiling of residual stress along interrupted test cuts in machined germanium crystals. *J. Appl. Phys.*, 1992; **71**: 891–897.
478. Vedula VR, Glass SJ, Saylor DM, Rohrer GS, Carter WC, Langer SA, Fuller Jr. ER. Residual-stress predictions in polycrystalline alumina. *J. Am. Ceram. Soc.*, 2001; **84**: 2947–2954.

479. Ma Q, Clarke DR. Piezospectroscopic determination of residual stresses in polycrystalline alumina. *J. Am. Ceram. Soc.*, 1994; **77**: 298–302.
480. Hsu YC, Forman RG. Elastic-plastic analysis of an infinite sheet having a circular hole under pressure. *Trans. ASME: J. Appl. Mech.*, 1975; **42**: 347–352.
481. Ball DL, Lowry DR. Experimental investigation on the effects of cold expansion of fastener holes. *Fatigue Fract. Eng. Mater. Struct.*, 1998; **21**: 17–34.
482. Che Z, Xiong L, Shi T, Cheng H, Yang L. Experimental analysis of microscale laser shock processing on metallic material using excimer laser. *J. Mater. Sci. Technol.*, 2009; **25**: 829–834.
483. Bhuvaraghan B, Srinivasan RM, Maffeo B. Optimization of the fatigue strength of materials due to shot peening: A survey. *Int. J. Struct. Changes — Solids*, 2010; **2**: 33–63.
484. Jahanmir S. Tribological applications of advanced ceramics. *Mat. Res. Soc. Symp. Proc.*, 1989; **140**: 285–291.
485. Xiong F, Manory RR, Ward L, Terheci M, Lathabai S. Effect of grain size and test configuration on the wear behavior of alumina. *J. Am. Ceram. Soc.*, 1997; **80**: 1310–1312.
486. Chen YM, Rigaut B. Friction and wear of alumina ceramics at high sliding speed. *Lubr. Eng.*, 1990; **47**: 531–537.
487. Dong X, Jahanmir S, Hsu SM. Tribological characteristics of α -alumina at elevated temperature. *J. Am. Ceram. Soc.*, 1991; **74**: 1036–1044.
488. Esposito L, Tucci A, Solomah AG, Palmonari C. Effects of temperature and sliding velocity on the dry tribological characteristics of high purity, high density polycrystalline aluminium oxides. *Wear*, 1992; **153**: 351–360.
489. Perez-Unzueta AJ, Beynon JH, Gee MG. The effect of surrounding atmosphere on the sliding wear of alumina. *Wear*, 1991; **146**: 179–196.
490. Andersson P. Water lubricated pin-on-disc tests with ceramics. *Wear*, 1992; **154**: 37–47.
491. Wang Y, Hsu SM. The effect of operating parameters and environment on the wear and wear transition of alumina. *Wear*, 1996; **195**: 90–99.
492. Mukhopadhyay AK, Mai YW. Grain size effect on abrasive wear mechanisms in alumina ceramics. *Wear*, 1993; **162–164**: 258–268.

493. Zum Gahr KH, Bundschuh W, Zimmerlin B. Effect of grain size on friction and sliding wear of oxide ceramics. *Wear*, 1993; **162-164**: 269-279.
494. Malkin S, Ritter JE. Grinding mechanisms and strength degradation for ceramics. *J. Eng. Ind.*, 1989; **111**: 167-174.
495. Mukherji J, Das PK. Wear of some advanced ceramics under a sharp indenter in unidirectional sliding. *J. Am. Ceram. Soc.*, 1993; **76**: 2376-2378.
496. Ajayi OO, Ludema KC. The effect of microstructure on wear modes of ceramic materials. *Wear*, 1992; **154**: 371-385.
497. Hokkirigawa K. Wear mode map of ceramics. *Wear*, 1991; **151**: 219-228.
498. Cutter LA, McPherson R. Plastic deformation of Al_2O_3 during abrasion. *J. Am. Ceram. Soc.*, 1973; **56**: 266-269.
499. Gilbert CJ, Petrany RN, Ritchie RO, Dauskardt RH, Steinbrech RW. Cyclic fatigue in monolithic alumina: mechanisms for crack advance promoted by frictional wear of grain bridges. *J. Mater. Sci.*, 1995; **30**: 643-654.
500. Gee MG. The formation of aluminium hydroxide in the sliding wear of alumina. *Wear*, 1992; **153**: 201-227.
501. Li J, Liu Y, Hermansson L, Soremark R. Evaluation of biocompatibility of various ceramic powders with human fibroblasts *in vitro*. *Clin. Mater.*, 1993; **12**: 197-201.
502. Khanna R, Basu B. Low friction and severe wear of alumina in cryogenic environment: A first report. *J. Mater. Res.*, 2006; **21**: 832-843.
503. Jamari J, de Rooij MB, Schipper DJ. Plastic deterministic contact of rough surfaces. *J. Tribol.*, 2007; **129**: 957-962.
504. Gao YF, Lucas BN, Hay JC, Oliver WC, Pharr GM. Nanoscale incipient asperity sliding at interface micro-slip assessed by the measurement of tangential contact stiffness. *Scripta Mater.*, 2006; **55**: 653-656.
505. Tipper JL, Hatton A, Nevelos JE, Ingham E, Doyle C, Streicher R, Nevelos AB, Fisher J. Alumina-alumina artificial hip joints. Part II: characterization of the wear debris from *in vitro* hip joint simulations. *Biomaterials*, 2002; **23**: 3441-3448.
506. Nevelos A, Evans PA, Harrison P, Rainforth WM. Examination of alumina ceramic components from total hip arthroplasties. *Proc. Inst. Mech. Eng. H*, 1993; **207**: 155-162.

507. Lagerlöf KPD, Mitchel TE, Heuer AH, Riviere JP, Cadoz J, Castaing J, Phillips DS. Stacking fault energy in sapphire (α -Al₂O₃). *Acta Metall.*, 1984; **32**: 97–105.
508. Jahanmir S. Wear of ceramics: wear transitions and tribochemical reactions. In Stachowiak GW (Ed.). *Wear — Materials, mechanisms and practice*. John Wiley & Sons Ltd, Chichester, pp. 167–189, 2005.
509. Jeng MC, Yan LY. Environmental effects on wear behavior of alumina. *Wear*, 1993; **161**: 111–119.
510. Mori S. The lubrication of ceramics — adsorption and chemical reaction. *Tribol. J. Jpn. Soc. Tribol.*, 1991; **36**: 130–134.
511. Shapovalov V, Truong TN. *Ab initio* study of water adsorption on α -Al₂O₃ (0001) crystal surface. *J. Phys. Chem. B*, 2000; **104**: 9859–9866.
512. Fernandez EM, Eglitis RI, Borstel G, Balbas LC. *Ab initio* calculations of H₂O and O₂ adsorption on Al₂O₃ substrates. *Comput. Mater. Sci.*, 2007; **39**: 587–592.
513. Zeng H, Chittur KK, Lacefield WR. Analysis of bovine serum albumin adsorption on calcium phosphate and titanium surfaces. *Biomaterials*, 1999; **20**: 377–384.
514. Garrett Q, Griesser HJ, Milthorpe BK, Garrett RW. Irreversible adsorption of human serum albumin to hydrogel contact lenses: A study using electron spin resonance spectroscopy. *Biomaterials*, 1999; **20**: 1345–1356.
515. Mishina H, Kojima M. Changes in human serum albumin on arthroplasty frictional surfaces. *Wear*, 2008; **265**: 655–663.
516. Nevelos JE, Prudhommeaux F, Hamadouche M, Doyle C, Ingham E, Meunier A, Nevelos AB, Sedel L, Fisher J. Comparative analysis of two different types of alumina-alumina hip prosthesis retrieved for aseptic loosening. *J. Bone Joint Surg. (Br.)*, 2001; **83-B**: 598–603.
517. Deckman DE, Jahanmir S. Wear mechanisms of alpha alumina lubricated with a paraffin oil. *Wear*, 1991; **149**: 155–168.
518. Dahl LB, Dahl IM, Engström-Laurent A, Granath K. Concentration and molecular weight of sodium hyaluronate in synovial fluid from patients with rheumatoid arthritis and other arthropathies. *Ann. Rheum. Dis.*, 1985; **44**: 817–822.
519. Ghamnia M, Jardin C, Bouslama M. Luminescence centres F and F⁺ in α -alumina detected by cathodoluminescence technique. *J. Electron Spectr. Rel. Phenom.*, 2003; **133**: 55–63.

520. Brandt G, Mikus M. An electron microprobe and cathodoluminescence study of chemical reactions between tool and workpiece when turning steel with alumina-based ceramics. *Wear*, 1987; **115**: 243–263.
521. Surdo AI, Pustarov VA, Kortov VS, Kishka AS, Zinin EI. Luminescence in anion-defective α - Al_2O_3 crystals over the nano- micro- and millisecond intervals. *Nucl. Instr. Meth. A*, 2005; **543**: 234–238.
522. Boumasa A, Djelloul A, Guerrab F. Specific signatures of α -alumina powders prepared by calcination of bohemite or gibbsite. *Powd. Tech.*, 2010; **201**: 177–180.
523. Stathopoulos AY, Pells GP. Damage in the cation sublattice of α - Al_2O_3 irradiated in an HVEM. *Philos. Mag. A*, 1983; **47**: 381–394.
524. Dubinko VI, Turkin AA, Vainshtein DI, den Hartog HW. New mechanism for radiation defect production and aggregation in crystalline ceramics. *J. Nucl. Mater.*, 2001; **289**: 86–95.
525. Oda K, Yoshio T. Hydrothermal corrosion of alumina ceramics. *J. Am. Ceram. Soc.*, 1997; **80**: 3233–3236.
526. Bennison SJ, Harmer MP. Swelling of hot-pressed Al_2O_3 . *J. Am. Ceram. Soc.*, 1985; **68**: 591–597.
527. Jonnard P, Bonnelle C, Blaise G, Remond G, Roques-Carmes C. F^+ and F centers in α - Al_2O_3 by electron-induced X-ray emission spectroscopy and cathodoluminescence. *J. Appl. Phys.*, 2000; **88**: 6413–6417.
528. Stoyanovskii VO, Snytnikov VN. Laser-induced luminescence associated with surface hydroxide groups in Al_2O_3 . *Kinet. Catal.*, 2009; **50**: 470–475.
529. Wiederhorn SM. Moisture assisted crack growth in ceramics. *Int. J. Fract. Mech.*, 1968; **4**: 171–177.
530. Castaing J, Kronenberg AK, Kirby SH, Mitchell TE. Hydrogen defects in α - Al_2O_3 and water weakening of sapphire and alumina ceramics between 600 and 1000°C — II. Mechanical properties. *Acta Mater.*, 2000; **48**: 1495–1504.
531. Mainprice D, Taki S, Hosaka M. Water in hydrothermally grown sapphire (α - Al_2O_3). In Boland JN, Fitz Gerald JD (Eds.). *Defects and processes in the solid state: geoscience applications, the McLaren volume*. Elsevier Science Publishers, Amsterdam and New York, pp. 347–358, 1993.
532. Lam DCC, Lange FF, Evans AG. Mechanical properties of partially dense alumina produced from powder compacts. *J. Am. Ceram. Soc.*, 1994; **77**: 2113–2117.

533. Ostrowski T, Ziegler A, Bordia RK, Rödel J. Evolution of Young's modulus, strength and microstructure during liquid phase sintering. *J. Am. Ceram. Soc.*, 1998; **81**: 1852–1860.
534. Ostrowski T, Rödel J. Evolution of mechanical properties of porous alumina during free sintering and hot pressing. *J. Am. Ceram. Soc.*, 1999; **82**: 3080–3086.
535. Baratta FI. Refinement of stress intensity factor estimates for a peripherally cracked spherical void and a hemispherical surface pit. *J. Am. Ceram. Soc.*, 1981; **64**: C3–C4.
536. Evans AG, Biswas DR, Fulrath RM. Some effects of cavities on the fracture of ceramics: II, spherical cavities. *J. Am. Ceram. Soc.*, 1979; **62**: 101–106.
537. Kingery WD, Francois B. Sintering of crystalline oxides, I. Interaction between grain boundaries and pores. In *Sintering and related phenomena*. Kuczynski GC, Hooton NA, Gibbon GF (Eds.). Gordon Breach, New York, pp. 471–498, 1967.
538. Kellett BJ, Lange FF. Experiments on pore closure during hot isostatic pressing and forging. *J. Am. Ceram. Soc.*, 1988; **71**: 7–12.
539. Oh K-S, Kim D-Y, Cho S-J. Shrinkage of large isolated pores during hot isostatic pressing of presintered alumina ceramics. *J. Am. Ceram. Soc.*, 1995; **78**: 2537–2540.
540. Evans AG, Hsueh CH. Behavior of large pores during sintering and hot pressing. *J. Am. Ceram. Soc.*, 1986; **69**: 444–448.
541. Flinn BD, Bordia RK, Rödel J. Evolution of strength determining flaws during sintering. In *Sintering technology*. German RM, Messing GL, Cornwall RG (Eds.). Marcel Dekker, New York, pp. 13–20, 1996.
542. Fett T, Munz D, Seidel J, Stech M, Rödel J. Correlation between long and short crack R-curves in alumina using the crack opening displacement and fracture mechanical weight function approach. *J. Am. Ceram. Soc.*, 1996; **79**: 1189–1196.
543. Zimmermann A, Hoffman M, Flinn BD, Bordia RK, Chuang T-J, Fuller ER, Rödel J. Fracture of alumina with controlled pores. *J. Am. Ceram. Soc.*, 1998; **81**: 2449–2457.
544. Seidel J, Claussen N, Rödel J. Reliability of alumina ceramics: I, Effect of grain size. *J. Eur. Ceram. Soc.*, 1995; **15**: 395–404.
545. Seidel J, Rödel J. Measurement of crack tip toughness in alumina as a function of grain size. *J. Am. Ceram. Soc.*, 1997; **80**: 433–438.

546. Velamakanni BV, Lange FF, Zok FW, Pearson DS. Influence of inter-particle forces on the rheological behavior of pressure-consolidated alumina particle slurries. *J. Am. Ceram. Soc.*, 1994; **77**: 216–220.
547. Heinrich J, Munz D. Strength of reaction-bonded silicon nitride with artificial pores. *Bull. Am. Ceram. Soc.*, 1980; **59**: 1221–1222.
548. Irwin GR. Analysis of stresses and strains near the end of a crack transversing a plate. *J. Appl. Mech. Trans. ASME*, 1957; **79**: 361–364.
549. Fett T. An extension of the Newman-Raju formula. *Int. J. Fracture*, 1987; **33**: R47–R50.
550. Jayatilaka ADeS, Trustrum K. Statistical approach to brittle fracture. *J. Mater. Sci.*, 1977; **12**: 1426–1430.
551. Trustrum K, Jayatilaka ADeS. On estimating the Weibull modulus for a brittle material. *J. Mater. Sci.*, 1979; **14**: 1080–1084.
552. Nakamura S, Tanaka S, Furushima R, Sato K, Uematsu K. Estimation of Weibull modulus from coarser defect distribution in dry-pressed alumina ceramics. *J. Ceram. Soc. Jpn.*, 2009; **117**: 742–747.
553. Tinschert J, Zwez D, Marx R, Anusavice KJ. Structural reliability of alumina-, feldspar-, leucite-, mica- and zirconia-based ceramics. *J. Dentistry*, 2000; **28**: 529–535.
554. Meyers MA, Chawla KK. *Mechanical behavior of materials* (2nd Edition). Cambridge University Press, Cambridge, p. 453, 2009.
555. Tuan WH, Kuo JC. Effect of grinding parameters on the reliability of alumina. *Mater. Chem. Phys.*, 1998; **52**: 41–45.
556. Gong J. Correlation between Weibull moduli for tensile and bending strength of brittle ceramics: A numerical simulation analysis based on a three-parameter Weibull distribution. *J. Mater. Sci.*, 2003; **38**: 2541–2545.
557. Ruff O, Ebert F. Beiträge zur Keramik hochfeuerfeste Stoffe. I. Die Formen des Zirkondioxyds. *Z. Anorg. Allg. Chem.*, 1929; **180**: 19–41.
558. Strickler DW, Carlson WG. Ionic conductivity of cubic solid solutions in the system $\text{CaO}-\text{Y}_2\text{O}_3-\text{ZrO}_2$. *J. Am. Ceram. Soc.*, 1964; **47**: 122–127.
559. Dixon JM, LaGrange LD, Merten U, Miller CF, Porter II JT. Electrical resistivity of stabilized zirconia at elevated temperatures. *J. Electrochem. Soc.*, 1963; **110**: 276–280.
560. Cales B. Zirconia as a sliding material: Histologic, laboratory, and clinical data. *Clin. Orthop. Relat. Res.*, 2000; **379**: 94–112.
561. Piconi C, Maccauro G. Zirconia as a ceramic biomaterial. *Biomaterials*, 1999; **20**: 1–25.

562. Nernst W. Über die Elektrolytische Leitung fester Körper bei sehr hohen Temperaturen. *Z. Elektrochem.*, 1899; **6**: 41–43.
563. Teufer G. The crystal structure of tetragonal ZrO_2 . *Acta Crystallogr.* 1962; **15**: 1187.
564. Orlando R, Pisani C, Poetti C, Stefanovich E. *Ab initio* Hartree–Fock study of tetragonal and cubic phases of zirconium dioxide. *Phys. Rev. B*, 1992; **45**: 596–601.
565. Patil RN, Subbarao EC. Axial thermal expansion of ZrO_2 and HfO_2 in the range room temperature to 1400°C . *J. Appl. Crystallogr.*, 1969; **2**: 281–288.
566. Patil RN, Subbarao EC. Monoclinic-tetragonal phase transition in zirconia: Mechanism, pretransformation and coexistence. *Acta Crystallogr. A*, 1970; **26**: 535–542.
567. Deville S, Guenin G., Chevalier J. Martensitic transformation in zirconia Part I. Nanometer scale prediction and measurement of transformation induced relief. *Acta Mater.*, 2004; **52**: 5697–5707.
568. Frey F, Boysen H, Vogt T. Neutron powder investigation of the monoclinic to tetragonal phase transformation in undoped zirconia. *Acta Crystallogr. B*, 1990; **46**: 724–730.
569. Subbarao EC, Maiti HS, Srivastava KK. Martensitic transformation in zirconia. *Phys. Status Solidi (a)*, 1974; **21**: 9–40.
570. Bansal G, Heuer AH. On a martensitic phase transformation in zirconia (ZrO_2) — I. Metallographic evidence. *Acta Metall.*, 1972; **20**: 1281–1289.
571. Bansal G, Heuer AH. On a martensitic phase transformation in zirconia (ZrO_2) — II. Crystallographic aspects. *Acta Metall.*, 1974; **22**: 409–417.
572. Chen M, Hallstedt B, Gauckler LJ. Thermodynamic modeling of the $\text{ZrO}_2\text{-YO}_{1.5}$ system. *Solid State Ionics*, 2004; **170**: 255–274.
573. Garvie RC. The occurrence of metastable tetragonal zirconia as a crystallite size effect. *J. Phys. Chem.*, 1965; **69**: 1238–1243.
574. Hund F. Anomale Mischkristalle im System $\text{ZrO}_2\text{-Y}_2\text{O}_3$. Kristallbau der Nernst-Stifte. *Zeitschrift. Elektrochem. Angew. Phys. Chem.*, 1951; **55**: 363–366.
575. Kröger FA, Vink HJ. Relations between the concentrations of imperfections in solids. *J. Phys. Chem. Solids*, 1958; **5**: 208–223.
576. Grain CF. Phase Relations in the $\text{ZrO}_2\text{-MgO}$ System. *J. Am. Ceram. Soc.*, 1967; **50**: 288–290.

577. Stubican VS, Ray SP. Phase equilibria and ordering in the system $\text{ZrO}_2\text{--CaO}$. *J. Am. Ceram. Soc.*, 1977; **60**: 534–537.
578. Goff JP, Hayes W, Hull S, Hutchings MT, Clausen KN. Defect structure of yttria-stabilized zirconia and its influence on the ionic conductivity at elevated temperatures. *Phys. Rev. B*, 1999; **59**: 14202–14219.
579. Stefanovich EV, Shluger AL, Catlow CRA. Theoretical study of the stabilization of cubic-phase ZrO_2 by impurities. *Phys. Rev. B*, 1994; **49**: 11560–11571.
580. Tuilier MH, Dexpert-Ghys J, Dexpert H, Lagarde PJ. X-ray absorption study of the $\text{ZrO}_2\text{--Y}_2\text{O}_3$ system. *Solid State Chem.*, 1987; **69**: 153–161.
581. Morikawa H, Shimizugawa Y, Marumo F, Harasawa T, Ikawa H, Tohji K, Udagawa Y. Local structures around Y atoms in Y_2O_3 -stabilized tetragonal ZrO_2 . *J. Jpn. Ceram. Soc.*, 1988; **96**: 253–258.
582. Steele D, Fender BEF. The structure of cubic $\text{ZrO}_2\text{:YO}_{1.5}$ solid solutions by neutron scattering. *J. Phys. C: Solid State Phys.*, 1974; **7**: 1–11.
583. Catlow CRA, Chadwick AV, Greaves GN, Moroney LM. EXAFS study of yttria-stabilized zirconia. *J. Am. Ceram. Soc.*, 1986; **69**: 272–277.
584. Veal BW, Mckale AG, Paulikas AP, Rothman SJ, Nowicki LJ. EXAFS study of yttria-stabilized cubic zirconia. *Physica B*, 1988; **150**: 234–240.
585. Komyoji D, Yoshiasa A, Moriga T, Emura S, Kanamaru F, Koto K. EXAFS study of the fluorite-type compounds in the systems $(1-x)\text{ZrO}_2\text{--}x\text{YbO}_{1.5}$ ($x = 0.18 \leq x \leq 0.5$) and $\text{Zr}_2\text{Ln}_2\text{O}_7$ (Ln = Tb, Dy, Ho, Er, and Yb). *Solid State Ionics*, 1992; **50**: 291–301.
586. Kushima A, Yildiz B. Oxygen ion diffusivity in strained yttria stabilized zirconia: where is the fastest strain? *J. Mater. Chem.*, 2010; **20**: 4809–4819.
587. Li P, Chen I-W, Penner-Hahn JE. Effect of dopants on zirconia stabilization — an X-ray-absorption study. 3. Charge-compensating dopants. *J. Am. Ceram. Soc.*, 1994; **77**: 1289–1295.
588. Stapper G, Bernasconi M, Nicoloso N, Parrinello M. *Ab initio* study of structural and electronic properties of yttria-stabilized cubic zirconia. *Phys. Rev. B*, 1999; **59**: 797–810.
589. Bogicevic A, Wolverton C, Crosbie GM, Stechel EB. Defect ordering in aliovalently doped cubic zirconia from first principles. *Phys. Rev. B*, 2001; **64**: 14106-1–14.
590. Howard CJ, Hill RJ, Reichert BE. Structures of the ZrO_2 polymorphs at room temperature by high-resolution neutron powder diffraction. *Acta Crystallogr.*, 1988; **B44**: 116–120.

591. Morterra C, Cerrato G, Ferroni L, Montanari L. Surface characterization of yttria-stabilized tetragonal ZrO₂. Part 1. Structural, morphological, and surface hydration features. *Mat. Chem. Phys.*, 1994; **37**: 243–257.
592. de Ridder M, Vervoort AGJ, van Welzenis RG, Brongersma HH. The limiting factor for oxygen exchange at the surface of fuel cell electrolytes. *Solid State Ionics*, 2003; **156**: 255–262.
593. de Ridder M, van Welzenis RG, Brongersma HH, Kreissig U. Oxygen exchange and diffusion in the near surface of pure and modified yttria-stabilised zirconia. *Solid State Ionics*, 2003; **158**: 67–77.
594. Bernasik A, Kowalski K, Sadowski A. Surface segregation in yttria-stabilized zirconia by means of angle resolved X-ray photoelectron spectroscopy. *J. Phys. Chem. Solids*, 2002; **63**: 233–239.
595. Zhu J, van Ommen JG, Henny J, Bouwmeester M, Lefferts LJ. Activation of O₂ and CH₄ on yttrium-stabilized zirconia for the partial oxidation of methane to synthesis gas. *J. Catal.*, 2005; **233**: 434–441.
596. Ballabio G, Bernasconi M, Pietrucci F, Serra S. *Ab initio* study of yttria-stabilized cubic zirconia surfaces. *Phys. Rev. B*, 2004; **70**: 075417-1–6.
597. Eichler A, Kresse G. First-principles calculations for the surface termination of pure and yttria-doped zirconia surfaces. *Phys. Rev. B*, 2004; **69**: 045402-1–17.
598. Rieth PH, Reed JS, Naumann AW. Fabrication and flexural strength of ultra-fine grained yttria-stabilised zirconia. *Bull. Am. Ceram. Soc.*, 1976; **55**: 717–721.
599. Christel P, Meunier A, Heller M, Torre JP, Peille CN. Mechanical properties and short-term *in-vivo* evaluation of yttrium-oxide partially-stabilized zirconia. *J. Biomed. Mater. Res.*, 1989; **23**: 45–61.
600. Tateishi T, Yunoki H. Research and development of alumina and zirconia artificial hip joint. *Clin. Mater.*, 1993; **12**: 219–225.
601. Piconi C, Burger W, Richter HG, Cittadini A, Maccauro G, Covacci V, Bruzzese N, Ricci GA, Marmo E. Y-TZP ceramics for artificial joint replacements. *Biomaterials*, 1998; **19**: 1489–1494.
602. Medical Devices Agency — Adverse Incident Centre. Zirconia ceramic heads for modular total hip femoral components: advice to users on re-sterilization. Safety Notice MDA SN 9617, UK Government, June 1996.
603. Guo X. Roles of alumina in zirconia for functional applications. *J. Am. Ceram. Soc.*, 2003; **86**: 1867–1873.
604. Guo X. On the degradation of zirconia ceramic during low-temperature annealing in water or water vapor. *J. Phys. Chem. Solids*, 1999; **60**: 539–546.

605. Matsui K, Ohmichi N, Ohgai M, Enomoto N, Hojo J. Sintering kinetics at constant rates of heating: Effect of Al_2O_3 on the initial sintering stage of fine zirconia powder. *J. Am. Ceram. Soc.*, 2005; **88**: 3346–3352.
606. Matsui K, Yamakawa T, Uehara M, Enomoto N, Hojo J. Mechanism of alumina-enhanced sintering of fine zirconia powder: Influence of alumina concentration on the initial stage sintering. *J. Am. Ceram. Soc.*, 2008; **91**: 1888–1897.
607. Li JF, Watanabe R. Influence of a small amount of Al_2O_3 addition on the transformation of Y_2O_3 -partially stabilized ZrO_2 during annealing. *J. Mater. Sci.*, 1997; **32**: 1149–1153.
608. Mullens S, Cooymans J, Smolders C, Luyten J. Processing oxide-based nanocomposites. *Am. Ceram. Soc. Bull.*, 2005; **84**: 9101–9103.
609. Chen C-C, Hsiang H-I, Hsu S-W. Preparation and characterization of Y-TZP powders coated with alumina. *J. Ceram. Proc. Res.*, 2008; **9**: 131–134.
610. Burger W, Richter HG, Piconi C, Vatteroni R, Cittadini A, Boccalari M. New Y-TZP powders for medical grade zirconia. *J. Mater. Sci. Mat. Med.*, 1997; **8**: 113–118.
611. Watanabe M, Iio S, Fukuura I. Aging behavior of Y-TZP. In *Advances in ceramics, Vol. 12, Science and technology of zirconia II*. Claussen N, Rühle M, Heuer AH (Eds.). The American Ceramic Society, Inc., Columbus, OH, pp. 391–398, 1984.
612. Chung TJ, Song H, Kim GH, Kim DY. Microstructure and phase stability of yttria-doped tetragonal zirconia polycrystals heat treated in nitrogen atmosphere. *J. Am. Ceram. Soc.*, 1997; **80**: 2607–2612.
613. Hernandez MT, Jurado JR, Duran P, Fierro JLG. Subeutectoid degradation of yttria-stabilized tetragonal zirconia polycrystal and ceria-doped yttria-stabilized tetragonal zirconia polycrystal ceramics. *J. Am. Ceram. Soc.*, 1991; **74**: 1254–1258.
614. Sato T, Ohtaki S, Endo T, Shimada M. Improvement of thermal stability of yttria-doped tetragonal zirconia polycrystals by doping CeO_2 on the surface. *J. Mat. Sci. Lett.*, 1986; **5**: 1140–1142.
615. Evans AG. Perspective on the development of high-toughness ceramics. *J. Am. Ceram. Soc.*, 1990; **73**: 187–206.
616. McMeeking RM, Evans AG. Mechanics of transformation toughening in brittle materials. *J. Am. Ceram. Soc.*, 1982; **65**: 242–246.
617. Nalla RK, Kruzic JJ, Kinney JH, Ritchie RO. Mechanistic aspects of fracture and R-curve behavior in human cortical bone. *Biomaterials*, 2005; **26**: 217–231.

618. Kulin RM, Jianf F, Vecchio KS. Loading effects on the R-curve behavior of cortical bone. *Acta Biomater.*, 2011; **7**: 724–732.
619. Rose LRF, Swain MV. Two R curves for partially stabilized zirconia. *J. Am. Ceram. Soc.*, 1986; **69**: 203–207.
620. Li CW, Yamanis J. Super-tough silicon nitride with R-curve behavior. *Ceram. Eng. Sci. Proc.*, 1989; **10**: 632–645.
621. Marshall DB, Shaw MC, Dauskardt RH, Ritchie RO, Readey MJ, Heuer AH. Crack-tip transformation zones in toughened zirconia. *J. Am. Ceram. Soc.*, 1990; **73**: 2659–2666.
622. Shimozono T, Ikeda J, Pezzotti G. Evaluation of transformation zone around propagating cracks in zirconia biomaterials using Raman microprobe spectroscopy. *Key Eng. Mater.*, 2006; **309–311**: 1207–1210.
623. Ohtsuka S, Zhu W, Tochino S, Sekiguchi Y, Pezzotti G. In depth analysis of residual stress in an alumina coating on silicon nitride substrate using confocal Raman piezo-spectroscopy. *Acta Mater.*, 2007; **55**: 1129–1135.
624. Rice JR. Some remarks on elastic crack — tip stress fields. *Int. J. Solids Struct.*, 1972; **8**: 751–758.
625. Evans AG, Heuer AH. Review — Transformation toughening in ceramics: Martensitic transformations in crack-tip stress fields. *J. Am. Ceram. Soc.*, 1980; **63**: 241–248.
626. Kouroulis GA, Liarokapis E. Pressure and temperature dependence of the Raman spectra of zirconia and hafnia. *J. Am. Ceram. Soc.*, 1991; **74**: 520–530.
627. Milman V, Perlov A, Refson K, Clark SJ, Gavartin J, Winkler B. Structural, electronic and vibrational properties of tetragonal zirconia under pressure: a density functional theory study. *J. Phys.: Condens. Matter*, 2009; **21**: 485404-1-12.
628. Sato T, Shimada M. Transformation of yttria-doped tetragonal zirconia polycrystals by annealing in water. *J. Am. Ceram. Soc.*, 1985; **68**: 356–359.
629. Yoshimura M, Noma T, Kawabata K, Somiya S. Role of water on the degradation process of Y-TZP yttrium-doped tetragonal zirconia. *J. Mater. Sci. Lett.*, 1987; **6**: 465–467.
630. Schmauder S, Schubert H. Significance of internal stresses for the martensitic transformation in yttria-stabilized tetragonal zirconia polycrystals during degradation. *J. Am. Ceram. Soc.*, 1986; **69**: 534–540.

631. von Schewelov, Sanzén L, Önsten I, Carlsson A, Besjakov J. Total hip replacement with a zirconium oxide ceramic femoral head. A randomized Roentgen stereophotogrammetric study. *J. Bone Joint Surg. (Br.)*, 2005; **87-B**: 1631–1635.
632. Kraay MJ, Thomas RD, Rimnac CM, Fitzgerald SJ, Goldberg VM. Zirconia versus Co–Cr femoral heads in total hip arthroplasty: Early assessment of wear. *Clin. Orthop. Relat. Res.*, 2006; **453**: 86–90.
633. Hall RM, Unsworth A. Friction in hip prostheses. *Biomaterials*, 1997; **18**: 1017–1026.
634. Clarke IC, Pezzotti G, Sakakura S, Sugano N. Phase transformation and residual stresses in retrieved zirconia ball implant. *Key Eng. Mater.*, 2003; **240–242**: 781–784.
635. Katagiri G, Ishida H, Ishitani A, Masaki T. Direct determination by Raman microprobe of the transformation zone size in Y_2O_3 containing tetragonal ZrO_2 polycrystals. In *Advances in ceramics, Vol. 24, Science and technology of zirconia III*. Somiya S, Yamamoto N, Yanagida H (Eds.). The American Ceramic Society, Columbus, OH, pp. 537–544, 1988.
636. Munoz-Saldana J, Balmori-Ramirez H, Jaramillo-Vigueras D, Iga T, Schneider GA. Mechanical properties and low-temperature aging of tetragonal zirconia polycrystals processed by hot isostatic pressing. *J. Mater. Res.*, 2003; **18**: 2415–2426.
637. Masonis JL, Bourne RB, Ries MD, McCalden RW, Salehi A, Kelman DC. Zirconia femoral head fractures: a clinical and retrieval analysis. *J. Arthroplasty*, 2004; **19**: 898–905.
638. Hellmann JR, Stubican VS. Stable and metastable phase relations in the system zirconia–calcia. *J. Am. Ceram. Soc.*, 1983; **66**: 260–264.
639. Roy ME, Whiteside LA, Katerberg BJ, Steiger JA. Phase transformation, roughness, and microhardness of artificially aged yttria- and magnesia-stabilized zirconia femoral heads. *J. Biomed. Mater. Res A*, 2007; **83-A**: 1096–1102.
640. Roy ME, Whiteside LA, Katerberg BJ, Steiger JA, Nayfeh TA. Not all zirconia femoral heads degrade *in vivo*. *Clin. Orthop. Relat. Res.*, 2007; **465**: 220–226.
641. Roy ME, Whiteside LA. Clinical comparison of polyethylene wear with zirconia or cobalt–chromium femoral heads. *Clin. Orthop. Relat. Res.* 2010; 468: 624–625.
642. Shimizu K, Oka M, Kumar P, Kotoura Y, Yamamuro T, Makinouchi K, Nakamura T. Time-dependent changes in the mechanical properties of zirconia ceramic. *J. Biomed. Mater. Res.*, 1993; **27**: 729–734.

643. Makinouchi K, Yanagida T, Shimizu K. Development of zirconia ceramic for implants. *Orthop. Ceram. Implant Jpn.*, 1992; **8**: 173–177.
644. Johnson W, Mehl R. Reaction kinetics in processes of nucleation and growth. *Trans. Am. Inst. Min. Metall. Pet. Eng.*, 1939; **135**: 416–441.
645. Chevalier J, Cales B, Drouin JM. Low temperature aging of Y-TZP ceramics. *J. Am. Ceram. Soc.*, 1999; **82**: 2150–2154.
646. Yashima M, Yoshimura M. Phase formation in rapidly quenched rare earths doped zirconia melts. In *Zirconia ceramics 12*. Masaki T, Yoshimura M. (Eds.). Japan Materials Research Society, Uchida Rokakuho, Tokyo, Japan, pp. 21–46, 1992.
647. Kim D-J, Park I-S, Lee K-Y, Chevalier J, Attaoui H, Han J-S. Subcritical crack growth resistance of low temperature degradation free zirconia/alumina composite for medical applications. *Key Eng. Mater.*, 2005; **284–286**: 1007–1010.
648. Ohmichi N, Kamioka K, Ueda K, Matsui K, Ogai M. Phase transformation of zirconia ceramics by annealing in hot water. *J. Ceram. Soc. Jpn.*, 1999; **107**: 128–133.
649. Matsui K, Horikoshi H, Ohmichi Y, Ohgai M, Yoshida H, Ikuhara Y. Cubic-formation and grain — growth mechanisms in tetragonal zirconia polycrystal. *J. Am. Ceram. Soc.*, 2003; **86**: 1401–1408.
650. Yamashita I, Tsukuma K. Phase separation and hydrothermal degradation of 3 mol% Y_2O_3 - ZrO_2 ceramics. *J. Ceram. Soc. Jpn.*, 2005; **113**: 530–533.
651. Chevalier J, Deville S, Münch E, Jullian R, Lair F. Critical effect of cubic phase on aging 3 mol% yttria-stabilized zirconia ceramics for hip replacement prosthesis. *Biomaterials*, 2004; **25**: 5539–5545.
652. Michel D, Van Den Borre MT, Ennaciri A. Vibrational spectra and force fields of tetragonal zirconia and zirconium germanates. *Advances in ceramics 24: Science and technology of zirconia III*. Somiya S, Yamamoto N, Yanagida H (Eds.). The American Ceramic Society, Columbus, OH, pp. 555–562, 1988.
653. Howard CJ, Hunter BA. Oxygen position and bond length from lattice parameters in tetragonal zirconias. *J. Am. Ceram. Soc.*, 1998; **81**: 241–243.
654. Igawa N, Ishii Y. Crystal structure of metastable tetragonal zirconia up to 1473 K. *J. Am. Ceram. Soc.*, 2001; **84**: 1169–1171.
655. Kim D-J, Jang J-W, Lee H-L. Effect of tetravalent dopants on Raman spectra of tetragonal zirconia. *J. Am. Ceram. Soc.*, 1997; **80**: 1453–1461.

- 656. Kim D-J, Jung H-J. Raman spectroscopy of tetragonal zirconia solid solution. *J. Am. Ceram. Soc.*, 1993; **76**: 2106–2108.
- 657. Yashima M, Ishizawa N, Yoshimura M. Application of an ion-packing model based on defect clusters to zirconia solid solutions. *J. Am. Ceram. Soc.*, 1992; **75**: 1541–1549.
- 658. Zhao X, Vanderbilt D. Phonons and lattice dielectric properties of zirconia. *Phys. Rev. B*, 2002; **65**: 075105-1–10.
- 659. Ohmichi N, Kamioka K, Ueda K, Matsui K. Phase transformation of zirconia ceramic by annealing in hot water. *J. Ceram. Soc. Jpn.*, 1999; **107**: 128–133.
- 660. Ma Q, Pompe W, Clarke DR. Residual stress in Al_2O_3 - ZrO_2 composites: A test of stochastic stress models. *Acta Metall. Mater.*, 1994; **42**: 1673–1681.
- 661. Lawson S. Environmental degradation of zirconia ceramics. *J. Eur. Ceram. Soc.*, 1995; **15**: 485–502.
- 662. Seung KL, Rajan T, Readey MJ, Lawn BR. Scratch damage in zirconia ceramics. *J. Am. Ceram. Soc.*, 2000; **83**: 1428–1432.
- 663. Lu X, Liang K, Gu S, Zheng Y, Fang H. Effect of oxygen vacancies on transformation of zirconia at low temperatures. *J. Mater. Sci.*, 1997; **32**: 6653–6656.
- 664. Petrik NG, Taylor DP, Orlando TM. Laser-stimulated luminescence of yttria-stabilized cubic zirconia crystals. *J. Appl. Phys.*, 1999; **85**: 6770–6776.
- 665. Li P, Chen I-W, Penner-Hahn JE. X-ray-absorption studies of zirconia polymorphs. I. Characteristic local structures. *Phys. Rev. B*, 1993; **48**: 10063–10073.
- 666. Smits K, Grigorjeva L, Qojkowski W, Fidelus JD. Luminescence of oxygen related defects in zirconia nanocrystals. *Phys. Status Solidi (c)*, 2007; **4**: 770–773.
- 667. Gholinia A, Leach C. Cathodoluminescence microscopy of impurity phases in ZrO_2/Ni nano-composites. *J. Mater. Sci.*, 1997; **32**: 6625–6628.
- 668. Shibano T, Takigawa Y, Uesugi T, Higashi K. Effect of second phase particles on phase stability of zirconia in hot water. *Adv. Mater. Res.*, 2007; **26–28**: 781–784.
- 669. Chevalier J, Grandjean S, Kuntz M, Pezzotti G. Activation energy for polymorphic transformation in an advanced alumina/zirconia composite for orthoplastic applications. *Biomaterials*, 2009; **30**: 5279–5282.

670. Liang B, Kawanabe K, Ise K, Iida H, Nakamura T. Polyethylene wear against alumina and zirconia heads in cemented total hip arthroplasty. *J. Arthroplasty*, 2007; **22**: 251–257.
671. Lu Z, McKellop H. Frictional heating of bearing materials tested in a hip joint wear simulator. *Proc. Inst. Mech. Eng. H*, 1997; **211**: 101–108.
672. Kim YH, Kim JS, Cho SH. A comparison of polyethylene wear in hips with cobalt-chrome or zirconia heads. A prospective, randomised study. *J. Bone Joint Surg. (Br.)*, 2001; **83**: 742–750.
673. Trunec M. Effect of grain size on mechanical properties of 3Y-TZP ceramics. *Ceramics — Silikáty*, 2008; **52**: 165–171.
674. Shevchenko AV, Ruban AK, Dudnik EV. High-technology ceramics based on zirconium dioxide. *Ogneup. Tekh. Keram.*, 2000; **9**: 2–8.
675. Pezzotti G, Matsutani A, Zhu W. Spectroscopic assessments of domain texture in barium titanate: I. Confocal Raman polarization analysis. *J. Am. Ceram. Soc.*, 2010; **93**: 256–264.
676. Tang X, Zheng X. Raman scattering and *t*-phase lattice vibration of 3% (mole fraction) Y_2O_3 - ZrO_2 . *J. Mater. Sci. Technol.*, 2004; **20**: 485–489.
677. Sobukawa H. Development of ceria-zirconia solid solutions and future trends. R&D Review Toyota CRDL 2002; **37(4)**: 1–5.
678. Pushkarev VV, Kovalchuk VI, d'Itri JL. Probing defect sites on the CeO_2 surface with dioxygen. *J. Phys. Chem. B*, 2004; **108**: 5341–5348.
679. Chevalier J, Gremillard L, Virkar AV, Clarke DR. The tetragonal-monoclinic transformation in zirconia: lessons learned and future trends. *J. Am. Ceram. Soc.*, 2009; **92**: 1901–1920.
680. Eichler A. Tetragonal Y-doped zirconia: Structure and ion conductivity. *Phys. Rev. B*, 2001; **64**: 174103-1–8.
681. Bonanos N, Butler EP. Ionic conductivity of monoclinic and tetragonal yttria-zirconia single crystals. *J. Mater. Sci. Lett.*, 1985; **4**: 561–564.
682. Badwal SPS. Zirconia-based solid electrolytes: Microstructure, stability and ionic conductivity. *Solid State Ionics*, 1992; **52**: 23–32.
683. Filal M, Petot C, Petot-Ervas G, Amamra MC, Carpentier JL, Dellis JL. Influence of the dopants and of the microstructure on the ionic conductivity of zirconia. *J. Phys. IV*, 1993; **3**: C7-1463–1466.
684. Marro FG, Valle J, Mestra A, Anglada M. Improvement of 3Y-TZP hydrothermal degradation resistance by surface modification with ceria without impairing mechanical properties. *IOP Conf. Series: Mater. Sci. Eng.*, 2009; **5**: 012015-1–8.
685. Claussen N. Microstructural design of zirconia-toughened ceramics ZTC. In: *Advances in Ceramics, Vol. 12: Science and Technology of*

- Zirconia II* (Claussen N, Rühle M, Heuer AH, eds). (American Ceramic Society, Westerville, Ohio 1984); pp. 325–351.
686. Rieu J, Goeuriot P. Ceramic composites for biomedical applications. *Clin. Mater.* 1993; **12**: 211–217.
687. Affatato S, Testoni M, Cacciari GL, Toni A. Mixed-oxide prosthetic ceramic ball heads. *Biomaterials*, 1999; **20**: 1925–1929.
688. Bartolomé JF, De Aza AH, Martín A, Pastor JY, Llorca J, Torrecillas R, Bruno G. Alumina/zirconia micro/nanocomposites: A new material for biomedical applications with superior sliding wear resistance. *J. Am. Ceram. Soc.*, 2007; **90**: 3177–3184.
689. Burger W. Umwandlungs- und plateletverstärkte Aluminiumoxid-Matrixwerkstoffe (Teil 1). *Keram. Z.*, 1997; **49**: 1067–1070.
690. Burger W, Richter HG. High strength and toughness alumina matrix composites by transformation toughening and “*in situ*” platelet reinforcement (ZPTA). *Key Eng. Mater.*, 2001; **192–195**: 545–548.
691. Deville S, Chevalier J, Fantozzi G, Bartolomé JF, Requena J, Moya JS, Díaz LA, Torrecillas R. Low-temperature ageing of zirconia-toughened alumina ceramics and its implication in biomaterial implants. *J. Eur. Ceram. Soc.*, 2003; **23**: 2975–2982.
692. Affatato S, Goldoni M, Testoni M, Toni A. Mixed oxides prosthetic ceramic ball heads. Part III: Effect of the ZrO_2 fraction on the wear of ceramic on polyethylene joints. A long-term *in vitro* wear study. *Biomaterials*, 2001; **22**: 717–723.
693. Stewart TP, Tipper JL, Insley G, Streicher RM, Ingham E, Fisher J. Long-term wear of ceramic-matrix composite material for hip prostheses under severe swing phase microsimulation. *J. Biomed. Mater. Res. Appl. Biomater.*, 2003; **66B**: 567–573.
694. Chang J-D, Kamdar R, Yoo J-H, Hur M, Lee S-S. Third generation ceramic-on-ceramic bearing surfaces in revision total hip arthroplasty. *J. Arthroplasty*, 2010; **24**: 1231–1235.
695. Hamilton WG, McAuley J, P, Dennis DA, Murphy JA, Blumenfeld TJ, Politi J. THA with Delta ceramic on ceramic. *Clin. Orthop.*, 2010; **468**: 358–366.
696. Sornakumar T, Krishnamurthy R, Gokularathnam CV. Machining performance of phase transformation toughened alumina and partially stabilized zirconia composite cutting tools. *J. Eur. Ceram. Soc.*, 1993; **12**: 455–460.
697. Kumar AS, Durai AR, Sornakumar T. Machinability of hardened steel using alumina based ceramic cutting tools. *Int. J. Refractory Met. Hard Mater.*, 2003; **21**: 109–117.

698. Taya M, Hayashi S, Kobayashi AS, Yoon HS. Toughening of a particulate-reinforced ceramic-matrix composite by thermal residual stress. *J. Am. Ceram. Soc.*, 1990; **73**: 1382–1391.
699. Mori T, Tanaka K. Average stress in matrix and average energy of materials with misfitting inclusions. *Acta Metall.*, 1973; **21**: 571–574.
700. Akiniwa Y, Tanaka K, Minakawa N, Morii Y. Neutron diffraction study of thermal residual stress in ceramic composite mater. *Sci. Res. Int.*, 2000; **6**: 281–286.
701. Harlan NR, Merino RI, Peña JI, Larrea A, Orera VM, González C, Poza P, LLorca J. Phase distribution and residual stresses in melt-grown $\text{Al}_2\text{O}_3\text{-ZrO}_2(\text{Y}_2\text{O}_3)$ eutectics. *J. Am. Ceram. Soc.*, 2002; **85**: 2025–2032.
702. Bobet JL, Ji N, LeBrun JL. The X-ray measurement of axial and hoop residual stresses in microcomposite specimens. *J. Thermal Stresses*, 1998; **21**: 743–749.
703. Ma Q, Pompe W, French JD, Clarke DR. Residual-stresses in $\text{Al}_2\text{O}_3\text{-ZrO}_2$ composites — a test of stochastic stress models. *Acta Metall. Mater.*, 1994; **42**: 1673–1681.
704. Garvie RC, Goss MF. Intrinsic size dependence of the phase transformation temperature in zirconia microcrystals. *J. Mater. Sci.*, 1986; **21**: 1253–1257.
705. Sergo V, Wang X-L, Clarke DR, Becher PF. Residual stress in alumina/ceria-stabilized zirconia composites. *J. Am. Ceram. Soc.*, 1995; **78**: 2213–2214.
706. Heuer AH, Claussen N, Kriven WM, Rühle M. Stability of tetragonal ZrO_2 particles in ceramic matrices. *J. Am. Ceram. Soc.*, 1982; **65**: 642–650.
707. Takao Y, Taya M. Thermal expansion coefficients and thermal stresses in an aligned short fiber composite with application to a short carbon fiber/aluminum. *J. Appl. Mech.*, 1985; **52**: 806–810.
708. Orera VM, Cemborain R, Merino RI, Peña JI, Larrea A. Piezo-spectroscopy at low temperatures: residual stresses in $\text{Al}_2\text{O}_3\text{-ZrO}_2(\text{Y}_2\text{O}_3)$ eutectics measured from 77 to 350 K. *Acta Mater.*, 2001; **50**: 4677–4686.
709. Budiansky B, Hutchinson J, Lambropoulos J. Continuum theory of dilatant transformation toughening in ceramics. *Int. J. Solids Struct.*, 1983; **19**: 337–355.
710. Amazigo JC, Budiansky B. Steady-state crack growth in supercritically transforming materials. *Int. J. Solids Struct.*, 1988; **24**: 751–755.

711. Ikeda J, Mabuchi M, Nakanishi T, Miyaji F, Ueno M, Pezzotti G. Phase stability and fracture toughness of zirconia toughened alumina for joint replacement. *Key Eng. Mater.*, 2008; **361-363**:: 767-770.
712. Tuan WH, Chen RZ, Wang TC, Cheng CH, Kuo PS. Mechanical properties of $\text{Al}_2\text{O}_3/\text{ZrO}_2$ composites. *J. Eur. Ceram. Soc.*, 2002; **22**: 2827-2833.
713. Tuan W-H, Chen J-R, Ho C-J. Critical zirconia amount to enhance the strength of alumina. *Ceram. Int.*, 2008; **34**: 2129-2135.
714. Rao PG, Iwasa M, Tanaka T, Kondoh I, Inoue T. Preparation and mechanical properties of Al_2O_3 -15 wt.% ZrO_2 composites. *Scripta Mater.*, 2003; **48**: 437-441.
715. Szutkowska M. Fracture resistance behavior of alumina-zirconia composites. *J. Mater. Proc. Tech.*, 2004; **153-54**: 868-874.
716. Shin YS, Rhee YW, Kang SJ. Experimental evaluation of toughening mechanism in alumina-zirconia composites. *J. Am. Ceram. Soc.*, 1999; **82**: 1229-1232.
717. Kuntz M, Masson B, Pandorf T. Current state of the art of the ceramic composite material BIOLOX®*delta*. In: *Strength of Materials*. (Mendes G, Lago B, eds) (Nova Science Publishers, Inc., Huntington, New York, 2009); pp. 133-155.
718. Nakanishi T, Sasaki M, Ikeda J, Miyaji F, Kondo M. Mechanical and phase stability of zirconia toughened alumina. *Key Eng. Mater.*, 2007; **330-332**: 1267-1270.
719. Sergo V, Clarke DR. Deformation bands in ceria-stabilized tetragonal zirconia/alumina: II, Stress-induced aging at room temperature. *J. Am. Ceram. Soc.*, 1995; **78**: 641-644.
720. Sergo V, Lipkin DM, De Portu G, Clarke DR. Edge stresses in ceramics laminate composites. *J. Am. Ceram. Soc.*, 1997; **80**: 1633-1639.
721. Sergo V. Room-temperature aging of laminate composites of alumina/3-mol%-yttria-stabilized tetragonal zirconia polycrystals. *J. Am. Ceram. Soc.*, 2004; **87**: 247-253.
722. Deville S, Chevalier J, Dauvergne CH, Fantozzi G, Bartolomé JF, Moya JS, Torrecillas R. Microstructural investigation of the aging behavior of (3Y-TZP)- Al_2O_3 composites. *J. Am. Ceram. Soc.*, 2005; **88**: 1273-1280.
723. ASTM F2033-05. Standard specification for total hip joint prosthesis and hip endoprosthesis bearing surfaces made of metallic, ceramic, and polymeric materials. In: *Book of Standards*, Vol. 13.01 (West Conshohocken, PA: ASTM International, 2005).

724. Pulliam IT, Trousdale RT. Fracture of a ceramic femoral head after a revision operation. A case report. *J. Bone Joint Surg. (Am.)*, 1997; **79**: 118–121.
725. Pfaff H-G, Rack R, Willmann G. Long-term performance of a transformation toughened platelet reinforced alumina matrix composite. *Bioceramics*. 2001; **14**: 541–542.
726. Insleyand G, Steicher R. Next generation ceramics based on zirconia toughened alumina for hip joint prostheses. *Key Eng. Mater.* 2004; **254–256**: 675–678.
727. Rühle M, Heuer AH, Claussen N. Transformation and microcrack toughening as complementary processes in zirconia-toughened alumina. *J. Am. Ceram. Soc.*, 1986; **69**: 195–197.
728. Claussen NJ, Fracture toughness of Al_2O_3 with an unstable ZrO_2 dispersed second phase. *J. Am. Ceram. Soc.*, 1976; **61**: 49–51.
729. Nojima T, Nakai O. Stable crack extension of an alumina ceramic in three point bending test. (in Jpn.) *J. Soc. Mater. Sci. Jpn.*, 1993; **42**, 142–148.
730. Srawley JE. Wide range stress intensity factor expressions for ASTM E399 Standard Fracture Toughness Specimens. *Int. J. Fract.*, 1976; **12**: 475–476.
731. Kruzic J, Ritchie O. Determining the toughness of ceramics from Vickers indentations using the crack-opening displacements: An experimental study. *J. Am. Ceram. Soc.*, 2003; **86**: 1433–1436.
732. Chevalier J, Deville S, Fantozzi G, Bartolomé JF, Pecharroman C, Moya JS, Diaz LA, Torrecillas R. Nanostructured ceramic oxides with a slow crack growth resistance close to covalent materials. *Nano Lett.*, 2005; **5**: 1297–1310.
733. Benzaid R, Chevalier J, Saâdaoui M, Fantozzi G, Nawa M, Diaz LA, Torrecillas R. Fracture toughness, strength and slow crack growth in a ceria stabilized zirconia–alumina nanocomposite for medical applications. *Biomaterials*, 2008; **29**: 3636–3641.
734. Akimov GYa, Timchenko VM. Effect of strain rate and preloading on the fracture toughness of ZrO_2 -based ceramics. *Strength Mater.*, 2002; **34**: 514–517.
735. Pezzotti G, Okamoto Y, Nishida T, Sakai M. On the near-tip toughening by crack-face bridging in particulate and platelet-reinforced ceramics. *Acta Mater.*, 1996; **44**: 899–914.
736. Novak S, Kalin M, Lukas P, Anne G, Vleugels J, Van Der Biest O. The effect of residual stresses in functionally graded alumina-ZTA composites on their wear and friction behavior. *J. Eur. Ceram. Soc.*, 2007; **27**: 151–156.

737. Yueh HK, Cox B. Luminescence properties of zirconium oxide films. *J. Nucl. Mater.*, 2003; **323**: 57–67.
738. Xu J, Mao HK, Bell PM. High-pressure ruby and diamond fluorescence: Observations at 0.21 to 0.55 terapascal. *Science*, 1986; **232**: 1404–1406.
739. Mikhailik VB, Di Stefano PCF, Henry S, Kraus H, Lynch A, Tsybul'skyi V, Verdier MA. Studies of concentration dependences in the luminescence of Ti-doped Al_2O_3 . *J. Appl. Phys.*, 2011; **109**: 053116-1–6.
740. Lee CH, Kröger FA. Electrical conductivity of polycrystalline Al_2O_3 doped with silicon. *J. Am. Ceram. Soc.*, 1985; **68**: 92–99.
741. Lushchik A, Lushchik Ch., Kirm M, Nagirnyi V, Savikhin F, Vasil'chenko E. Defect creation caused by the decay of cation excitons and hot electron-hole recombination in wide-gap dielectrics. *Nucl. Instr. Meth. B*, 2006; **250**: 330–336.
742. Mohapatra SK, Kröger FA. Defect structure of $\alpha\text{-Al}_2\text{O}_3$ doped with titanium. *J. Am. Ceram. Soc.*, 1977; **60**: 381–387.
743. Guo X. Property degradation of tetragonal zirconia induced by low-temperature defect reaction with water molecules. *Chem. Mater.*, 2004; **16**: 3988–3994.
744. Schubert H, Frey F. Stability of Y-TZP during hydrothermal treatment: Neutron experiments and stability considerations. *J. Eur. Ceram. Soc.*, 2005; **25**: 1597–1602.
745. Pezzotti G, Takahashi Y, Zhu W. In-depth profiling of elastic residual stress and the *in vivo* wear mechanism of self-mating alumina hip joints. *Wear*, 2012; **284–285**: 91–97.
746. Kreher W, Pompe W. *Internal Stresses in Heterogeneous Solids*. Akademie Verlag: Berlin (1988).
747. Gregori G, Burger W, Sergio V. Piezo-spectroscopic analysis of the residual stresses in zirconia-toughened alumina ceramics: The influence of the tetragonal-to-monoclinic transformation. *Mater. Sci. Eng. A*, 1999; **271**: 401–406.
748. Larché F, Cahn JW. The interactions of composition and stress in crystalline solids. *Acta Metall.*, 1985; **33**: 331–357.
749. Pezzotti G, Yamada K, Sakakura S, Pitto RP. Raman spectroscopic analysis of advanced ceramic composite for hip prosthesis. *J. Am. Ceram. Soc.*, 2008; **91**: 1199–1206.

750. Puchin VE, Gale JD, Shluger AL, Kotomin EA, Günster J, Brause M, Kempter V. Atomic structure of the (0001) corundum surface. *Surf. Sci.*, 1997; **370**: 190–200.
751. Zhu W, Puppulin L, Leto A, Takahashi Y, Sugano N, Pezzotti G. *In situ* measurements of local temperature and contact stress magnitude during wear of ceramic-on-ceramic hip joints. *J. Mech. Behavior Biomater.* DOI: 10.1016/j.jmbbm.2013.01.018.
752. Mc Cumber DE, Sturge MD. Linewidth and temperature shift of the R lines in ruby. *J. Appl. Phys.*, 1963; **34**: 1682–1684.
753. Huber MT. Zur Theorie der Berührung fester elastischer Körper. *Ann. Phys.*, 1904; **14**: 153–163.
754. Deeg EW. New algorithms for calculating Hertzian stresses, deformations, and contact zone parameters. *AMP J. Tech.*, 1992; **2**: 14–24.
755. Clarke IC, Green D, Williams P, Donaldson T, Pezzotti G. US perspective on hip simulator wear testing of BIOLOX®*delta* in “severe” test modes. In: *Bioceramics and Alternative Bearings in Joint Arthroplasty*. (Benazzo F, Falez F, Dietrich M, eds) (Steinkopff Verlag, Darmstadt, Germany, 2006); pp. 189–205.
756. Harris WH. The problem is osteolysis. *Clin. Orthop.*, 1995; **311**: 46–53.
757. Fisher J. Biomedical Applications. Modern Tribology Handbook, Vol. Two: Materials, Coating and Industrial Applications, (Bharat Bhushan. Florida: CRC Press, Boca Raton; 2001, pp. 1593–1609.
758. Green TR, Fisher J, Stone MH, Wroblewski BM, and Ingham E. Polyethylene particles of a “critical size” are necessary for the induction of cytokines by macrophages *in vitro*. *Biomaterials*, 1998; **19**: 2297–2302.
759. Semlitsch M, Lehmann M, Weber H, Doerre E, Willert HG. New prospects for a prolonged functional life span of artificial hip joints by using the material combination polyethylene/aluminum oxide ceramic metal. *J. Biomed. Mater. Res.*, 1977; **11**: 537–552.
760. Oonishi H, Kuno M, Tsuji E, Fujiwara A. The optimum dose of gamma radiation-heavy doses to low wear to low wear polyethylene in total hip prostheses. *J. Mater. Sci.: Mater. Med.*, 1997; **8**: 11–18.
761. Scott M, Morrison M, Mishra SR, Jani S. Particle analysis for the determination of UHMWPE wear. *J. Biomed. Mater. Res. B*, 2005; **73**: 325–337.

762. McKellop H, Shen F, Lu B, Campbell P, Salovey R. Development of an extremely wear-resistant ultra high molecular weight polyethylene for total hip replacement. *J. Orthop. Res.*, 1999; **17**: 157–167.
763. Oonishi H, Saito M, Kadoya Y. Wear of high-dose gamma irradiated polyethylene in total joint replacement-Long term radiological evaluation. In: *Transaction of the 44th Annual Meeting of the Orthopaedic Research Society*, New Orleans, LA, March 16–19, 1998; 97: 17.
764. Digas G, Kärrholm J, Thanner J, Malchau H, Herberts P. The Otto Aufranc Award. Highly cross-linked polyethylene in total hip arthroplasty: Randomized evaluation of penetration rate in cemented and uncemented sockets using radiostereometric analysis. *Clin. Orthop. Relat. Res.*, 2004; **429**: 6–16.
765. Dorr LD, Wan Z, Shahrdrar C, Sirianni L, Boutary M, Yun A. Clinical performance of a Durasul highly corss-linked polyethylene acetabular liner for total hip arthroplasty at five years. *J. Bone Joint Surg., (Am.)* 2005; **87**: 1816–1821.
766. Zhao Y, Luo YX, Jiang BZ. Effect of irradiation on crystallinity and mechanical properties of ultrahigh molecular-weight polyethylene. *J. Appl. Polym. Sci.*, 1993; **50**: 1797–1801.
767. Lewis G. Properties of crosslinked ultra-high-molecular-weight polyethylene. *Biomaterials*, 2001; **22**: 371–401.
768. Oral E, Malhi AS, Muratoglu OK. Mechanism of decrease in fatigue crack propagation resistance in irradiated and melted UHMWPE. *Biomaterials*, 2006; **27**: 917–925.
769. Eyerer P, Ke YC. Property changes of UHMW polyethylene hip cup endoprostheses during implantation. *J. Biomed. Mater. Res.*, 1984; **18**: 1137–1151.
770. Fouad H. Effect of long-term aging on the thermal, mechanical, and viscoelastic behavior of biomedical grade of ultra high molecular weight polyethylene. *J. Appl. Polym. Sci.*, 2010; **118**: 17–24.
771. Oral E, Godleski Beckos C, Bassem W, Ghali BW, Lozynsky AJ, Muratoglu OK. Effect of crosslink density on the high pressure crystallization of UHMWPE. *J. Biomed. Mater. Res. B: Appl. Biomater.*, 2009; **90**: 720–729.
772. Bellare A, Cohen RE. Morphology of rod stock and compression-moulded sheets of ultra-high-molecular-weight polyethylene used in orthopaedic implants. *Biomaterials*, 1996; **17**: 2325–2333.

773. Edidin AA, Pruitt L, Jewett CW, Crane DJ, Roberts D, Kurtz SM. Plasticity-induced damage layer is a precursor to wear in radiation-cross-linked UHMWPE acetabular components for total hip replacement. *J. Arthroplasty.*, 1999; **14**: 616–627.
774. Dumbleton JH, D'Antonio JA, Manley MT, Capello WN, Wang A. The basis for a second-generation highly cross-linked UHMWPE. *Clin. Orthop. Relat. Res.*, 2006; **453**: 265–271.
775. Campbell DG, Field JR, Stuart AC. Second-generation highly cross-linked X3TM polyethylene wear: A preliminary radiostereometric analysis study. *Clin. Orthop. Relat. Res.*, 2010; **468**: 2704–2709.
776. Bellare A, Schnablegger H, Cohen RE. A small-angle X-ray scattering study of high-density polyethylene and ultra-high molecular weight polyethylene. *Macromolecules*, 1995; **17**: 2325–2333.
777. Jaynes ET. Information theory and statistical mechanics. *Phys. Rev.*, 1957; **106**: 620–630.
778. Pérez R, Banda S, Ounaies Z. Determination of the orientation distribution function in aligned single wall nanotube polymer composites by polarized Raman spectroscopy. *J. Appl. Phys.*, 2008; **103**: 074302-1–14.
779. Roe RJ. Orientation distribution function of statistical segments in deformed polymer networks. *J. Appl. Phys.*, 1964; **35**: 2215–2219.
780. Wang A, Polineni VK, Essner AP, Sokol M, Sun DC, Stark C, Dumbleton JH. The significance of nonlinear motion in the wear screening of orthopaedic implant materials. *J. Test. Eval.*, 1997; **25**: 239–245.
781. Oonishi H, Takayama Y, Tsuji E. Improvement of polyethylene by irradiation in artificial joints, *Radiat. Phys. Chem.*, 1992; **39**: 495–504.
782. Wroblewski GM, Siney PD, Dowson D, Collins SN. A prospective clinical and joint simulator study of the performance of 22 mm alumina ceramic heads and polyethylene acetabular cups in total hip arthroplasty. *J. Bone Joint Surg. (Br.)*, 1996; **78**: 280–285.
783. Sambasivan S, Fischer DA, Hsu SM. Effect of cross-linking ultrahigh molecular weight polyethylene: Surface molecular orientation and wear characteristics. *J. Vac. Sci. Technol. A*, 2007; **25**: 932–937.
784. Popli R, Mandelkern L. Influence of structural and morphological factors on the mechanical properties of the polyethylenes. *J. Polym. Sci. Polym. Phys. Edn.*, 1987; **25**: 441–483.
785. Williamson GR, Wright B, Haward RN. The preparation and properties of fractions from high density polyethylenes. *J. Appl. Chem.*, 1964; **14**: 131–140.

786. Fleissner M. Die Spezifische Bruchenergie von Polyethylen in Abhängigkeit von Strukturellen Parametern. *Die Angew. Macromol. Chem.*, 1982; **105**: 167–185.
787. Lu X, Qian R, Brown N. The effect of crystallinity on fracture and yielding of polyethylenes. *Polymer*, 1995; **36**: 4239–4244.
788. Lin L, Argon AS. Review Structure and plastic deformation of polyethylene. *J. Mater. Sci.*, 1994; **29**: 294–323.
789. Philip M, Ward IM, Parsons B. A comparison of tensile, compressive and torsional creep in isotropic and oriented polyethylene. *J. Mater. Sci.*, 1986; **21**: 879–886.
790. Bartczak Z. Effect of chain entanglements on plastic deformation behavior of ultra-high molecular weight polyethylene. *J. Polym. Sci., Part B: Polym. Phys.*, 2010; **48**: 276–285.
791. Lee KY, Pienkowski D. Compressive creep characteristics of extruded ultrahigh-molecular weight polyethylene. *J. Biomed. Mater. Res.*, 1998; **39**: 261–265.
792. Collier JP, Currier BH, Kennedy FE, Currier JH, Timmins GS, Jackson SK, Brewer RL. Comparison of cross-linked polyethylene materials for orthopaedic applications. *Clin. Orthop. Relat. Res.*, 2003; **414**: 289–304.
793. Wang A, Zeng H, Yau S-S, Essner A, Manely M, Dumbleton J. Wear, oxidation and mechanical properties of a sequentially irradiated and annealed UHMWPE in total joint replacement. *J. Phys. D: Appl. Phys.*, 2006; **39**: 3213–3219.
794. Barron D, Birkinshaw C. On the morphology of some irradiated ultra high molecular weight polyethylenes. *Polym. Degradation and Stability*, 2009; **94**: 1621–1631.
795. Moonen JAHM, Roovers WAC, Meier RJ, Kip, BJ. Crystal and molecular deformation in strained high-performance polyethylene fibers studied by wide-angle X-ray scattering and Raman spectroscopy. *J. Polym. Sci.: Part B: Polym. Phys.*, 1992; **30**: 361–372.
796. Tashiro K, Wu G, Kobayashi M. Morphological effect on the Raman frequency shift induced by tensile stress applied to crystalline polyoxymethylene and polyethylene: Spectroscopic support for the idea of an inhomogeneous stress distribution in polymer material. *Polymer*, 1988; **29**: 1768–1783.
797. Yeh WY, Young RJ. Deformation processes in poly(ethylene terephthalate) fibers. *J. Macromol. Sci. — Phys.*, 1998; **B37**: 83–118.

798. Bartczak Z, Argon AS, Cohen RE. Deformation mechanisms and plastic resistance in single-crystal-textured high-density polyethylene. *Macromolecules*, 1992; **25**: 5036–5053.
799. Galeski A, Bartczak Z, Argon AS, Cohen RE. Morphological alterations during texture-producing plastic plane strain compression of high-density polyethylene. *Macromolecules*, 1992; **25**: 5705–5718.
800. Boontongkong Y, Cohen RE, Spector M, Bellare A. Orientation of plane strain-compressed ultra-high-molecular-weight polyethylene. *Polymer*, 1998; **39**: 6391–6400.
801. Wroblewski B. Direction and rate of socket wear in Charnley low friction arthroplasty. *J. Bone Joint Surg. (Br.)*, 1985; **67**: 757–761.
802. McDonald MD, Bloebaum RD. Distinguishing wear and creep in clinically retrieved polyethylene inserts. *J. Biomed. Mater. Res.*, 1995; **29**: 1–7.
803. Huber J, Walter A, Plitz W, Refior HJ. Effect of the manufacturing process on creep and wear properties of UHMWPE (ultra-high molecular weight polyethylene). *Biomed. Tech. (Berl.)*, 1995; **40**: 88–92.
804. Taddei P, Affatato S, Fagnano C, Bordini B, Tinti A, Toni A. Vibrational spectroscopy of ultra-high molecular weight polyethylene hip prostheses: Influence of the sterilization method on crystallinity and surface oxidation. *J. Mol. Struct.*, 2002; **613**: 121–129.
805. Goldman M, Gronsky R, Ranganathan R, Pruitt L. The effects of gamma radiation sterilization and ageing on the structure and morphology of medical grade ultra high molecular weight polyethylene. *Polymer*, 1996; **37**: 2909–2913.
806. Heisel C, Silva M, dela Rosa MA, and Schmalzried TP. Short-term *in vivo* wear of cross-linked polyethylene. *J. Bone Joint Surg. (Am.)*, 2004; **86**: 748–751.
807. Gomez-Barrena E, Li S, Furman BS, Masri BA, Wright TM, Salvati EA. Role of polyethylene oxidation and consolidation defects in cup performance. *Clin. Orthop. Relat. Res.*, 1998; **352**: 105–117.
808. Stea S, Antonietti B, Baruffaldi F, Visentin M, Bordini B, Sudanese A, Toni A. Behavior of Hylamer polyethylene in hip arthroplasty: Comparison of two gamma sterilization techniques. *Int. Orthop.*, 2006; **30**: 35–38.
809. Williams S, Isaac G, Porter P, Fisher J, Older J. Long-term radiographic assessment of cemented polyethylene acetabular cups. *Clin. Orthop. Relat. Res.*, 2008; **466**: 366–372.

810. Affatato S, Bersaglia G, Rocchi M, Taddei P, Fagnano C, Toni A. Wear behaviour of cross-linked polyethylene assessed *in vitro* under severe conditions. *Biomaterials*, 2005; **26**: 3259–3267.
811. McKellop HA, Campbell P, Park SH, Schmalzried TP, Grigoris P, Amstutz HC, Sarmiento A. The origin of submicron polyethylene wear debris in total hip arthroplasty. *Clin. Orthop.*, 1995; **311**: 3–20.
812. Kabo J, Gebhard S, Loren G, Amstutz HC. *In vivo* wear of polyethylene acetabular components. *J. Bone Joint Surg. (Br.)*, 1993; **75**: 254–258.
813. Lewis G, Carroll M. Effect of crosslinking UHMWPE on its tensile and compressive creep performance. *Bio-Med. Mater. Eng.*, 2001; **11**: 167–183.
814. Galvin AL, Ingham E, Stone MH, Fisher J. Penetration, creep and wear of highly crosslinked UHMWPE in a hip joint simulator. *J. Bone Joint Surg. (Br.)*, 2006; **88** (Suppl. II): 236–241.
815. Digas G, Thanner J, Nivbrant B, Rohrl S, Strom HC, Karrholm J. Increase in early polyethylene wear after sterilization with ethylene oxide: Radiostereometric analyses of 201 total hips. *Acta Orthop., Scand.*, 2003; **74**: 531–541.
816. Rose RM, Goldfarb EV, Ellis E, Crugnola AN. Radiation sterilization and the wear rate of polyethylene. *J. Orthop. Res.*, 2005; **2**: 393–400.
817. Dowson D, Jobbins B. Design and development of a versatile hip joint simulator and a preliminary assessment of the wear and creep in Charnley total replacement hip joints. *Engng. Med.*, 1988; **17**: 111–117.
818. Tarantili PA, Andreopoulos AG, Galiotis C. Real-time micro-Raman measurements on stressed polyethylene fibers. 1. Strain rate effects and molecular stress redistribution. *Macromolecules*, 1998; **31**: 6964–6976.
819. Wool RP, Bretzlaff RS, Li BY, Wang CH, Boyd RH. Infrared and Raman spectroscopy of stressed polyethylene. *J. Polym. Sci. Part B: Polym. Phys.*, 1986; **24**: 1039–1066.
820. Wong WF, Young RJ. Molecular deformation processes in gel-spun polyethylene fibres using Raman spectroscopy. *J. Mater. Sci.*, 1994; **29**: 510–519.
821. Rull F, Prieto AC, Casado JM, Sobron F, Edwards HGM. Estimation of crystallinity in polyethylene by Raman spectroscopy. *J. Raman Spectrosc.*, 1993; **24**: 545–550.

822. Kyomoto M, Miwa Y, Pezzotti G. Strain in UHMWPE for orthopaedic use studied by Raman microprobe spectroscopy. *J. Biomater. Sci. Polym. Ed.*, 2007; **18**: 165–178.
823. Hiss R, Hobeika S, Lynn C, Strobl G. Network stretching, slip processes, and fragmentation of crystallites during uniaxial drawing of polyethylene and related copolymers. A comparative study. *Macromolecules*, 1999; **32**: 4390–4403.
824. Bell C, Walker P, Abeysundera M, Simmons J, King P, Blunn G. Effect of oxidation on delamination of ultrahigh-molecular-weight polyethylene tibial components. *J. Arthroplasty*, 2009; **13**: 280–290.
825. Muratoglu OK, Mark A, Vittetoe DA, Harris WH, Rubash HE. Polyethylene damage in total knees and use of highly crosslinked polyethylene. *J. Bone Joint Surg. (Am.)*, 2003; **85**: S7–S13.
826. Daly BM, Yin J. Subsurface oxidation of polyethylene. *J. Biomed. Mater. Res.*, 1998; **42**: 523–529.
827. Jacob RJ, Pienkowski D, Lee KY, Hamilton DM, Schroeder D, and Higgins J. Time- and depth-dependent changes in crosslinking and oxidation of shelf-aged polyethylene acetabular liners. *J. Biomed. Mater. Res.*, 2001; **56**: 168–176.
828. Glyn-Jones S, McLardy-Smith P, Gill HS, Murray DW. The creep and wear of highly cross-linked polyethylene. *J. Bone Joint Surg. (Br.)*, 2008; **90**: 556–561.
829. Bewill SL, Bevil GR, Penmetsa JR, Petrella AJ, Rullkoetter PJ. Finite element simulation of early creep and wear in total hip arthroplasty. *J. Biomech.*, 2005; **38**: 2365–2374.
830. Plank GR, Estok II DM, Muratoglu OK, O'Connor DO, Burroughs BR, Harris WH. Contact stress assessment of conventional and highly crosslinked ultra high molecular weight polyethylene acetabular liners with finite element analysis and pressure sensitive films. *J. Biomed. Mater. Res. Part B: Appl. Biomater.*, 2006; **80B**: 1–10.
831. Medel FJ, Rimnac CM, Kurtz SM. On the assessment of oxidative and microstructural changes after *in vivo* degradation of historical UHMWPE knee components by means of vibrational spectroscopies and nanoindentation. *J. Biomed. Mater. Res. Part B: Appl. Biomater.*, 2008; **89A**: 530–538.
832. Hood RW, Wright TM, Burstein AH. Retrieval analysis of total knee prostheses: A method and its application to 48 total condylar prostheses. *J. Biomed. Mater. Res.*, 1983; **17**: 829–842.

833. Buchanan FJ, White JR, Simand B, Downes S. The influence of gamma irradiation and aging on degradation mechanisms of ultra-high molecular weight polyethylene. *J. Mater. Sci. Mater. Med.*, 2001; **12**: 29–37.
834. Buchanan FJ, Simand B, Downes S. Effect of sterilisation and ageing on UHMWPE used in medical implants. *Plastics Rubber Compd. Process. Appl.*, 1998; **27**: 148–153.
835. Costa L, Bracco P, Brach del Prever E, Luda MP, Trossarelli L. Analysis of products diffused into UHMWPE prosthetic components *in vivo*. *Biomaterials*, 2001; **22**: 307–315.
836. Oral E, Ghali BW, Neils A, Muratoglu OK. A new mechanism of oxidation in ultrahigh molecular weight polyethylene caused by squalene absorption. *J. Biomed. Mater. Res. Part B: Appl. Biomater.*, 2012; **100B**: 742–751.
837. Amstutz HC, Campbell P, Kossovsky N, Clarke IC. Mechanism and clinical significance of wear debris-induced osteolysis. *Clin. Orthop.*, 1992; **276**: 7–18.
838. Oral E, Muratoglu OK. Radiation cross-linking in ultra-high molecular weight polyethylene for orthopaedic applications. *Nucl. Instrum. Methods Phys. Res. B*, 2007; **265**: 18–22.
839. Baker DA, Bellare A, Pruitt L. The effects of degree of crosslinking on the fatigue crack initiation and propagation resistance of orthopedic-grade polyethylene. *J. Biomed. Mater. Res.*, 2003; **66A**: 146–154.
840. Gencur SJ, Rimnac CM, Kurtz SM. Failure micromechanisms during uniaxial tensile fracture of conventional and highly crosslinked ultra-high molecular weight polyethylenes used in total joint replacements. *Biomaterials*, 2003; **24**: 3947–3954.
841. Muratoglu OK, Merrill EW, Bragdon CR, O'Connor D, Hoeffel D, Burroughs B, Jasty M, Harris WH. Effect of radiation, heat, and aging on *in vitro* wear resistance of polyethylene. *Clin. Orthop. Relat. Res.*, 2003; **417**: 253–262.
842. Wannomae K, Bhattacharyya S, Freiberg A, Estok D, Harris WH, Muratoglu O. *In vivo* oxidation of retrieved cross-linked ultra-high-molecular-weight polyethylene acetabular components with residual free radicals. *J. Arthropl.*, 2006; **21**: 1005–1011.
843. Oral E, Wannomae KK, Hawkins NE, Harris WH, Muratoglu OK. α -Tocopherol doped irradiated UHMWPE for high fatigue resistance and low wear. *Biomaterials*, 2004; **25**: 5515–5522.
844. Oral E, Muratoglu OK. Vitamin E diffused, highly crosslinked UHMWPE: A review. *Int. Orthop.*, 2011; **35**: 215–223.

845. Kurtz SM, Bracco P, Costa L. *Vitamin E blended UHMWPE biomaterials*. In: Kurtz SM, editor. *UHMWPE Biomaterials, Handbook*. 2nd ed. (Elsevier; Amsterdam, 2009). pp. 237–246.
846. Lerf R, Zurbrugg D, Delfosse D. Use of vitamin E to protect cross-linked UHMWPE from oxidation. *Biomaterials*, 2010; **31**: 3643–3648.
847. Bracco P, Brunella V, Zanetti M, Luda MP, Costa L. Stabilisation of ultra-high molecular weight polyethylene with vitamin E. *Polym. Degrad. Stab.*, 2007; **92**: 2155–2162.
848. Burton G, Ingold K. Autoxidation of biological molecules. 1. The antioxidant activity of vitamin E and related chain-breaking phenolic antioxidants *in vitro*. *J. Am. Chem. Soc.*, 1981; **103**: 6472–6477.
849. Kamal-Eldin A, Appelqvist L. The chemistry and antioxidant properties of tocopherols and tocotrienols. *Lipids*, 1996; **31**: 671–701.
850. Strobl GR, Hagedorn W. Raman spectroscopic method for determining the crystallinity of polyethylene. *J. Polym. Sci. Polym. Phys. Ed.*, 1978; **16**: 1181–1193.
851. Maxfield J, Stein RS, Chen MC. Polarized Raman studies of crystalline and amorphous orientation in polyethylene. *J. Polym. Sci. Polym. Phys. Ed.*, 1978; **16**: 37–48.
852. Nylor CC, Meier RJ, Kip BJ, Williams KPJ, Mason SM, Conroy N, Gerrard DL. Raman spectroscopy employed for the determination of the intermediate phase in polyethylene. *Macromolecules*, 1995; **28**: 2969–2978.
853. Oral E, Wannomae KK, Rowell SL, Muratoglu OK. Diffusion of vitamin E in ultra-high molecular weight polyethylene. *Biomaterials*, 2007; **28**: 5225–5237.
854. Wolf C, Maninger J, Lederer K, Fruhwirth-Smounig H, Gamse T, Marr R. Stabilisation of crosslinked ultra-high molecular weight polyethylene (UHMW-PE)-acetabular components with α -tocopherol. *J. Mater. Sci. Mater. Med.*, 2006; **17**: 1323–1331.
855. Li DS, Garmestani H, Davis SC, Moss LK, Siddiqi AK, Guthrie JB, Johansen N, Matriciano L. Wear resistance and texture evolution of ultra high molecular weight polyethylenes during uniaxial compression. *Ceramic Transactions*, 2009; **201**: 595–603.
856. Wang A, Sun DC, Yau S-S, Edwards B, Sokol M, Essner A, Polineni VK, Stark C, Dumbleton JH. Orientation softening in the deformation and wear of ultra-high molecular weight polyethylene. *Wear*, 1997; **203–204**: 230–241.
857. <http://www.biometeurope.fr/userfiles/files/Technologies/E1BiometLab-Paper.pdf>.

858. Birkinshaw C, Buggy M, Daly S, O'Neill M. The effect of gamma radiation on the physical structure and mechanical properties of ultrahigh molecular weight polyethylene. *J. Appl. Polym. Sci.*, 1989; **38**: 1967–1973.
859. Hozack WJ, Mesa JJ, Carey C, Rothman RH. Relationship between polyethylene wear, pelvic osteolysis and clinical symptomatology in patients with cementless acetabular components. *J. Arthroplasty*, 1996; **11**: 769–772.
860. Campbell P, Ma S, Yeom B. Isolation of predominantly submicron-sized UHMWPE wear particles from periprosthetic tissues. *J. Biomed. Mater. Res.*, 1995; **29**: 127–131.
861. Yeom B, Yu Y-J, McKellop HA, Salovey R. Profile of oxidation in irradiated polyethylene. *J. Polym. Sci.: Part A: Polym. Chem.*, 1998; **36**: 329–339.
862. Fagnano C, Rossi M, Porter RS, Ottani S. A study on solid-state drawn fibers of polyethylene by confocal Raman microspectrometry: Evaluation of the orientation profiles of amorphous and crystalline phases across the fiber section. *Polymer*, 2001; **42**: 5871–5883.
863. Ratner S, Moret PM, Wachtel E, Marom G. New Insights into lamellar twisting in transcrystalline polyethylene. *Macromol. Chem. Phys.*, 2005; **206**: 1183–1189.
864. Pigeon M, Prud'homme RE, Pézolet M. Characterization of molecular orientation in polyethylene by Raman spectroscopy. *Macromolecules*, 1991; **24**: 5687–5694.
865. Citra MJ, Chase DB, Ikeda RM, Gardner KH. Molecular orientation of high-density polyethylene fibers characterized by polarized Raman spectroscopy. *Macromolecules*, 1995; **28**: 4007–4012.
866. Nikolaeva GY, Semenova LE, Prokhorov KA, Gordeyev SA. Quantitative characterization of macromolecules orientation in polymers by micro Raman spectroscopy. *Laser Phys.*, 1997; **7(2)**: 403–415.
867. Bower DI. Investigation of molecular orientation distributions by polarized Raman scattering and polarized fluorescence. *J. Polym. Sci. Polym. Phys. Ed.*, 1972; **10**: 2135–2153.
868. Frisk S, Ikeda RM, Chase DB, Rabolt JF. Determination of the molecular orientation of poly(propylene terephthalate) fibers using polarized Raman spectroscopy: A comparison of methods. *Appl. Spectrosc.*, 2004; **58**: 279–286.
869. Minn M, Sinha SK. Molecular orientation, crystallinity, and topographical changes in sliding and their frictional effects for UHMWPE film. *Tribol. Lett.*, 2009; **34**: 133–140.

870. Heo SJ, Jang I, Barry PR, Phillpot SR, Perry SS, Sawyer WG, Sinnott SB. Effect of the sliding orientation on the tribological properties of polyethylene in molecular dynamics simulations. *J. Appl. Phys.*, 2008; **103**: 083502-1-6.
871. Sambasivan S, Fischer DA, Shen MC, Hsu SM. Molecular orientation of ultrahigh molecular weight polyethylene induced by various sliding motions. *J. Biomed. Mater. Res.*, 2004; **70**: 273-285.
872. Gulp MV. The use of rotation matrices in the mathematical description of molecular orientations in polymers. *Colloid Polym. Sci.*, 1995; **273**: 607-625.
873. Bower DI. Orientation distribution functions for biaxially oriented polymers. *Polymer*, 1982; **23**: 1251-1255.
874. McBrierty VJ. Use of rotation operators in the general description of polymer properties. *J. Chem. Phys.*, 1974; **61**: 872-882.
875. Mutter R, Stille W, Strobl G. Transition regions and surface melting in partially crystalline polyethylene: A Raman spectroscopic study. *J. Polym. Sci.: Part B: Polym. Phys.*, 1993; **31**: 99-105.
876. Bergstrom JS, Rimnac C, Kurtz SM. Molecular chain stretch is a multiaxial failure criterion for conventional and highly crosslinked UHMWPE. *J. Orthop. Res.*, 2005; **23**: 367-375.
877. Kurtz SM, Muhlstein C, Edidin AA. Surface morphology and wear mechanisms of four clinically relevant biomaterials after hip simulator testing. *J. Biomed. Mater. Res. A*, 2000; **52**: 447-459.
878. Bankston AB, Cates H, Ritter MA, Keating EM, Faris PM. Polyethylene wear in total hip arthroplasty. *Clin Orthop.*, 1995; **317**: 7-13.
879. Kurtz SM. Stress in UHMWPE tibial and patellar components for TKR. In: Kurtz SM editor. *The UHMWPE Handbook, Ultra-High-Molecular-Weight-Polyethylene in Total Joint Replacement*. (New York: Elsevier Academic Press; 2002); pp. 100-102.
880. Bartel DL, Rawlinson VL, Burstein AH, Ranawat CS, Flynn Jr WF. Stress in polyethylene components of contemporary total knee replacements. *Clin. Orthop.*, 1995; **380**: 76-82.
881. Olley RH, Hosier IL, Bassett DC, Smith NG. On morphology of consolidated UHMWPE resin in hip cups. *Biomaterials*, 1999; **20**: 2037-2046.
882. Li DS, Garmestani H, Alamo RG, Kalidindi SR. The role of crystallinity in the crystallographic texture evolution of polyethylenes during tensile deformation. *Polymer*, 2003; **44**: 5355-5367.

883. Song HH, Argon AS, Cohen RE. Morphology of highly textured high-density polyethylene. *Macromolecules*, 1990; **23**: 870–876.
884. Bartczak Z, Cohen RE, Argon AS. Evolution of the crystalline texture of high-density polyethylene during uniaxial compression. *Macromolecules*, 1992; **25**: 4692–4704.
885. Atkinson JR, Dowling JM, Cicek RZ. Materials for internal prostheses: The present position and possible future developments. *Biomaterials*, 1980; **1**: 89–96.
886. Edidin AA, Herr MP, Villarraga ML, Muth J, Yau SS, Kurtz SM. Accelerated ageing studies of UHMWPE. 1. Effect of resin, processing, and radiation environment on resistance to mechanical degradation. *J. Biomed. Mater. Res.*, 2002; **61**: 312–322.
887. Muratoglu OK, O'Connor DO, Bragdon CR, Delaney J, Jasty M, Harris WH, Merrill E, Venugopalan P. Gradient crosslinking of UHMWPE using irradiation in molten state for total joint arthroplasty. *Biomaterials*, 2002; **23**: 717–724.
888. Muratoglu OK, Bragdon CR, O'Connor DO, Jasty M, Harris WH, Gul R, McGarry F. Unified wear model for highly crosslinked ultra-high molecular weight polyethylenes (UHMWPE). *Biomaterials*, 1999; **20**: 1463–1470.
889. Hamadouche M, Boutin P, Daussange J, Bolander ME, Sedel L. Alumina-on-alumina total hip arthroplasty: A minimum 18.5-year follow-up study. *J. Bone Joint Surg. (Am.)*, 2002; **84**: 69–77.
890. Sedel L. Evolution of alumina-on-alumina implants: A review. *Clin. Orthop. Relat. Res.*, 2000; **379**: 48–54.
891. Huo MH, Martin RP, Zatorski LE, Keggi KJ. Total hip replacements using the ceramic Mittelmeier prosthesis. *Clin. Orthop.*, 1996; **332**: 143–150.
892. Peiro A, Pardo J, Navarrete R, Rodriguez-Alonso L, Martos F. Fracture of the ceramic head in total hip arthroplasty: Report of two cases. *J. Arthroplasty*, 1991; **6**: 371–374.
893. Cameron HU. Ceramic head implantation failures. *J. Arthroplasty*, 1991; **6**: 185–188.
894. Oonishi H. New design feature of high-quality alumina-alumina ceramic combination in total hip replacement. *Bioceramics*, 1992; **5**: 403–408.
895. Suzuki K, Matsubara M, Morita S, Muneta T, Shinomiya K. Fracture of a ceramic acetabular insert after ceramic-on-ceramic THA — a case report. *Acta Orthop. Scand.*, 2003; **74**: 101–103.

896. Amino H. Ceramic on ceramic total hip arthroplasty in Japan. (in Japanese) *Pharm. Medica*, 2002; **20**: 19–25.
897. Kitajima S, Hotokebuchi T. Ceramic on ceramic total hip arthroplasty. (in Japanese) *J. Joint Surg.*, 2003; **22**: 85–89.
898. Park YS, Hwang SK, Choy WS, Kim YS, Moon YW, Lim SJ. Ceramic failure after total hip arthroplasty with an alumina-on-alumina bearing. *J. Bone Joint Surg. (Am.)*, 2006; **88**: 780–787.
899. Krikler SJ. Fracture of a ceramic femoral head after a revision operation. A case report. *J. Bone Joint Surg. (Am.)*, 1997; **79A**: 118–121.
900. Maccauro G, Piconi C. Ceramic femoral head fracture in total hip replacement. *Int. Orthop.*, 2000; **24**: 239–243.
901. McLean CR, Dabis H, Mok D. Delayed fracture of the ceramic femoral head after trauma. *J. Arthroplasty*, 2002; **17**: 503–504.
902. Piconi C, Labanti M, Magnani G, Caporale M, Maccauro G, Magliocchetti G. Analysis of a failed alumina THR ball head. *Biomaterials*, 1999; **20**: 1637–1646.
903. Lewinnek GE, Lewis JL, Tarr R, Compere CL, Zimmerman JR. Dislocations after total hip-replacement arthroplasties. *J. Bone Joint Surg. (Am.)*, 1978; **60**: 217–220.
904. Messieh M, Mattingly DA, Turner RH, Scott R, Fox J, Slater J. Wear debris from bipolar femoral neck-cup impingement: A cause of femoral stem loosening. *J. Arthroplasty*, 1994; **9**: 89–93.
905. Kaku N, Tsumura H, Yorisu T. Qualitative analysis of polyethylene wear in a bipolar femoral prosthesis: A case report. *J. Orthop. Surg.*, 2001; **9**: 71–76.
906. Yamaguchi M, Akisue T, Bauer TW, Hashimoto Y. The spatial location of impingement in total hip arthroplasty. *J. Arthroplasty*, 2000; **15**: 305–313.
907. Coventry MB. Late dislocations in patients with Charnley total hip arthroplasty. *J. Bone Joint Surg. (Am.)*, 1985; **67**: 832–841.
908. McCollum DE, Gray WJ. Dislocation after total hip arthroplasty: Causes and prevention. *Clin. Orthop. Relat. Res.*, 1990; **261**: 159–170.
909. Woo RY, Morrey BF. Dislocations after total hip arthroplasty. *J. Bone Joint Surg. (Am.)*, 1982; **64**: 1295–1306.
910. Dalla Pria P, Zagra L, Esopi P, Masoni D. Breakage and noises in ceramic on ceramic couplings. *Eur. Orthop. Traumatol.*, 2010; **1**: 53–59.

911. Sariali E, Stewart T, Mamoudy P, Jin Z, Fisher J. Undetected fracture of an alumina ceramic on ceramic hip prosthesis. *J. Arthroplasty*. 2009; **25**: 658.E1–E5.
912. Willmann G. Retrieved ceramic wear couple: unexpected findings. In: *Bioceramics in Joint Arthroplasty: Proceedings of the 6th BIOLOX®Symposium*. (Toni A, Willmann G, eds). (Georg Thieme Verlag, Stuttgart, Germany, 2001) pp. 63–65.
913. Hasegawa M, Sudo A, Uchida A. Cobalt-chromium head wear following revision hip arthroplasty performed after ceramic fracture — a case report. *Acta Orthop.*, 2006; **77**: 833–835.
914. Rudas M, Qasim T, Bush MB, Lawn BR. Failure of curved brittle layer systems from radial cracking in concentrated surface loading. *J. Mater. Res.*, 2005; **20**: 2812–2819.
915. Espinosa HD, Zavattieri PD, Dwivedi SK. A finite deformation continuum/discrete model for the description of fragmentation and damage in brittle materials. *J. Mech. Phys. Solids*, 1998; **46**: 1909–1942.
916. Zavattieri PD, Espinosa HD. Grain level analysis of crack initiation and propagation in brittle materials. *Acta Mater.*, 2001; **49**: 4291–4311.
917. Uribe J, Hausselle J, Geringer J, Forest B. Finite element modeling of shock-induced damages on ceramic hip prostheses. *ISRN Mater. Sci.*, 2011; **121**, 486–1–14.
918. Evans AG, Crumley GB, Demaray RE. On the mechanical behavior of brittle coatings and layers. *Oxidation Met.*, 1983; **20**: 193–216.
919. Teixeira V. Residual stress and cracking in thin PVD coatings. *Vacuum*, 2002; **64**: 393–399.
920. Jha SK, Sohn YH, Sastri S, Gunda N, Haynes JA. Al-O-N based duplex coating system for improved oxidation resistance of superalloys and NiCrAlY coatings. *Surf. Coatings Tech.*, 2004; **183**: 224–232.
921. Gu T, Xiong W, Ning C, Zhang J. Residual stresses in microarc oxidation ceramic coatings on biocompatible AZ31 magnesium alloys. *J. Mater. Eng. Performance*, 2012; **21**: 1085–1090.
922. Pang X, Gao K, Yang H, Qiao L, Wang Y, Volinsky AA. Interfacial microstructure of chromium oxide coatings. *Adv. Eng. Mater.*, 2007; **9**: 594–599.
923. Ohno K, Uchiyama H, Kozuka H. Understanding of the development of the in-plane residual stress in sol–gel-derived metal oxide thin films. *J. Appl. Phys.*, 2012; **111**: 014910–1–9.
924. Sue JA. X-ray elastic constants and residual stress of textured titanium nitride coating. *Surf. Coatings Tech.*, 1992; **54–55**: 154–159.

925. Leoni M, Scardi P, Rossi S, Fedrizzi L, Massiani Y. (Ti,Cr)N and Ti/TiN PVD coatings on 304 stainless steel substrates: Texture and residual stress. *Thin Solid Films* 1999; **345**: 263–269.
926. Shieu FS, Cheng LH, Shiao MH, Lin SH. Effects of Ti interlayer on the microstructure of ion-plated TiN coatings on AISI 304 stainless steel. *Thin Solid Films*, 1997; **311**: 138–145.
927. Agarwal A, Dahotre NB, Sudarshan TS. Evolution of interface in pulsed electrode deposited titanium diboride on copper and steel. *J. Surf. Eng.*, 1999; **15**: 27–32.
928. Tomsia AP, Launey ME, Lee JS, Mankani MH, Wegst UGK, Saiz E. Nanotechnology approaches for better dental implants. *Int. J. Oral Maxillofac. Implants*, 2011; **26** (Suppl.): 25–49.
929. Moon H, Lange FF. Strengthening with a uniform compressive layer produced by a dip-coating: A study of processing variables. *J. Am. Ceram. Soc.*, 2010; **93**: 1264–1269.
930. Fu Y, Loh NL, Batchelor AW, Liu D, Zhu X, He J, Xu K. Improvement in fretting wear and fatigue resistance of Ti–6Al–4V by application of several surface treatments and coatings. *Surf. Coatings Tech.*, 1998; **106**: 193–197.
931. Mao WG, Dai CY, Zhou YC, Liu QX. An experimental investigation on thermo-mechanical buckling delamination failure characteristic of air plasma sprayed thermal barrier coatings. *Surf. Coatings Tech.*, 2007; **201**: 6217–6227.
932. Chen J, Bull SJ. Approaches to investigate delamination and interfacial toughness in coated systems: An overview. *J. Phys. D: Appl. Phys.*, 2011; **44**: 34001-1–35.
933. Rühle M, Evans AG. Structure and chemistry of metal/ceramic interfaces. *Mater. Sci. Eng. A*, 1989; **A107**: 187–197.
934. Beltran JI, Gallego S, Cerda J, Munoz MC. Oxygen vacancies at Ni/c-ZrO₂ interfaces. *J. Eur. Ceram. Soc.*, 2003; **23**: 2737–2740.
935. Parise M, Touet I, Sicardy O. Oxidation of zirconium alloys. Crystallographic texture of zirconia: Interpretation and mechanical consequences. *Textures Microstr.*, 1998; **30**: 247–263.
936. Hobbs LW, Benezra Rosen V, Mangin SP, Treska M. Oxidation microstructures and interfaces in the oxidized zirconium knee. *Int. J. App. Ceram. Technol.*, 2005; **2**: 221–246.
937. Ries MD, Salehi A, Widding K, Hunter G. Polyethylene wear performance of oxidized zirconium and cobalt-chromium knee components

- under abrasive conditions. *J. Bone Joint Surg. (Am.)*, 2002; **84A** (Suppl. 2): 129–135.
938. Davidson JA, Asgian CM, Mishra AK, Kovaks P. Zirconia (ZrO_2)-coated zirconium-2.5Nb alloy for prosthetic knee bearing applications. *Bioceramics*, 1992; **5**: 389–401.
939. Mishra AK, Davidson JA. Zirconia/zirconium: A new abrasion resistant material for orthopaedic applications. *Mater. Technol.*, 1993; **8**: 16–21.
940. Laskin RS. An oxidized Zr ceramic surfaced femoral component for total knee arthroplasty. *Clin. Orthop. Relat. Res.*, 2003; **416**: 191–196.
941. Patel AM, Spector M. Oxidized zirconia for hemiarthroplasty: An *In vitro* assessment. *Biomaterials*, 1995; **8**: 169–175.
942. White SE, Whiteside LA, McCarthy DS, Anthony M, Poggie RA. Simulated wear with cobalt-chromium and oxidized zirconium knee femoral component. *Clin. Orthop.*, 1994; **309**: 176–184.
943. Laskin RS, Davis J. Total knee replacement using the Genesis II prosthesis: A 5-year follow-up study of the first 100 consecutive cases. *Knee*, 2005; **12**: 163–167.
944. National Joint Registry of England and Wales: NJR Prostheses used 2010; p. 84. Available from: URL: www.njcentre.org.uk
945. National Joint Registry of England and Wales: 8th Annual Report 2011; p. 160. Available from: URL: www.njcentre.org.uk
946. Australian Orthopaedic Association National Joint Replacement Registry: Annual Report 2011, Hip and Knee Arthroplasty; p. 65. Available from: URL: www.dmac.adelaide.edu.au/aoanjrr/index.jsp.
947. Hunter G, Long M. Abrasive wear of oxidized Zr-2.5Nb, CoCrMo and Ti-6Al-4V against bone cement. In: *Proceedings of the 6th World Biomaterials Congress*. (Trans. Society for Biomaterials; Minneapolis, MN, 2000). p. 835.
948. Gotman I, Gutmanas EY, Hunter G. Wear-resistant ceramic films and coatings. *Comprehensive Biomater.*, 2011; **1**: 127–155.
949. Kop AM, Whitewood C, Johnston DJL. Damage of Oxinium femoral heads subsequent to hip arthroplasty dislocation. Three retrieval case studies. *J. Arthroplasty*, 2007; **22**: 775–779.
950. McCalden RW, Charron KD, Davidson RD, Teeter MG, Holdsworth DW. Damage of an Oxinium femoral head and polyethylene liner following “routine” total hip replacement. *J. Bone Joint Surg. (Br.)*, 2011; **93B**: 409–413.

951. Godlewski J, Gros JP, Lambertin M, Wadier JF, Weidinger H. Raman spectroscopy study of the tetragonal-to-monoclinic transition in zirconium oxide scales and determination of overall oxygen diffusion by nuclear microanalysis of O¹⁸. *ASTM Special Technical Publications*, 1991; **1132**: 416–436.
952. Cox B, Wu C. Dissolution of zirconium oxide films in 300°C LiOH. *J. Nucl. Mater.*, 1993; **199**: 272–284.
953. Barberis P, Merle-Mejean T, Quintard P. On Raman spectroscopy of zirconium oxide films. *J. Nucl. Mater.*, 1997; **246**: 232–243.
954. Galetz MC, Fleischmann EW, Konrad CH, Schuetz A, Glatzel U. Abrasion resistance of oxidized zirconium in comparison with CoCrMo and titanium nitride coatings for artificial knee joints. *J. Biomed. Mater. Res. B*, 2010; **93B**: 244–251.
955. Guo X. Effect of Nb₂O₅ on the space charge conduction of Y₂O₃ stabilized ZrO₂. *Solid State Ionics*, 1997; **99**: 137–142.
956. Vidyavathy SM, Kamaraj V. Microwave sintering of niobium co-doped yttria stabilized zirconia. *Mod. Appl. Sci.*, 2009; **3**: 102–105.
957. Bartolomé JH, Gutierrez-Gonzales CF, Pecharroman C, Moya JS. Synergetic toughening mechanism in 3Y-TZP/Nb composites. *Acta Mater.*, 2007; **55**: 5924–5933.
958. Kim DJ. Effect of Ta₂O₅, Nb₂O₅, and HfO₂ alloying on the transformability of Y₂O₃-stabilized tetragonal ZrO₂. *J. Am. Ceram. Soc.*, 1990; **73**: 115–120.
959. Wachsman ED, Jiang N, Frank CW, Mason DM, Stevenson DA. Spectroscopic investigation of oxygen vacancies in solid oxide electrolytes. *Appl. Phys. A*, 1990; **50**: 545–549.
960. Matsui K, Yoshida H, Ikuhara Y. Phase-transformation and grain-growth kinetics in yttria-stabilized tetragonal zirconia polycrystal doped with a small amount of alumina. *J. Eur. Ceram. Soc.*, 2010; **30**: 1679–1690.
961. Alonso PJ, Alcalá R, Casas-Gonzales J, Cases R, Orera VM. Spectroscopy of chromium (III) in yttrium-stabilized ZrO₂. *J. Phys. Chem. Solids*, 1989; **50**: 1185–1191.
962. Chang S-M, Doong R-A. The effect of chemical states of dopants on the microstructures and band gaps of metal-doped ZrO₂ thin films at different temperatures. *J. Phys. Chem. B*, 2004; **108**: 18098–18103.
963. Berry FJ, Loretto MH, Smith MR. Iron-zirconium oxide: An investigation of structural transformations by X-ray diffraction,

- electron diffraction, and iron-57 Mössbauer spectroscopy. *J. Solid State Chem.*, 1989; **83**: 91–99.
964. Nakajima H, Ishihara H, Shen Q, Toyoda T, Itoh K, Kaneko H, Tamaura Y. Effect of Fe doping on photoluminescence of yttria-stabilized zirconia. *J. Alloys Comp.*, 2007; **441**: 255–258.
 965. Foster AS, Sulimov VB, Lopez Gejo F, Shluger AL, Nieminen RM. Structure and electrical levels of point defects in monoclinic zirconia. *Phys. Rev. B*, 2001; **64**: 224108-1–10.
 966. Emeline A, Kataeva GV, Litke AS, Rudakova AV, Ryabchuk VK, Serpone N. Spectroscopic and photoluminescence studies of a wide-band gap insulating material: Powdered and colloidal ZrO_2 sols. *Langmuir*, 1998; **14**: 5011–5022.
 967. Petrik NG, Alexandrov AB, Vall AI. Interfacial energy transfer during gamma radiolysis of water on the surface of ZrO_2 and some other oxides. *J. Phys. Chem. B*, 2001; **105**: 5935–5944.
 968. Foster AS, Shluger AL, Nieminen RM. Mechanisms of interstitial oxygen diffusion in hafnia. *Phys. Rev. Lett.*, 2002; **89**: 225901-1–4.
 969. Howard CJ, Hill RJ, Reichert BE. Structures of the ZrO_2 polymorphs at room temperature by high-resolution neutron powder diffraction. *Acta Cryst. B*, 1988; **B44**: 116–120.
 970. Zacate MO, Minervini L, Bradfield DJ, Grimes RW, Sickafus KE. Defect cluster formation in M_2O_3 -doped cubic ZrO_2 . *Solid State Ionics* 2000; **128**: 243–254.
 971. Minervini L, Zacate MO, Grimes RW. Defect cluster formation in M_2O_3 -doped CeO_2 . *Solid State Ionics*, 1999; **116**: 339–349.
 972. Stefanovich EV, Shluger AL, Catlow CRA. Theoretical study of the stabilization of cubic-phase ZrO_2 by impurities. *Phys. Rev. B*, 1994; **49**: 560–571.
 973. Konttinen YT, Takagi M, Mandelin J, Lassus J, Salo J, Ainola M, Li T-F, Virtanen I, Lilieström M, Sakai H, Kobayashi Y, Sorsa T, Lappalainen R, Demulter A, Santavirta S. Acid attack and cathepsin K in bone resorption around total hip replacement prosthesis. *J. Bone Miner. Res.*, 2001; **16**: 1780–1786.
 974. Li CW, McKerns MM, Fultz B. A Raman spectrometry study of phonon anharmonicity of zirconia at elevated temperatures. *J. Am. Ceram. Soc.*, 2011; **94**: 224–229.
 975. McBride JR, Hass KC, Poindexter BD, Weber WH. Raman and x-ray studies of $\text{Ce}_{1-x}\text{RE}_x\text{O}_{2-y}$, where $\text{RE}=\text{La, Pr, Nd, Eu, Gd, and Tb}$. *J. Appl. Phys.*, 1994; **76**: 2435–2441.

976. Namavar F, Cheung CL, Sabirianov RF, Mei WN, Zeng XC, Wang G, Haider H, Garvin KL. Lotus effect in engineered zirconia. *Nano Lett.*, 2008; **8**: 988–996.
977. Namavar F, Wang G, Cheung CL, Sabirianov RF, Zeng XC, Mei WN, Bai J, Brewer JR, Haider H, Garvin KL. Thermal stability of nanostructurally stabilized zirconium oxide. *Nanotechnology*, 2007; **18**: 415702-1–9.
978. Liu D, Lord O, Flewitt PE. Calibration of Raman spectroscopy in the stress measurement of air-plasma-sprayed yttria-stabilized zirconia. *Appl. Spectrosc.*, 2012; **66**: 1204–1209.
979. Bouvier P, Lucazeau G. Raman spectra and vibrational analysis of nanometric tetragonal zirconia under high pressure. *J. Phys. Chem. Solids*, 2000; **61**: 569–578.
980. Balzaretti NM, da Jornada JAH. Pressure dependence of the refractive index of monoclinic and yttria-stabilized cubic zirconia. *Phys. Rev. B*, 1995; **52**: 9266–9269.
981. Tanaka K, Ishihara K, Akiniwa Y, Ohta H. Residual stress of aluminium thin films measured by X-ray and curvature methods. *Mater. Sci. Res. Int.*, 1996; **2**: 153–159.
982. Taylor CA, Wayne MF, Chiu WKS. Residual stress measurement in thin carbon films by Raman spectroscopy and nanoindentation. *Thin Solid Films*, 2003; **429**: 190–200.
983. Im SH, Huang R. Wrinkle patterns of anisotropic crystal films on viscoelastic substrates. *J. Mech. Phys. Solids*, 2008; **56**: 3315–3330.
984. Kharton VV, Yaremchenko AA, Patrakeeve MV, Naumovich EN, Marques FMB. Thermal and chemical induced expansion of $\text{La}_{0.3}\text{Sr}_{0.7}(\text{Fe,Ga})\text{O}_{3-\delta}$ ceramics. *J. Eur. Ceram. Soc.*, 2003; **23**: 1417–1426.
985. Hayashi H, Watanabe M, Ohuchida M, Inaba H, Hiei Y, Yamamoto T, Mori M. Thermal expansion of $\text{La}_{1-x}\text{Sr}_x\text{CrO}_{3-\delta}$. *Solid State Ionics*, 2001; **144**: 301–313.
986. Evans AG, Hutchinson JW. On the mechanics of delamination and spalling in compressed films. *Int. J. Solids Structures*, 1984; **20**: 455–466.
987. Evans AG, Mumm DR, Hutchinson JW, Meier GH, Pettit FS. Mechanisms controlling the durability of thermal barrier coatings. *Progress Mater. Sci.*, 2001; **46**: 505–553.
988. Hutchinson JW, Suo Z. Mixed mode cracking in layered materials. *Adv. Appl. Mech.*, 1991; **29**: 63–191.
989. Drory MD, Hutchinson JW. Measurement of the adhesion of a brittle film on a ductile substrate by indentation. *Proc. R. Soc. London A*, 1996; **452**: 2319–2341.

990. Pezzotti G, Okai K, Zhu W. Stress tensor dependence of the polarized Raman spectrum of tetragonal barium titanate. *J. Appl. Phys.*, 2012; **111**: 013504-1-16.
991. Miyatake T, Pezzotti G. Validating Raman spectroscopic calibrations of phonon deformation potentials in silicon single crystal: A comparison between ball-on-ring and micro-indentation methods. *J. Appl. Phys.*, 2011; **110**: 093511-1-13.
992. Zhu W, Wan K, Pezzotti G. Methods of piezo-spectroscopic calibration on thin film materials: II. Tensile stress field at indentation crack tip. *Meas. Sci. Technol.*, 2006; **17**: 191-198.
993. Fett T. *Computation of the crack opening displacements for Vickers indentation cracks*. Report FZKA 6757; Forschungszentrum Karlsruhe, Karlsruhe, Germany, 2002.
994. Gruniger MF, Lawn BR, Farabaugh EN, Wachtman JB. Measurement of residual stresses in coatings on brittle substrates by indentation fracture. *J. Am. Ceram. Soc.*, 1987; **70**: 344-348.
995. Miller KJ, Kfoury AP. An elastic-plastic finite element analysis of crack tip fields under biaxial loading conditions. *Int. J. Fracture*, 1974; **10**: 393-404.
996. Haerle AG, Cannon WR, Denda M. Direct measurement of crack tip stresses. *J. Am. Ceram. Soc.*, 1991; **74**: 2897-2901.
997. Denda M, Mattingly E. The singular crack element for 2-d boundary element analysis of multiple straight cracks in the general anisotropic solids. *Electronic J. Boundary Elements*, 2003; **1**: 404-417.
998. Puchi-Cabrera ES. A new model for the computation of the composite hardness of coated systems. *Surf. Coat. Technol.*, 2002; **160**: 177-186.
999. Malzbender J, den Toonder MJ, Balkenende AR, de With G. Measuring mechanical properties of coatings: A methodology applied to nano-particle-filled sol-gel coatings on glass. *Mater. Sci. Eng.*, 2002; **R36**: 47-103.
1000. Demidova NV, Wu XJ, Liu R. A fracture toughness model for brittle coating on ductile substrate under indentation loading. *Eng. Fracture Mech.*, 2012; **82**: 17-28.
1001. Ichimura H, Rodriguez FM, Rodrigo A. The composite and film hardness of TiN coatings prepared by cathodic arc evaporation. *Surf. Coat. Technol.*, 2000; **127**: 138-143.
1002. Borodachev N. An elliptical crack under point forces applied to its surface. *J. Appl. Math. Mech.*, 1998; **64**: 477-483.

1003. Light TR, Keggi KJ. Anterior approach to hip arthroplasty. *Clin. Orthop. Relat. Res.*, 1980; **152**: 255–260.
1004. Walker TJ. Characterization of the fracture toughness of zircaloy. *Nucl. Technol.* 1972; **16**: 509–520.
1005. Coleman CE, Cheadle BA, Causey AR, Chow PEK, Davies PH, McManus MD, Rodgers DK, Sagat S, van Drunen G. Evaluation of Zircaloy-2 pressure tubes from NPD. Solid State Ionics ASTM Special Technical Publications, **1023**, 1989; pp. 35–49.
1006. Wallace AC, Gordon KS, Lepik OE. Effects of hydride morphology on Zr-2.5Nb fracture toughness. ASTM Special Technical Publications, **1023**, 1989; pp. 66–88.
1007. Roy H, Parida N, Sivaprasad S, Tarafder S, Rayc KK. Acoustic emissions during fracture toughness tests of steels exhibiting varying ductility. *Mater. Sci. Eng.*, 2008; **A486**: 562–571.
1008. Bhowmick S, Kale AN, Jayaram V, Biswas SK. Contact damage in TiN coatings on steel. *Thin Solid Films*, 2003; **436**: 250–258.
1009. Zhang S. TiN coating of tool steels: A review. *J. Mater. Processing Technol.*, 1993; **39**: 165–177.
1010. Evangelista GT, Fulkerson E, Kummer F, DiCesare PD. Surface damage to an oxinium femoral head prosthesis after dislocation. *J. Bone Joint Surg.*, 2007; **89**: 535–537.
1011. Pawar V, Weaver C, Jani S. Physical characterization of a new composition of oxidized zirconium-2.5 wt% niobium produced using a two step process for biomedical applications. *Appl. Surf. Sci.*, 2011; **257**: 6118–6124.
1012. Jerosch J, Theising C, Fadel ME. Antero-lateral minimal invasive (ALMI) approach for total hip arthroplasty technique and early results. *Arch. Orthop. Trauma Surg.*, 2006; **126**: 164–173.
1013. Light TR, Keggi KJ. Anterior approach to hip arthroplasty. *Clin. Orthop. Relat. Res.*, 1980; **152**: 255–260.
1014. Rittmeister M, Peters A. A posterior mini-incision for total hip arthroplasty — results of 76 consecutive cases. *Z. Orthop. Ihre Grenzgeb.*, 2005; **143**: 403–411.
1015. Keggi KJ, Huo MH, Zatorski LE. Anterior approach to total hip replacement: Surgical technique and clinical results of our first one thousand cases using non-cemented prostheses. *Yale J. Biol. Med.*, 1993; **66**: 243–256.
1016. Kennon RE, Keggi JM, Wetmore RS, Zatorski LE, Huo MH, Keggi KJ. Total hip arthroplasty through a minimally invasive anterior

- surgical approach. *J. Bone Joint Surg. (Am.)*, 2003; **85** (Suppl. 4): 39–48.
1017. Krismer M, Nogler M, Rachbauer F. Direct, anterior, single incision approach. In: *Minimal Invasive Joint Arthroplasty*. Hozak WJ, Krismer M, Nogler M, Bonutti PM, Rachbauer F, Schaffer JL, Donnelly WJ (Eds.): (Springer, Heidelberg, NewYork, Tokyo, 2004). pp. 4–10.
 1018. Oinuma K, Eingartner C, Saito Y, Shiratsuchi H. Total hip arthroplasty by direct anterior approach. *Operat. Orthop. Traumatol.*, 2007; **19**: 310–326.
 1019. Nogler M. Navigated minimal invasive total hip arthroplasty. *Surg., Technol. Int.*, 2004; **12**: 259–262.
 1020. Lucas DH, Scott RD. The Ranawat sign. A specific maneuver to assess component positioning in total hip arthroplasty. *J. Orthop. Tech.*, 1994; **2**: 59–61.
 1021. White TO, Dougall TW. Arthroplasty of the hip: Leg length is not important. *J. Bone Joint Surg. (Br.)*, 2002; **84**: 335–338.
 1022. Honl M, Schwieger K, Salineros M, Jacobs J, Morlock M, Wimmer M. Orientation of the acetabular component. A comparison of five navigation systems with conventional surgical techniques. *J. Bone Joint Surg. (Br.)*, 2006; **88**: 1401–1405.
 1023. Noble PC, Sugano N, Johnston JD, Thompson MT, Conditt MA, Engh A, Mathis KB. Computer simulation: How can it help the surgeon optimize implant position? *Clin. Orthop. Relat. Res.*, 2003; **417**: 242–252.
 1024. Lazovic D, Kaib N. Results with navigated Bicontact total hip arthroplasty. *Orthopedics*, 2005; **28** (Suppl. 10): 1227–1233.
 1025. Parratte S, Argenson JN. Validation and usefulness of a computer assisted cup positioning system in THA. A prospective, randomized, controlled study. *J. Bone Joint Surg. (Am.)*, 2007; **89**: 494–499.
 1026. Dorr LD. *Hip arthroplasty: minimally invasive techniques and computer navigation*. Saunders Elsevier, Philadelphia, 2006.
 1027. Haaker RG, Stockheim M, Kamp M, Proff G, Breitenfelder J, Ottersbach A. Computer-assisted navigation increases precision of component placement in total knee arthroplasty. *Clin. Orthop. Relat. Res.*, 2005; **433**: 152–159.
 1028. Stulberg SD, Loan P, Sarin V. Computer-assisted navigation in total knee replacement: Results of an initial experience in thirty-five patients. *J. Bone Joint Surg.*, 2002; **84**: S90–S98.

1029. Pitto RP, Graydon AJ, Bradley L, Malak SF, Walker CG, Anderson IA. Accuracy of a computer-assisted navigation system for total knee replacement. *J. Bone Joint Surg. (Br.)*, 2006; **88**: 601–605.
1030. Shimmin AJ, Back D. Femoral neck fractures following Birmingham hip resurfacing: A national review of 50 cases. *J. Bone Joint Surg. (Br.)*, 2005; **87**: 463–464.
1031. Grammatopolous G, Pandit H, Kwon Y-M, Gundle R, McLardy-Smith P, Beard DJ, Murray DW, Gill HS. Hip resurfacings revised for inflammatory pseudotumour have a poor outcome. *J. Bone Joint Surg. (Br.)*, 2009; **91**: 1019–1024.
1032. Grigoris P, Roberts P, Panousis K, Jin Z. Hip resurfacing arthroplasty: The evolution of contemporary designs. *Proc. Inst. Mech. Eng. H.*, 2006; **220**: 95–105.
1033. Goebel S, Blanke M, Hendrich C. Surface replacement of the hip: Contra. In: *Proceedings of the 9th BIOLOX[®] Symposium*. (Lazennec JY, Dietrich M, eds). (Steinkopff Verlag, Darmstadt, Germany, 2004). pp. 119–126.
1034. Clarke MT, Lee PTH, Arora A, Villar RN. Levels of metal ions after small- and large-diameter metal-on-metal hip arthroplasty. *J. Bone Joint Surg. (Br.)* 2003; **85**: 913–917.
1035. Jacobs JJ, Skipor AK, Doorn PF, Campbell PA, Schmalzried TP, Black J, Amstutz HC. Cobalt and chromium concentrations in patients with metal on metal total hip replacement. *Clin. Orthop. Relat. Res.*, 1996; **329**: S256–S263.
1036. Jacobs JJ, Skipor AK, Patterson LM, Hallab NJ, Paprosky WG, Black J, Galante JO. Metal release in patients who have had a primary total hip arthroplasty. A prospective, controlled, longitudinal study. *J. Bone Joint Surg. (Am.)*, 1998; **80**: 1447–1458.
1037. Savarino L, Granchi D, Ciapetti G, Cenni E, Greco M, Rotini R, Veronesi CA, Baldini N, Giunti A. Ion release in stable hip arthroplasties using metal-on-metal articulating surfaces: A comparison between short- and medium-term results. *J. Biomed. Mater. Res.*, 2003; **66A**: 450–456.
1038. Savarino L, Greco M, Cenni E, Cavasinni L, Rotini R, Baldini N, Giunti A. Differences in ion release after ceramic-on-ceramic and metal-on-metal total hip replacement, medium-term follow-up. *J. Bone Joint Surg. (Br.)*, 2006; **88**: 472–476.
1039. Daniel J, Ziaee H, Pradhan C, Pynsent PB, McMinn DJ. Blood and urine metal ion levels in young and active patients after Birmingham

- hip resurfacing arthroplasty: Four-year results of a prospective longitudinal study. *J. Bone Joint Surg. (Br.)*, 2007; **89**: 169–173.
1040. Mont MA, Schmalzried TP. Modern metal-on-metal hip resurfacing: Important observations from the first ten years. *J. Bone Joint Surg. (Am.)*, 2008; **90**: 3–11.
 1041. Hart AJ, Skinner JA, Winship P, Faria N, Kulinskaya E, Webster D, Muirhead-Allwood S, Aldam CH, Anwar H, Powell JJ. Circulating levels of cobalt and chromium from metal-on-metal hip replacement are associated with CDT-cell lymphopenia. *J. Bone Joint Surg. (Br.)*, 2009; **91**: 835–842.
 1042. Willert HG, Buchhorn GH, Fayyazi A, Flury R, Windler M, Koester G, Lohmann CH. Metal-on-metal bearings and hyper-sensitivity in patients with artificial hip joints. A clinical and histomorphological study. *J. Bone Joint Surg. (Am.)*, 2005; **87**: 28–36.
 1043. Available from: URL: www.tga.gov.au/newsroom/btn-dupuy-recall.htm.
 1044. Griss P, Werner E. Alumina ceramic, bioglass and silicon nitride. A comparative biocompatibility study. In: *Mechanical Properties of Biomaterials*. (Hastings GW, Williams DE, eds) (John Wiley & Sons Ltd., London, 1980). pp. 217–225.
 1045. Willmann G. Survival rate and reliability of ceramic femoral heads for total hip arthroplasty. *Mat.-wiss. U. Werkstofftech.*, 1998; **29**: 595–604.
 1046. Takami Y, Nakazawa T, Makinouchi K, Glueck J, Nose Y. Biocompatibility of alumina ceramic and polyethylene as materials for pivot bearings of a centrifugal blood pump. *J. Biomed. Mater. Res.*, 1997; **36**: 381–386.
 1047. Dorlot JM. Long-term effects of alumina components in total hip prostheses. *Clin. Orthop.*, 1992; **282**: 47–52.
 1048. Jazrawi LM, Kummer FJ, DiCesare PE. Alternative bearing surfaces for total joint arthroplasty. *J. Am. Acad. Orthop. Surg.*, 1998; **6**: 198–203.
 1049. Granchi D, Savarino L, Ciapetti G, Cenni E, Rotini R, Mieti M, Baldini N, Giunti A. Immunological changes in patients with total joint replacement following idiopathic osteoarthritis of the hip. *J. Bone Joint Surg. (Br.)*, 2003; **85**: 758–764.
 1050. Bizot P, Nizard R, Hamadouche M, Hannouche D, Sedel L. Prevention of wear and osteolysis: Alumina-on-alumina bearing. *Clin. Orthop.*, 2001; **393**: 85–93.

1051. Shimmin A, Beaulé PE, Campbell P. Metal-on-metal hip resurfacing arthroplasty. *J. Bone Joint Surg. (Am.)*, 2008; **90**: 637–654.
1052. Ong KL, Manley MT, Kurtz SM. Have contemporary hip resurfacing designs reached maturity? A review. *J. Bone Joint Surg. (Am.)*, 2008; **90**: 81–88.
1053. Zhang W, Titze M, Cappi B, Wirtz DC, Telle R, Fischer H. Improved mechanical long-term reliability of hip resurfacing prostheses by using silicon nitride. *J. Mater. Sci. Mater. Med.*, 2010; **21**: 3049–3057.
1054. Cappi B, Neuss S, Salber J, Telle R, Knuechel R, Fischer H. Cytocompatibility of high strength non-oxide ceramics. *J. Biomed. Mater. Res. A*, 2009; **93**: 67–76.
1055. Becher PF, Sun EY, Plucknett KP, Alexander KB, Hsueh C-H, Lin H-T, Waters SB, Westmoreland CG, Kang E-S, Hirao K, Brito ME. Microstructural design of silicon nitride with improved fracture toughness: 1. Effects of grain shape and size. *J. Am. Ceram. Soc.*, 1998; **81**: 2821–2830.
1056. Sun EY, Becher PF, Plucknett KP, Hsueh C-H, Alexander KB, Waters SB, Hirao K, Brito ME. Microstructural design of silicon nitride with improved fracture toughness: 2. Effects of yttrium and alumina additives. *J. Am. Ceram. Soc.*, 1998; **81**: 2831–2840.
1057. Padture N. *In situ*-toughened silicon carbide. *J. Am. Ceram. Soc.*, 1994; **77**: 519–523.
1058. Gilbert CJ, Dauskardt RH, Ritchie RO. Behaviour of cyclic fatigue cracks in monolithic silicon nitride. *J. Am. Ceram. Soc.*, 1995; **78**: 2291–2298.
1059. Lancaster JK. A review of the influence of environmental humidity and water on friction, lubrication and wear. *Tribol. Int.*, 1990; **23**: 371–389.
1060. Tanaka I, Pezzotti G. Evaluation of slow crack growth resistance in ceramics for high-temperature applications. *J. Am. Ceram. Soc.*, 1992; **75**: 772–777.
1061. Munz D, Fett T. Ceramics: *Mechanical Properties, Failure Behaviour, Materials Selection* (1st ed.). Springer: Berlin (1999).
1062. Takahashi Y, Zhu W, Sugano N, Pezzotti G. On the role of oxygen vacancies, aliovalent ions and lattice strain in the *in vivo* wear behavior of alumina hip joints. *J. Mech. Behav. Biomed. Mater.*, 2011; **4**: 993–1003.

1063. Fischer TE, Tomizawa H. Interaction of tribochemistry and microfracture in the friction and wear of silicon nitride. *Wear*, 1985; **105**: 29–45.
1064. Dong X, Jahanmir S. Wear transition diagram for silicon nitride. *Wear*, 1993; **165**: 169–180.
1065. Dong X, Jahanmir S, Ives LK. Wear transition diagram for silicon carbide. *Tribol. Int.*, 1995; **28**: 559–572.
1066. Wilson K, Roques A, Dickinson A, Mathias R, Taylor A, Holland J. Initial fixation of a pre-assembled cup system. In: *Proceedings of the 13th Biolox Symposium 2009, Bioceramics and Alternative Bearings in Joint Arthroplasty*, Vol. 13. (Cobb JP, ed) (Springer; Berlin, 2010).
1067. Pandorf T. Delta motion monoblock cup system: What can we expect? *J. Bone Joint Surg. (Br.)*, 2010; **92-B** (Suppl. I): 98.
1068. *National Joint Registry of England and Wales*: NJR Prostheses used 2010; p. 8. Available from: URL: www.njcentre.org.uk.
1069. Oral E, Rowell SL, Muratoglu OK. The effect of alpha-tocopherol on the oxidation and free radical decay in irradiated UHMWPE. *Biomaterials*, 2006; **27**: 5580–5587.
1070. Kurtz SM, Dumbleton J, Siskey RS, Wang A, Manley M. Trace concentrations of vitamin E protect radiation crosslinked UHMWPE from oxidative degradation. *J. Biomed. Mater. Res. A*, 2009; **90**: 549–563.
1071. Wang AG, Yau SS, Essner A, Herrera L, Manley M, Dumbleton J. A highly crosslinked UHMWPE for CR and PS total knee arthroplasties. *J. Arthroplasty*, 2008; **23**: 559–566.
1072. Kurtz SM, Mazzucco D, Rimnac CM, Schroeder D. Anisotropy and oxidative resistance of highly crosslinked UHMWPE after deformation processing by solid-state ram extrusion. *Biomaterials*, 2006; **27**: 24–34.
1073. Herrera L, Essner A, Loving L, Wang A. Hip simulator evaluation of the effect of liner thickness on the wear of sequentially crosslinked acetabular liners. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; Las Vegas, NV, 2009; p. 2336.
1074. Kelly NH, Rajadhyaksha AD, Wright TM, Maher SA, Westrich GH. The effect of liner thickness on the wear of highly cross-linked polyethylene acetabular components under “near-impingement” conditions. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; 2009; Las Vegas, NV, 2009; p. 2315.

1075. Rowell SL, Oral E, Muratoglu OK. Three-Year Real-Time Aging of vitamin E-diffused, Radiation Cross-linked UHMWPE. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; Las Vegas, NV, 2009; p. 21.
1076. Costa L, Bracco PM, Carpentieri I, V; B, Brach del Prever EM. On post-irradiation oxidation of vitamin E-stabilized UHMWPE. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; Las Vegas, NV, 2009; p. 461.
1077. Yau S-S, Le K-P, Wang A. Doping vitamin E by diffusion deteriorates properties of crosslinked UHMWPE: Verified by experiments. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; Las Vegas, NV, 2009; p. 458.
1078. Chumakov MC, Silverman J, Al-Sheikhly M. The novel scavenging of free radicals in UHMWPE with TEMPO, a nitroxide antioxidant. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; Las Vegas, NV 2009; p. 453.
1079. Soule PB. The chemistry and biology of nitroxide compounds. *Free Radical Biol. Med.*, 2007; **42**: 1632–1650.
1080. Samuni A, Goldstein S, Russo A, Mitchell JB, Krishna MC, Neta P. Kinetics and mechanism of hydroxyl radical and OH-adduct radical reactions with nitroxides and with their hydroxylamines. *J. Am. Chem. Soc.*, 2002; **124**: 8719–8724.
1081. Beckwith ALJ, Bowry VW, Ingold KU. Kinetics of nitroxide radical trapping. 1. Solvent effect. *J. Am. Chem. Soc.*, 1992; **114**: 4983–4992.
1082. Gijsman P, Smelt HJ, Schumann D. Hindered amine light stabilizers: An alternative for radiation cross-linked UHMWPE implants. *Biomaterials*, 2010; **31**: 6685–6691.
1083. Gijsman P, Gitton M. Hindered amine stabilisers as long-term heat stabilisers for polypropylene. *Polym. Degradation Stability*, 1999; **66**: 365–371.
1084. Gijsman P, Hamskog M. Mechanism of action of hindered amines as long term heat stabilizers. *ACS Symp. Ser.*, 2007; **978**: 48–58.
1085. Klemchuk PP, Gande ME, Cordola E. Hindered Amine. Mechanisms: Part III — Investigations using isotopic labeling. *Polym. Degradation Stability*, 1990; **27**: 65–74.
1086. He S, Le K-P, Blitz JW, Yau S-S, Korduba LA, A. W. Anthocyanin doped UHMWPE: Oxidation, wear and mechanical properties. In: *Transactions of the 55th Annual Meeting of the Orthopaedic Research Society*; Las Vegas, NV 2009; p. 451.

1087. Bakshi SR, Tercero JE, Agarwal A. Synthesis and characterization of multiwalled carbon nanotube reinforced ultra high molecular weight polyethylene composite by electrostatic spraying technique. *Composites: Part A*, 2007; **38**: 2493–2499.
1088. Tang W, Santare MH, Advani SG. Melt processing and mechanical property characterization of multi-walled carbon nanotube/high density polyethylene (MWNT/HDPE) composite films. *Carbon*, 2003; **41**: 2779–2785.
1089. Ruan SL, Gao P, Yang XG, Yu TX. Toughening high performance ultrahigh molecular weight polyethylene using multiwalled carbon nanotubes. *Polymer*, 2003; **44**: 5643–5654.
1090. Wang Y, Cheng R, Liang L, Wang Y. Study on the preparation and characterization of ultra-high molecular weight polyethylene–carbon nanotubes composite fiber. *Compos. Sci. Technol.*, 2005; **65**: 793–797.
1091. Xue Y, Wu W, Jacobs O, Schadel B. Tribological behaviour of UHMWPE /HDPE blends reinforced with multi-wall carbon nanotubes. *Polym. Test.*, 2005; **25**: 221–229.
1092. Gallardo LA, Carpentieri I, Laurent MP, Costa L, Wimmer MA. Europium stearate additives delay oxidation of UHMWPE for orthopaedic applications: A pilot study. *Clin. Orthop. Relat. Res.*, 2011; **469**: 2294–2301.
1093. Moro T, Takatori Y, Ishihara K, Konno T, Takigawa Y, Matsushita T, Chung U-I, Nakamura K, Kawaguchi H. Surface grafting of artificial joints with a biocompatible polymer for preventing periprosthetic osteolysis. *Nat. Mater.*, 2004; **3**: 829–836.
1094. Kyomoto M, Moro T, Konno T, Takadama H, Yamawaki N, Kawaguchi H, Takatori Y, Nakamura K, Ishihara K. Enhanced wear resistance of modified cross-linked polyethylene by grafting with poly(2-methacryloyloxyethyl phosphorylcholine). *J. Biomed. Mater. Res.*, 2007; **82A**: 10–17.
1095. Kyomoto M, Moro T, Konno T, Takadama H, Kawaguchi H, Takatori Y, Nakamura K, Yamawaki N, Ishihara K. Effects of photo-induced graft polymerization of 2-methacryloyloxyethyl phosphorylcholine on physical properties of cross-linked polyethylene in artificial hip joints. *J. Mater. Sci.: Mater. Med.*, 2007; **18**: 1809–1815.
1096. Zoo YS, An JW, Lim DP, Lim DS. Effect of carbon nanotube addition on tribological behavior of UHMWPE. *Tribol. Lett.*, 2004; **16**: 305–309.

1097. Johnson BB, Santare MH, Novotny JE, Advani SG. Wear Behavior of carbon nanotube/high density polyethylene composites. *Mech. Mater.*, 2009; **41**: 1108–1115.
1098. Ishihara K, Ziats NP, Tierney BP, Nakabayashi N, Anderson JM. Protein adsorption from human plasma is reduced on phospholipid polymers. *J. Biomed. Mater. Res. Part A*, 1991; **25**: 1397–1407.
1099. Kuiper KJ, Nordrehaug JE. Early mobilization after protamine reversal of heparin following implantation of phosphorylcholine-coated stents in totally occluded coronary arteries. *Am. J. Cardiol.*, 2000; **85**: 698–702.
1100. Galli M, Sommariva L, Prati F, Zerboni S, Politi A, Bonatti R, Mameli S, Butti E, Pagano A, Ferrari G. Acute and mid-term results of phosphorylcholine-coated stents in primary coronary stenting for acute myocardial infarction. *Cathet. Cardiovasc. Intervent.*, 2001; **53**: 182–187.
1101. Lewis AL, Tolhurst LA, Stratford PW. Analysis of a phosphorylcholine-based polymer coating on a coronary stent pre- and post-implantation. *Biomaterials*, 2002; **23**: 1697–1706.
1102. Ishihara K, Aragaki R, Ueda T, Watanabe A, Nakabayashi N. Reduced thrombogenicity of polymers having phospholipid polar groups. *J. Biomed. Mater. Res.*, 1990; **24**: 1069–1077.
1103. Wright JM, Pellicci PM, Salvati EA, Ghelman B, Roberts MM, Koh JL. Bone density adjacent to press-fit acetabular components: A prospective analysis with quantitative computed tomography. *J. Bone Joint Surg. (Am.)*, 2001; **83**: 529–536.
1104. Manley MT, Ong KL, Kurtz SM. The potential for bone loss in acetabular structures following THA. *Clin. Orthop. Relat. Res.*, 2006; **453**: 246–253.
1105. Field RE, Cronin MD, Singh PJ, Burtenshaw C, Rushton N. Bone remodeling around the Cambridge cup: A DEXA study of 50 hips over 2 years. *Acta Orthop.*, 2006; **77**: 726–732.
1106. Latif AMH, Mehats A, Elcocks M, Rushton N, Field RE, Jones E. Pre-clinical studies to validate the MITCH PCR™ Cup: A flexible and anatomically shaped acetabular component with novel bearing characteristics. *J. Mater. Sci. Mater. Med.*, 2008; **19**: 1729–1736.
1107. Hunziker EB. Articular cartilage repair: Basic science and clinical progress. A review of the current status and prospects. *Osteoarthritis Cartilage*, 2002; **10**: 432–463.

1108. Redman SN, Oldfield SF, Archer CW. Current strategies for articular cartilage repair. *Eur. Cell. Mater.*, 2005; **9**: 23–32.
1109. Kaul G, Cucchiaroni M, Remberger K, Kohn D, Madry H. Failed cartilage repair for early osteoarthritis defects: A biochemical, histological and immunohistochemical analysis of the repair tissue after treatment with marrow-stimulation techniques. *Knee Surg. Sports Traumatol. Arthrosc.*, 2012; **20**: 2315–2324.
1110. Felson DT, Zhang Y. An update on the epidemiology of knee and hip osteoarthritis with a view to prevention. *Arthritis Rheum.*, 1998; **41**: 1343–1355.
1111. Hangody L, Vasárhelyi G. Autologous osteochondral grafting — technique and long-term results. *Injury*, 2008; **39** (Suppl.): 32–39.
1112. LaPrade R, Botker JC. Donor-site morbidity after osteochondral autograft transfer procedures. *Arthrosc. J. Arthrosc. Rel. Surg.*, 2004; **20**: e69–e73.
1113. Nho SJ, Green DM, Shindle MK, Carter T, Williams III RJ, Wickiewicz TL. Patellofemoral osteochondral autologous transfer. *Tech. Knee Surg.*, 2006; **5**: 134–137.
1114. Brittberg M, Lindahl A, Nilsson A, Ohlsson C, Isaksson O, Peterson L. Treatment of deep cartilage defects in the knee with autologous chondrocyte transplantation. *New Engl. J. Med.*, 1994; **331**: 889–895.
1115. Marlovits S, Zeller P, Singer P, Resinger C, Vécsei V. Cartilage repair: Generations of autologous chondrocyte transplantation. *Eur. J. Radiol.*, 2006; **57**: 24–31.
1116. Djouad F, Bouffi C, Ghannam S, Noël D, Jorgensen C. Mesenchymal stem cells: Innovative therapeutic tools for rheumatic diseases. *Nat. Rev. Rheumatol.*, 2009; **5**: 392–399.
1117. Namba RS, Meuli M, Sullivan KM, Le AX, Adzick NS. Spontaneous repair of superficial defects in articular cartilage in a fetal lamb model. *J. Bone Joint Surg. (Am.)*, 1998; **80**: 4–10.
1118. Mankin HJ. The response of articular cartilage to mechanical injury. *J. Bone Joint Surg. (Am.)*, 1982; **64**: 460–466.
1119. Hunziker EB. Growth-factor-induced healing of partial-thickness defects in adult articular cartilage. *Osteoarthritis Cartilage*, 2001; **9**: 22–32.
1120. Hunziker EB, Rosenberg LC. Repair of partial-thickness defects in articular cartilage: Cell recruitment from the synovial membrane. *J. Bone Joint Surg. (Am.)*, 1996; **78**: 721–733.

1121. Jakob RP, Franz T, Gautier E, Mainil-Varlet P. Autologous osteochondral grafting in the knee: Indication, results, and reflections. *Clin. Orthop. Relat. Res.*, 2002; **401**: 170–184.
1122. O'Driscoll SW. The healing and regeneration of articular cartilage. *J. Bone Joint Surg. (Am.)*, 1998; **80**: 1795–1812.
1123. Minas T. The role of cartilage repair techniques, including chondrocyte transplantation, in focal chondral knee damage. *AAOS Inst. Course Lect.*, 1999; **48**: 629–643.
1124. Heath CA, Magari SR. Mini-review: Mechanical factors affecting cartilage regeneration *in vitro*. *Biotechnol. Bioeng.*, 1996; **50**: 430–437.
1125. Carver SE, Heath CA. Semi-continuous perfusion system for delivering intermittent physiological pressure to regenerating cartilage. *Tissue Eng.*, 1999; **5**: 1–11.
1126. Brittberg M. Autologous chondrocyte transplantation. *Clin. Orthop.*, 1999; **367**: S147–S155.
1127. Peterson L, Minas T, Brittberg M, Nilsson A, Sjogren-Jansson E, Lindahl A. Two- to 9-year outcome after autologous chondrocyte transplantation of the knee. *Clin. Orthop.*, 2000; **374**: 212–234.
1128. Bachmann G, Basad E, Lommel D, Steinmeyer J. MRI in the follow-up of matrix-supported autologous chondrocyte transplantation (MACI) and microfracture. *Radiologe*, 2004; **44**: 773–782.
1129. Behrens P, Ehlers EM, Kochermann KU, Rohwedel J, Russlies M, Plotz W. New therapy procedure for localized cartilage defects. Encouraging results with autologous chondrocyte implantation. *MMW Fortschr. Med.*, 1999; **141**: 49–51.
1130. Ronga M, Grassi FA, Bulgheroni P. Arthroscopic autologous chondrocyte implantation for the treatment of a chondral defect in the tibial plateau of the knee. *Arthroscopy*, 2004; **20**: 79–84.
1131. Vibe-Hansen R, Aesculai S. Methods, instruments and kit for autologous chondrocyte transplantation. *Patent WO 98/08469* (1998).
1132. Barry FP. Biology and clinical applications of mesenchymal stem cells. *Birth Defects Res., C Embryo Today*, 2003; **69**: 250–256.
1133. Barry FP. Mesenchymal stem cell therapy in joint disease. *Novartis Found. Symp.*, 2003; **249**: 86–96.
1134. Caplan AI. Mesenchymal stem cells. *J. Orthop. Res.*, 1991; **9**: 641–650.
1135. Gao J, Caplan AI. Mesenchymal stem cells and tissue engineering for orthopaedic surgery. *Chir. Organi Mov.*, 2003; **88**: 305–316.

1136. Minguell JJ, Erices A, Conget P. Mesenchymal stem cells. *Exp. Biol. Med.*, (Maywood) 2001; **226**: 507–520.
1137. Pittenger MF, Mackay AM, Beck SC, Jaiswal RK, Douglas R, Mosca JD, Moorman MA, Simonetti DW, Craig S, Marshak DR. Multilineage potential of adult human mesenchymal stem cells. *Science*, 1999; **284**: 143–147.
1138. Prockop DJ. Marrow stromal cells as stem cells for nonhematopoietic tissues. *Science*, 1997; **276**: 71–74.
1139. Roufosse CA, Direkze NC, Otto WR, Wright NA. Circulating mesenchymal stem cells. *Int. J. Biochem. Cell. Biol.*, 2004; **36**: 585–597.
1140. Temenoff JS, Mikos AG. Review: Tissue engineering for regeneration of articular cartilage. *Biomaterials*, 2000; **21**: 431–440.
1141. Carden A, Morris MD. Application of vibrational spectroscopy to the study of mineralized tissues (review). *J. Biomed. Opt.*, 2000; **5**: 259–268.
1142. Mahadevan-Jansen A. Raman spectroscopy: From benchtop to bedside. In: *Biomedical Photonics Handbook*. (Vo-Dinh T, ed) (CRC Press; Boca Raton, 2003).
1143. Puppels GJ. *In vivo* Raman spectroscopy. In: *Handbook of Raman Spectroscopy: From the Research Laboratory to the Process Line*. (Lewis IR, Edwards HGM, eds) (Marcel Dekker; New York, 2001).
1144. Morris M. Raman spectroscopy of bone and cartilage. In: *Emerging Raman Applications and Techniques in Biomedical and Pharmaceutical Fields*. (Matousek P, Morris M, eds) (Springer-Verlag; Berlin, 2010). Chapter 14.
1145. Esmonde-White K, Mandair GS, Morris M, Raaij F, Jacobson JA, Miller BS, Urquhart AG, Roessler BJ. Raman spectroscopy of synovial fluid as a tool for diagnosing osteoarthritis. *J. Biomed. Opt.*, 2009; **14**: 034013-1–9.
1146. Heger M, Mordon S, Leroy G, Fleurisse L, Creusy C. Raman microspectrometry of laser-resaped rabbit auricular cartilage: Preliminary study on laser-induced cartilage mineralization. *J. Biomed. Opt.*, 2006; **11**: 024003-1–8.
1147. Boskey A, Camacho NP. FT-IR imaging of native and tissue-engineered bone and cartilage. *Biomaterials*, 2007; **28**: 2465–2478.
1148. Camacho NP, West P, Griffith MH, Warren RF, Hidaka C. FT-IR imaging spectroscopy of genetically modified bovine chondrocytes. *Mater. Sci. Eng.*, 2001; **C17**: 3–9.

1149. Obeid EM, Adams MA, Mewman JH. Mechanical properties of articular cartilage in knees with unicompartmental osteoarthritis. *J. Bone Joint Surg. (Br.)*, 1994; **76**: 315–319.
1150. Kuettner KE, Cole AA. Cartilage degeneration in different human joints. *Osteoarthritis Cartilage*, 2005; **13**: 93–103.
1151. Thambyah A, Broom N. On how degeneration influences load-bearing in the cartilage-bone system: A microstructural and micro-mechanical study. *Osteoarthritis Cartilage*, 2007; **15**: 1410–1423.
1152. Kellgren JH, Lawrence JS. Radiological assessments of osteoarthritis. *Ann. Rheum. Dis.*, 1957; **16**: 494–502.
1153. Xia Y. Magic-angle effect in magnetic resonance imaging of articular cartilage: A review. *Invest. Radiol.*, 2000; **35**: 602–621.
1154. Alhadlaq HA, Xia Y, Moody JB, Matyas JR. Detecting structural changes in early experimental osteoarthritis of tibial cartilage by microscopic magnetic resonance imaging and polarised light microscopy. *Ann. Rheum. Dis.*, 2004; **63**: 709–717.
1155. Goodwin DW, Wadghiri YZ, Zhu H, Vinton CJ, Smith ED, Dunn JF. Macroscopic structure of articular cartilage of the tibial plateau: Influence of a characteristic matrix architecture on MRI appearance. *Am. J. Roentgenol.*, 2004; **182**: 311–318.
1156. Mansfield P, Glover P. Limits to magnetic resonance microscopy. *Rep. Prog. Phys.*, 2002; **65**: 1489–1511.
1157. Collins DH, McElligott TF. Sulphate (35SO_4) uptake by chondrocytes in relation to histological changes in osteo-arthritic human articular cartilage. *Ann. Rheum. Dis.*, 1960; **19**: 318–330.
1158. West PA, Bostrom MPG, Torzilli PA, Camacho NP. Fourier transform infrared spectral analysis of degenerative cartilage: An Infrared fiber optic probe and imaging study. *Appl. Spectrosc.*, 2004; **58**: 376–381.
1159. Frushour BG, Koenig JL. Raman scattering of collagen, gelatin, and elastin. *Biopolymers*, 1975; **14**: 379–391.
1160. Chi Z, Chen XG, Holtz JSW, Asher SA. UV resonance Raman-selective amide vibrational enhancement: Quantitative methodology for determining protein secondary structure. *Biochemistry*, 1998; **37**: 2854–2864.
1161. Dehring KA, Smukler AR, Roessler BJ, Morris MD. Correlating changes in collagen secondary structure with aging and defective type II collagen by Raman spectroscopy. *Appl. Spectrosc.*, 2006; **60**: 366–372.

1162. Dehring KA, Crane NJ, Smukler AR, McHugh JB, Roessler BJ, Morris MD. Identifying chemical changes in subchondral bone taken from murine knee joints using Raman spectroscopy. *Appl. Spectrosc.*, 2006; **60**: 1134–1141.
1163. Ignatieva N, Zakharkina O, Leroy G, Sobol E, Vorobieva N, Mordon S. Molecular processes and structural alterations in laser redhaping of cartilage. *Laser Phys. Lett.*, 2007; **10**: 749–753.
1164. Lim NS, Hamed Z, Yeow CH, Chan C, Huang Z. Early detection of biomolecular changes in disrupted porcine cartilage using polarized Raman spectroscopy. *J. Biomed. Opt.*, 2012; **16**: 017003-1–10.
1165. Teeple E, Elsaid KA, Fleming BC, Jay GD, Aslani K, Crisco JJ, Mechrefe AP. Coefficients of friction, lubricin, and cartilage damage in the anterior cruciate ligament-deficient guinea pig knee. *J. Orthop. Res.*, 2008; **26**: 231–237.
1166. Neu CP, Reddi AH, Komvopoulos K, Schmid TM, Di Cesare PE. Friction coefficient and superficial zone protein are increased in patients with advanced osteoarthritis. *Arthritis Rheum.*, 2010; **62**: 2680–2687.
1167. Mow VC, Ratcliffe A, Poole RA. Cartilage and diarthrodial joints as paradigms for hierarchical materials and structures. *Biomaterials*, 1992; **13**: 67–97.
1168. D'Antonio JA, Manley MT, Capello WN, Bierbaum BE, Ramakrishnan R, Naughton M, Sutton K. Five-year experience with crossfire highly crosslinked polyethylene. *Clin. Orthop. Relat. Res.*, 2005; **441**: 143–150.
1169. Duffy GP, Wannomae KK, Rowell SL, Muratoglu OK. Fracture of a cross-linked polyethylene liner due to impingement. *J. Arthroplasty*, 2009; **24**: 158.e15–19.
1170. Tower SS, Currier JH, Currier BH, Lyford KA, Van Citters DW, Mayor MB. Rim cracking of the cross-linked longevity polyethylene acetabular liner after total hip arthroplasty. *J. Bone Joint Surg. (Am.)*, 2007; **89**: 2212–2217.
1171. Moore KD, Beck PR, Petersen DW, Cuckler JM, Lemons JE, Eberhardt AW. Early failure of a cross-linked polyethylene acetabular liner. Acase report. *J. Bone Joint Surg. (Am.)*, 2008; **90**: 2499–2504.
1172. Blumenfeld TJ, McKellop HA, Schmalzried TP, Billi F. Fracture of a cross-linked polyethylene liner: A multifactorial issue. *J. Arthroplasty*, 2011; **26**: 666.e5–8.
1173. Waewsawangwong W, Goodman SB. Unexpected failure of highly cross-linked polyethylene acetabular liner. *J. Arthroplasty*, 2012; **27**: 323.e1–4.

1174. Morscher EW. Failures and successes in total hip replacement — why good ideas may not work. *Scand. J. Surg.*, 2003; **92**: 113–120.
1175. Loudon R. Theory of the resonance Raman effect in crystals. *J. Phys.*, 1965; **26**: 677–683.
1176. Browne WR, McGarvey JJ. The Raman effect and its application to electronic spectroscopies in metal-centered species: Techniques and investigations in ground and excited states. *Coordination Chem. Rev.*, 2007; **251**: 454–473.
1177. Williams AC, Edwards HGM, Lawson EE, Barry BW. Molecular interactions between the penetration enhancer 1,8-cineole and human skin. *J. Raman Spectrosc.*, 2006; **37**: 361–366.
1178. Krafft C, Sobottka SB, Schackert G, Salzer R. Near infrared Raman spectroscopic mapping of native brain tissue and intracranial tumors, *Analyst*, 2005; **130**: 1070–1077.
1179. Ip K, Baik KH, Overberg ME, Lambers ES, Heo YW, Norton DP, Pearton SJ, Ren F, Zavada JM. Effect of high-density plasma etching on the optical properties and surface stoichiometry of ZnO. *Appl. Phys. Lett.*, 2002; **81**: 3546–3548.
1180. Goslowsky H, Kühne H-M, Neff H, Kötz R, Lewerenz HJ. The influence of chemical surface alteration on photoresponse of polycrystalline CuInS₂ electrodes. *Surf. Sci.*, 1985; **149**: 191–208.
1181. Goodfellow JW. The new Esperanto. *J. Bone Joint Surg. (Am.)*, 1993; **75(A)**: 1423–1426.

Index

- acetabular cups 10, 14, 21, 44, 82, 85–86, 116, 189
- acetabulum 8–9
- AFM *see* atomic force microscopy
- alumina 7, 20–21, 30, 47, 63–64, 69, 71–81, 102–4, 113, 130–33, 144–45, 150, 169–70, 197–98, 208–9
 - biomedical grades of 133–34
 - monolithic 77, 99, 118, 120, 130, 134, 180, 198, 207–8, 224
 - polycrystalline 71–72, 75–76, 78–80, 101–3, 131, 134, 174
 - wear resistance of 113, 120
 - zirconia-toughened 199, 207
- alumina bioceramics 130, 145, 176
- alumina biomaterials 134, 136
 - hard 145
- alumina ceramics 30, 69, 72, 80–81, 118, 128–29, 135–37, 145–46, 197
- alumina femoral heads 72, 94, 99–100, 108, 113–14
- alumina grain array 75, 77
- alumina heads 80, 87, 95, 114, 117, 154, 158, 197
- alumina hip joints 82, 105, 113
- alumina hip surfaces 119
- alumina liner 80, 86
- alumina materials
 - medical-grade 76
 - modern 76, 131
- alumina microstructures 30, 76–77, 83, 130, 208
- alumina polycrystals 74, 79, 102
 - fine grained 178
- alumina powders 81
- alumina–zirconia composites 207, 209, 211, 213, 215, 217
- alumina–zirconia system 207
- angular orientation map 201, 203
- apatite crystals 24
- articular cartilage 11, 13
- artificial joints 2, 4, 8–9, 11, 13, 23, 25, 29–31, 33, 37, 43–44, 53, 57, 59, 159
 - biomechanics of 8–9, 11, 13
- atomic force microscopy (AFM) 25, 31, 34–38, 59, 68, 84, 89, 111, 113, 118
- bioceramics 47, 49, 59, 61, 198, 222
- biomaterial microstructures 22, 31, 52, 198
- biomaterials research 33–34
- biomedical alumina, grained 150
- biomedical alumina grades 131
- biomedical implants 24, 26, 65, 133
- brittle materials 54, 58, 105, 132
- cantilever deflection 35–36
- cartilage 9–12
 - osteoarthritic 12
- cathodoluminescence (CL) 33, 45, 47–48, 113, 122–23, 128–29
- cathodoluminescence spectroscopy 45, 47, 101, 179

- ceramic biomaterials 30, 53, 55, 71, 199
- ceramic crystal, synthetic 12
- ceramic liners 21, 83, 85, 91
- ceramic-on-ceramic articulations 5–6
- ceramic oxides 48
- ceria 49
- CL *see* cathodoluminescence
- CL, extrinsic 45–46
- CL equipment 47
- clearance 84–85, 91, 111
- closure stresses 131
- COD method 150, 177, 179
- collagen fibers 10, 12–14
- collagen fibrils 13, 24
- compressive residual stresses 74, 76, 112, 156, 174, 224
- cortical bone 10, 24
- crack
 - advancing 56, 150–51, 217
 - surface radial 58
- crack-face bridging 55–57
- crack initiation 55, 58, 149, 151
- crack instability 131
- crack propagation 55, 132, 148, 150, 176, 178, 209, 214, 217
- crack-tip fracture toughness 176–77, 179
- crack-tip transformation 214–15
- cubic grains 164, 167

- debris formation 69
- dislocation loops 122, 126

- EBSD *see* electron backscattering diffraction
- electron backscattering diffraction (EBSD) 33, 50, 52–53, 103
- environmental transformation 178

- Eshelby procedure 75, 77–78
- extensive surface dislocation 69

- femoral head fracture 18
- femoral heads 8, 18–20, 44, 60–62, 66–68, 83–85, 87–88, 90–92, 114–17, 123–26, 146, 179–85, 187–90, 195–98, 224–25
 - ceramic 18–19, 85, 111, 180
 - fractured 20, 155
 - polyethylene-mating alumina 115, 117
 - zirconia 157, 180
- femur 9–11
- forbidden gap 47
- fracture propagation 149, 151
- fracture strength 57, 129, 131, 135
- fracture toughness 55, 57–58, 129–30, 176, 178, 214–15, 217

- gas plasma 17
- grain-boundary grooving 113–14
- grain-boundary microcracks 78, 112–13, 119
- grain detachment 94–95, 108, 111–13, 119, 126–27
- grain dislodgement 113

- hardness 63, 147, 159, 198, 206
- hip arthroplasty 61, 72, 196
- hip implants 18, 58, 72, 155
- hip joints 4–5, 20, 60, 76, 80, 98, 113, 118, 159, 184, 219, 224
 - alumina-on-alumina 113–14
- hip surgeries 15–16, 55

- hydrothermal attack 180, 217, 220, 224, 226
- hydrothermal degradation 147, 180
- hydrothermal environment 119, 147, 152, 156, 166, 179–80, 182, 189–91, 194, 203, 206, 220–22, 225–26
- infrared spectroscopy 38, 336, 343, 482, 485, 504
 - Fourier-transform 25
- interstitial aluminum 118, 120
- intragranular silicon carbide particles 78
- joint arthroplasty 1–8, 44–45, 48, 71, 141, 199
- joint replacement surgery 26
- joints, metal-on-metal 68–69
- knee joints 12, 14, 22–23, 52
- knee simulators 61–62
- laser probes 45, 66, 102, 224, 226
- laxity 84, 95
- liner, acetabular 6, 61–62
- load-bearing surfaces 23, 31, 37, 48, 107, 116
- low-temperature degradation 176, 201, 204
- microcracks 69, 92, 178
- microscopic surface asperities 83
- microseparation 83–84, 97
- microstructural material design 6–7
- mild wear regimes 128
- monoclinic fraction 196, 214, 217, 221
- monoclinic nuclei 163–64, 193
- monoclinic phase 19, 44, 142, 151–53, 155–57, 161, 190, 199, 206, 209–11, 215–16, 222, 224
- monoclinic phase transformation 19, 158
- monoclinic zirconia polymorphs 8, 181, 223, 225
- monoclinic ZrO_2 phases 214, 223, 225
- non-destructive evaluations 27, 59, 61
- osteoarthritis 9, 12, 195–97
- osteolysis 3, 6, 14, 146, 180
- oxide bioceramics 48–49
- oxygen off-stoichiometry 201, 205
- oxygen vacancy annihilation 192–93
- patella 10–11
- piezo-spectroscopic effect 43, 150
- pin-on-ball geometries 66–67
- plastic deformation 63, 69, 72, 126, 128
- point defects 118, 120, 122, 129, 141
- polycrystalline alumina biomaterials 65

- polycrystalline zirconia 137, 139, 154, 159–60
- polyethylene 6, 14, 17–18, 21, 27, 72, 80, 82, 113, 154, 180, 189, 197
 - ultra-high molecular weight 16–17
- polyethylene liners 3, 16–17, 113, 115, 138, 180, 195, 197
- prostheses 4–5, 17, 38, 113
- proton defects 153

- Raman spectroscopy 23–26, 31, 38–45, 64, 98, 149–51, 154–55, 168, 172, 176, 179, 190, 206, 219, 261, 266, 313, 330, 333, 348, 493–94, 504
 - back-scattered 504
 - confocal 237, 239, 333, 422, 473
 - near-infrared 484–86
 - polarized 23–24, 330, 370, 382, 396
- rare-earth elements 46, 79
- residual stresses 63, 73–75, 78, 98–99, 103–7, 109, 111–12, 115–16, 145, 155, 157–58, 174, 201–2, 211–12, 223–24
- revision surgeries 2, 5, 15–16, 21, 196
- roughening 159, 180

- scanning electron microscopy (SEM) 24–25, 32–33, 45–47, 50–54, 59, 84, 111, 113, 132
- SEM *see* scanning electron microscopy
- SENB *see* single-edge-notched beam
- silicon impurities 192, 195
- single-edge-notched beam (SENB) 57–58
- sliding, alumina surfaces 113
- statistical sampling 26
- Stokes scattering 40
- stress fields, crack-tip 148, 150
- stress-induced phase transformation 150
- stress-induced tetragonal-to monoclinic transformation 151
- stylus profilometer 34, 38
- surface artifacts 52
- surface blistering 155
- surface blisters 156
- surface characterization methods 31, 33
- surface chemistry 29, 71, 144
- surface cracks 113
- surface damage 38, 62, 80, 97, 113
 - polishing-induced 53
- surface damage accumulation mechanisms 69
- surface deterioration 155, 180
- surface disruption 108, 113
- surface grain detachment 112
- surface lattice strain 120
- surface microcracks 111, 138
- surface modifications 44, 64, 147, 206
- surface monolayers 143
- surface plasticity 128
 - wear-induced 126
- surface protuberances 94
- surface residual stresses 97, 99, 101, 103, 105, 107, 109, 111, 113, 115, 117
- surface roughening 180, 223
- surface roughness 31, 37–38, 63, 146, 150, 160, 187, 197
- surface scratches 104
- surface strain 154
 - localized 49

- tetragonal distortion 142, 171
- tetragonal grains 153, 167
- tetragonal zirconia 164, 200, 205, 208, 213
- tetragonal zirconia phases 170, 223–24
- THA *see* total hip arthroplasties
- total hip arthroplasties (THA) 2, 15
- total joint replacement 1–2
- toughening 55, 59, 159, 161, 163, 165, 167, 169, 171, 173, 175, 177, 179, 208, 214
- toughening effect 149, 178, 214, 217
- toughening mechanisms 54–55, 57, 59, 150–51, 198, 208, 214
- transformation toughening 55–56, 148, 152, 215
- tribochemical reactions 68–69, 119, 123
- tribology assessments 61, 63, 65, 67, 69

- UHMWPE *see* ultra-high molecular weight polyethylene
- ultra-high molecular weight polyethylene (UHMWPE) 25–26, 44–45

- wear 16, 22, 30, 37, 44, 61, 64–65, 68–69, 74, 84, 86, 89, 103, 118–19, 219
 - extensive 16
 - induced 113
 - stripe 83, 86–87, 95
 - wear damage, role of chemistry in 118–19, 121, 123, 125, 127
 - wear debris 4, 69, 71–72, 180
 - wear mechanisms 83, 85, 99, 111, 113, 127
 - Weibull modulus 134–35, 150, 197

- yttria 49, 167, 175

- zirconia 5, 18–19, 49, 63–64, 137–39, 141, 143–49, 152–53, 159, 171, 176, 180, 203–4, 206, 208
 - pure 139, 141, 203
- zirconia ceramics 57, 138, 143, 148, 151–52, 154, 168, 197
- zirconia femoral heads 18–19, 49, 154, 158, 188–89, 197
- zirconia heads 18, 138, 158, 179, 181, 183, 185, 187, 189, 191, 193, 195, 197
- zirconia hip joints 154, 157
- zirconia materials, stabilized 144–45, 151, 159
- zirconia-toughened alumina (ZTA) 199, 207–8, 212, 214–17, 220
- ZTA *see* zirconia-toughened alumina
- ZTA composites 208, 214–15
- ZTA microstructure 209–10, 215–16

