

Index

- ABC *see* absorbing boundary conditions
absorbing boundary conditions (ABC) 41, 57, 79
absorption 79, 98, 100, 119, 137, 142, 143, 150, 152, 173, 192, 235, 281, 304, 368, 386
band-to-band 304
parasitic 214, 238
three-photon 459, 471
two-photon 386, 459
active layers 86–88, 97, 100, 142, 152, 161, 226, 230, 233, 238, 271, 278, 280, 282, 287
active region 84, 86, 91, 122, 158, 159, 163, 197, 220, 225, 228, 233, 296, 357, 486–489, 491, 492
AFM *see* atomic force microscopy
air holes 43, 44, 53–58, 73, 214, 220
air opening 260–262
approaches 162, 166, 170, 171, 180, 185, 187, 188, 211, 213, 234–237, 327, 330, 393, 442, 443, 461, 463
approximate analytical 422
chemical lift-off 364
combinatorial 289
cost-effective 237, 316
dry-etching 188
finite-element 393
geometric 132, 133, 138, 139
growth interruption 164, 179
heterogeneous 349
monolithic 372
optical modal volume 474
semi-analytical 392, 393, 396, 425
technological 160
transfer-matrix 396
two-temperature 178
arrays 98, 170, 186, 197, 212, 321, 329, 338, 344, 432
air hole 56
aperiodic 368
closed-packed 317
close-packed 269
hemi-ellipsoid 320
multi-coupled ring 342
nanobelt 364
nanopillar 322, 347
non-closed packed sphere 338
ordered hexagonal 317
square lattice 65
atomic force microscopy (AFM) 147, 164, 220, 308, 338
azimuthal dependence 393, 394
azimuthal direction 138, 139
azimuthal mode orders 47, 49, 50
azimuthal number 137, 141, 150, 387, 391, 396, 402, 422, 427, 430
band gap 57, 58, 109, 175, 181, 182, 354, 355, 372, 443
bands 54–56, 58, 61, 354–356, 358, 452, 487, 490
conduction 60, 61, 68, 69
stop 88, 89
valence 60, 61, 68, 69
boundary conditions 46, 135, 138, 139, 482
absorbing 41, 79
open 43
periodic 64, 66

- carriers 68, 146, 157, 193, 244, 296, 297, 355, 489
charge 51, 59–61
photo-generated 182, 355
cavity 56, 57, 70–72, 87–89, 91, 100, 136–138, 189, 294, 295, 339–341, 384–388, 397, 398, 441–443, 465, 466, 480–484, 489, 490
circular 79, 147, 316, 327, 334
cold 141
dielectric-type 87
free-standing 137
gallery 421
heater's 406, 407
hybrid 88, 91
microheater's 407
nanopillar 480
pillar 332, 334
plasmonic 442
polygonal 455
quasi-WGM 455
random 442, 443
resonance 294, 295
sphere-patterned 317, 329, 344
strip-line 382
symmetric 384
traveling-wave 473
vertical 93
cavity effects 447
cavity layer 187, 188
cavity length 84, 91, 104, 158, 186, 188, 201, 354
cavity mode 53, 70, 71, 97, 99–101, 151, 340, 386, 459
cavity quality factor 86, 93, 104, 492
cavity quantum electrodynamics 131, 441
cavity resonance 382, 421, 465, 478, 480, 482
cavity structure 188–190, 199
CCD *see* charge-coupled device
CFS *see* complex frequency shifted
charge-coupled device (CCD) 103, 149, 227, 251, 445
chemical etching 180, 185, 368, 375
circuits 373, 379
integrated 116, 372
logic 353
power conversion 373
silicon-based VLSI 350
circular gratings 248, 250, 251, 255, 265, 267, 268, 289
CMT *see* coupled mode theory
complex frequency shifted (CFS) 42
conditions 31, 70, 77, 164, 183, 327, 397, 398, 415
ambient 318, 424, 446
continuous-wave 122
diffusion 276
forward-bias 217
high temperature 97
lossless 398
low RF power 338
momentum matching 294
non-interruption 164
phase-matching 420
refraction 70
resonance phase 101, 190
reverse-bias 217
wavefront-matching 457
confined modes 49, 53, 139, 140, 149, 151, 248, 264, 269, 272, 273
confinement 43, 54, 56, 132, 460, 483
gentle 70, 72, 82
in-plane 47
insufficient 355
slab plane 44
surface plasmonic 476
coupled mode theory (CMT) 384, 398
coupling 225, 293–296, 298–300, 302, 304, 306, 308, 310, 312,

- 384, 386, 396–399, 401, 403, 408
 coherent 298
 contra-directional 342
 critical 398, 401, 403, 410, 414
 intracavity 337
 light-matter 141
 light-mediated 75
 optical 342, 344
 optical-mechanical 382
 parasitic 408
 radiative 65, 66
 unidirectional 396
 vacuum 431
 coupling coefficient 136, 142, 397–399, 435
 coupling constant 69, 460
 coupling regimes 27, 28, 70, 206, 401, 459–461, 466
 crack generation 166, 167, 169, 172, 205
 cracks 88, 89, 163, 166–170, 172, 179, 201, 276, 352, 353, 364, 369–371
 bowing-induced 352
 stress-induced 371
 current density 28–30, 85, 103, 191, 192, 195, 196
 current injection 88, 101, 127, 204, 227, 230, 231, 329, 347
- DBRs *see* distributed Bragg reflectors
 DBRs
 cracking-free 165
 epitaxial 159, 187, 197, 203
 gap-based 180, 182, 183
 hybrid 87, 102
 nitride-based 107, 160
 oxide 186
 oxide-based 87
 DBR structure 89, 107, 108, 112, 113, 116, 161, 162, 172, 200, 201
- deep level emission (DLE) 447, 448, 450, 465, 469
 deep reactive ion etching (DRIE) 248, 249, 265, 274
 defect modes 23, 58, 59, 322
 defects 43, 53, 54, 56–58, 84, 180, 185, 418, 470
 density 28, 29, 59, 62, 68, 145, 426, 452
 charge 29, 51
 crack 246
 low defect 368
 low dislocation 365
 spectral mode 150
 threshold power 113, 119
 design 27, 90, 91, 107, 141, 144, 162, 167, 172, 182, 183, 185, 202, 246, 475, 479, 481
 flexible 364
 metal-clad nanoring 482
 quantum device 213
 structural 87, 237
 devices 27, 28, 48, 50, 51, 56, 57, 84, 85, 116, 117, 119, 122, 124, 125, 212, 214–216, 237, 297, 298, 464, 475
 biochemical 317
 charge-coupled 103, 149, 227
 charged coupled 445
 chip-scale 238
 electroluminescent 337
 heterostructured diode 464
 metal-coated 119
 microelectronic 350
 nanophotonic 212
 optical 146, 151, 208, 245, 375
 photonic crystal 128
 silicon logic 365
 DFT *see* discrete Fourier transform
 dielectric materials 39, 45, 51, 75, 159, 302, 310, 386, 389
 dielectric mirrors 88–90, 92, 93, 349
 differential equations 47, 67

- ordinary 75
- partial 30, 394
- discrete Fourier transform (DFT) 75, 76
- disk 44, 47, 48, 138, 139, 149, 150, 152, 383–389, 391–393, 396–398, 401, 404, 405, 410–413, 415–422, 424–432, 444, 446
 - broken 420
 - ceramic 406
 - collapsed 418
 - corrupted 420
 - damaged 418
 - distinct 417
 - optically valid 420
 - thin 412
- disk cavity 386, 387, 389, 392, 398, 401
- disk edges 133, 138, 139, 149
- disk geometry 412, 419, 427
- disk radius 133, 140, 141, 411, 413, 419, 420, 422, 428
- disk resonator 348, 383, 384, 386, 389, 392, 394, 396, 437, 438
- dislocations 110, 158, 163, 164, 166, 196, 205, 363, 375
- distributed Bragg reflectors (DBRs) 86, 91–93, 104, 106–109, 115, 126, 127, 129, 157, 160–163, 166–168, 170, 172–176, 197, 200, 201, 205–210
- DLE *see* deep level emission
- DRIE *see* deep reactive ion etching
- EB *see* electron beam
- EBL *see* electron-beam lithography
- edge-emitting lasers (EELs) 84, 86, 158, 316, 349
- EELs *see* edge-emitting lasers
- effective index 114, 122, 132–135, 137, 139, 140, 258, 263, 387, 390, 411, 487
- EHP *see* electron-hole plasma
- electric field 30–32, 34, 45, 52, 63–65, 72, 133, 134, 137, 138, 151, 390, 395, 477, 478, 482, 486, 492
- electron beam (EB) 111, 128, 203, 218, 241, 248, 464, 485
- electron-beam lithography (EBL) 146, 298, 316
- electron-hole plasma (EHP) 452, 454, 466
- ELO *see* epitaxial lift-off
- epitaxial lift-off (ELO) 349–352, 354, 356, 358, 360, 362, 364, 366, 368, 370–372, 374, 376, 378
- etching 85, 111, 184, 185, 220, 233, 236, 248, 284, 319, 331, 354, 355, 359, 361, 362, 442
 - anisotropic 259
 - anisotropic crystallographic 356
 - buffered HF 254, 282
 - diffusion-limited 356
 - dry 147, 226, 229, 230, 248, 254, 259, 298
 - isotropic 259
 - lateral undercut 360
 - lateral wet-chemical 364
 - uniform 355
 - vertical 233
- etching mask 117, 254, 255, 259, 269, 279, 282, 283
- etching rate 180–183, 185, 249, 356, 363
- etching selectivity 144, 152, 183, 351, 355, 365
- etching time 183, 184, 364, 367
- evanescent coupling 383, 385, 386, 396, 405, 408, 410, 413, 416, 420, 462, 473, 483
- excitation density 332, 339, 446, 450–454, 462, 463

- excitation intensity 28, 445, 453
- excitation power 181, 187, 301, 302, 324, 360
- excitation power density 324, 325, 333, 337, 454, 459
- excitons 60, 198, 199, 203, 237, 289, 340, 447, 451, 452, 459, 460, 466, 470
- extraction efficiency 127, 211, 212, 214, 225, 228, 235, 236, 238, 273
- extraction lengths 235, 242

- FAB etching *see* fast atom beam etching
- fabrication 87–90, 106, 107, 128, 129, 132, 144–146, 158, 180, 182, 183, 190, 200–202, 236–238, 288, 289, 320, 321, 376–378, 485
- fiber-coupler 407
- fiber-taper 406
- reproducible 406
- fabrication process 111, 116, 143, 152, 185, 259, 269, 274, 276, 282, 404, 408, 417, 420, 426
- fast atom beam etching (FAB etching) 248, 249, 254, 259, 264, 265, 269, 271, 279, 282, 283
- FDM *see* filter diagonalization method
- FDTD method *see* finite-difference time-domain method
- FDTD simulations 37, 114, 335, 342, 486, 491
- FEM *see* finite element method
- FEM simulation 125, 395, 420, 428, 430
- FIB *see* focused ion beam
- fiber 103, 337, 406, 407, 410, 422, 458
- multimode 113
- silica 406, 407
- single-mode telecom 406
- tapered 406, 407, 410, 413, 462
- fiber polarization controller (FPC) 410, 423
- fiber taper 384, 406, 408, 411, 415–417, 436
- looped 410–412, 416, 417, 438
- micro-looped 408
- movable optical 416
- single-loop 409
- symmetric 408
- filter diagonalization method (FDM) 49, 76, 80, 476
- finite-difference time-domain method (FDTD method) 28, 60, 63, 68, 74, 78, 114, 493
- finite element method (FEM) 28, 78, 79, 121, 393, 435, 457
- focused ion beam (FIB) 128, 316, 346, 486
- FPC *see* fiber polarization controller
- free spectral range (FSR) 387, 388, 411, 430, 481
- FSR *see* free spectral range

- GaN buffer 161, 165, 179, 197, 201
- GaN devices 363
- GaN epilayers 145, 350, 351, 363, 364, 368, 371
- GaN film 351–353, 363, 365, 367, 370
- GaN layer 183–185, 188, 246, 248, 260, 281, 308, 332, 356, 358, 362, 364, 368, 369, 377
- GaN microdisks 114, 154, 288, 329, 347, 357, 360, 378
- GaN nanocolumns 279–281
- GaN nanorods 366
- GaN nanostripe 117, 118, 125
- GaN substrate 84, 195, 197, 203, 204, 208, 280, 365, 366, 463

- GaN surface 98, 269, 271, 272, 361, 367
- grating height 247–249, 252, 253, 265
- grating period 246–250, 252, 253, 255, 257, 258, 260, 261, 263, 266–268, 274, 275, 278, 296, 299
- grating region 250, 251, 254, 256, 267, 276, 277
- gratings 103, 247, 250, 252, 255–257, 259, 260, 262, 275, 276, 288, 324, 490
- grating width 246, 250, 252, 253, 255, 274–279
- grids 31, 32, 35, 38, 298
 - dense 64
 - electric 31
 - nonuniform 57
 - primary 31, 32
 - secondary 31, 32
 - staggered 31
 - uniform 37
- guided modes 111, 132, 212, 214, 225, 228, 233–235, 238, 256

- HEMTs *see* high electron mobility transistors
- high electron mobility transistors (HEMTs) 368, 372
- holes 56, 60, 181, 217, 230, 231, 233, 238, 307, 308, 354–356, 451, 486, 488
 - missing 53
 - photogenerated 355
 - photo-generated 354

- ICP *see* inductive coupled plasma
- III-nitride gratings 247, 248, 250, 251, 253, 256, 257, 275, 276, 288
- epitaxial 262
- linear 252
- mode resonant 254
- nanoscale 274
- III-nitride layer 248, 254, 255, 264
 - thick 264
 - thin 264
- III-nitride LEDs 211, 214, 219, 226, 235, 237
- III-nitride materials 220, 221, 226, 259, 267
- III-nitride nanocolumns 260, 261, 278, 281–285, 287
- III-nitride nanocolumn slab 284, 286–288
- III-nitrides 154, 158–160, 165, 166, 180, 181, 201, 203, 206, 211, 214, 215, 235–237, 248, 254, 255, 274, 275, 345, 346, 350
- index contrast
 - high refractive 172
 - low refractive 89
 - optical 176
 - refractive 132, 172, 176, 257, 486
- inductive coupled plasma (ICP)
 - 111, 220, 226, 229, 230, 319, 323, 331, 353
- interface 38, 45–47, 163, 164, 178, 188, 189, 294, 351, 352, 354, 355, 358, 365, 366, 368, 432, 442, 443, 460, 465
 - electrolyte 355
 - electrolyte-GaN 356
 - liquid-solid 444
 - material-air 50, 59
 - metal-semiconductor 476
 - nanoporous 362
 - slab-vacuum 56
- internal quantum efficiency (IQE)
 - 267, 281, 296–298, 301
- IQE *see* internal quantum efficiency

- laser beam 95, 97, 188, 269, 352, 353, 446
- laser cavity 322, 443, 476, 478, 481, 483, 487, 490
- laser devices 85, 86, 124, 479, 487
- laser diodes (LDs) 106
- lasers 81, 85, 87, 98, 100, 124, 128, 315, 323, 442, 445, 468, 469, 474, 487, 490
 - blue-ultraviolet 315
 - bowtie cavity 475
 - continuous-wave 119
 - edge-emitting 84–86, 105, 158, 316, 349
 - low-threshold 145, 151
 - microdisk-based 131
 - nanopatch 475
 - plasmonic nanowire 475
 - pulsed nitrogen 186
 - ring 473–475, 479, 491, 492
 - single-mode 387
 - vertical-emitting-type 86
- laser structures 123, 477–479
 - metal-clad 478
 - microring 479
 - nanopillar 483
- lasing 115, 119, 121, 126, 130, 186, 190, 192, 193, 443, 445, 450, 451, 455, 468, 472, 492, 493
 - clear 200
 - defect-mode 322
 - excitonic 452, 453
 - inversionless 198
 - low threshold 329
 - low-threshold 327
 - photon 200
 - short wavelength 315
 - single-mode 330
- lasing action 89–91, 104, 111, 113, 116, 119, 121, 123, 474
- lasing modes 95, 100, 113, 114, 119, 128, 333, 334, 341
- lasing peaks 111, 121, 324–326, 328, 334, 339, 341, 458, 465, 487
- lasing threshold 91, 100, 325, 340, 450, 451, 456, 476, 489
- lasing wavelengths 88, 113, 477, 489–491
- lattice constant 54–57, 166, 228, 230–233, 328, 370
- lattice mismatch 145, 162, 275, 276, 280
- lattices 51, 53, 85, 225, 485
 - crystal 402
 - periodic 56
 - triangular 220
- layers 51, 54, 88, 98, 100, 157, 158, 162, 163, 165, 178, 180, 246, 248, 249, 298, 299, 302, 361
 - capping 299
 - closed-packed silica 283
 - close-packed silica 284
 - continuous 361
 - doped 235
 - epitaxial gain 108
 - epoxy 302
 - etching stop 282
 - graphene 368
 - high refractive index 161
 - high refractive-index 172
 - lower refracted index 110
 - low refractive index 161
 - low refractive-index 172
 - nanoporous 362
 - nanoporous 360
 - nanostructured mask 368
 - strain engineering 370
 - superlattice 84
 - wetting 146
- LDs *see* laser diodes
- LDs
 - blue 106
 - edge emitting 191, 192, 202
 - edge-emitting 186
 - violet 106
- LEDs *see* light emitting diodes
- LEDs
 - blue 106, 161, 201, 226–229, 243, 374

- encapsulated 235
- nitride 211, 215, 227
- ring-shaped 226
- LEDs, GaN heterostructure 218
- lift-off 321, 338, 349, 359, 360, 362–364, 367, 368, 373, 377
 - chemical 351, 363, 371, 376, 377
 - mechanical 351, 368, 371
 - nanoepitaxial 364, 371
 - photoelectrochemical 351
 - thin-film 372
- lift-off method 360, 364, 367, 368, 370
- lift-off techniques 351, 353, 355, 357, 359, 361, 363, 365, 367, 369–371
- light emission 24, 93, 103, 113, 193, 219, 296, 365
- light emitter 293–296, 298, 300, 302–304, 306, 308, 310, 312
- light emitting diodes (LEDs) 200, 210–215, 217–219, 226–231, 235, 236, 240, 242, 243, 294, 298, 346, 350, 365, 368, 462, 469
- light extraction 127, 190, 213, 215, 219, 225, 228, 233–235, 239, 241–243, 263, 289, 321, 368
- light extraction efficiency 201, 239, 242, 246, 269, 272, 273, 297, 367
- light-extraction efficiency 264, 267, 268, 272, 281, 287
- lighting 215, 217, 218, 237, 240
 - automotive 106
 - directional 217
 - solid-state 236, 239, 378
- lighting sources 158, 181, 211, 215, 217
 - artificial 215
 - fluorescent 217
 - popular 181
 - traditional 217
- light–matter interaction 27, 61, 70, 72, 388
- light–matter interactions 153, 384
- line splitting 69–74
 - clear 72
 - symmetric 70
- linewidth 88, 96, 99, 119, 121, 124, 410, 413, 414, 489, 490
- lithography 147, 220
 - electron beam 111, 128, 485
 - nano-imprint 299
 - standard 98, 170
- localized surface plasmon (LSP) 294–296, 312, 322
- lower polariton branch (LPB) 199
- LPB *see* lower polariton branch
- LSP *see* localized surface plasmon
- LSP coupling 301, 304, 305
- LSP modes 298, 304–307
- LSP resonance 299, 300, 303–305, 309

- magnetic fields 28, 31, 32, 34, 48, 134, 389, 390, 394
- mask 111, 274, 338, 371, 420
 - electronic lithography 417
 - etch 338, 360
 - hard 254, 323, 485
 - lithographic 317, 319
 - nanosphere 330
 - silicon diode 368
- materials 30, 37–39, 43, 44, 48, 56, 57, 218, 219, 226, 229, 321, 322, 326, 387, 388, 404, 425, 426, 469, 471
 - anisotropic 40, 389
 - compound 51
 - dispersive 42, 387
 - epitaxial 262
 - host 383
 - isotropic 389
 - lossy 41

- low refractive index 254, 262
 nitride-based 317
 nonmagnetic 30
 optical 259
 optoelectronic 237
 MBE *see* molecular beam epitaxy
 mechanical modes 383, 384, 421,
 424–428, 430, 431
 mechanical oscillators 75,
 381–383, 421, 432
 mechanical systems 381, 382, 421,
 424, 432
 metal nanodisks 293, 294, 299,
 308, 310
 metal-organic chemical vapor
 deposition (MOCVD) 88, 98,
 107, 158, 205, 206, 220, 226,
 228, 323, 331, 337, 361–363,
 366, 372, 485
 microcavities 43, 88, 100, 101,
 153, 157, 207, 209, 212, 289,
 344, 349, 437, 439, 442, 460
 disk-shaped 344
 epitaxial nitride 87, 128, 207
 high-quality nitride-based 88
 hybrid 87, 206
 planar 152
 vertical pillar 344
 microdisk cavities 110, 115, 116,
 131, 132, 134, 136–138, 140,
 142, 144, 146, 148, 150, 152,
 154, 156, 345
 microdisk lasers 110, 113, 114,
 141, 212, 237, 357
 microdisk resonators 49, 50, 132,
 141, 143–145, 147, 149
 microdisks 27, 49, 111–113,
 132–135, 137, 139–143,
 146–149, 151, 152, 155, 329,
 330, 357, 359, 434, 443, 445
 fabricated 112
 free-standing 146
 group-III nitride 146
 nitride-based 142, 152
 semiconductor 131
 microdisk structures 111, 153,
 329, 330
 microlasers 24, 132, 441, 466
 microresonators 434, 435, 442,
 458
 MOCVD *see* metal-organic chemical
 vapor deposition
 model 121, 137, 140, 240, 417,
 426, 489
 constant hot-zone 407
 mathematical 42
 nonlocal 60
 plane wave 458
 plane-wave 448
 modes 40, 41, 46, 48–50, 53, 54,
 56–59, 113–115, 133–136,
 139–143, 150, 151, 327, 387,
 390–392, 402, 411–413, 427,
 428
 backward-propagation 342
 counter-propagating 342
 electromagnetic 213
 evanescent 53, 54
 harmonic 53
 higher-order 59, 304–306
 hybrid 477
 hybrid dielectric-plasmonic 477,
 492
 leaky 58, 225, 228, 234
 non-lasing 116
 non-resonant 340
 optical-guided 235
 parasitic 143
 photon 225, 228
 radiation 225, 233
 resonance 343
 standing-wave 403
 surface plasmonic 477
 theoptical 482
 mode spacing 150, 151, 329, 330,
 334, 335, 340, 342

- mode volume 141, 144, 151, 295
 molecular beam epitaxy (MBE)
 183, 259, 260, 274, 282, 289,
 372, 404
 MQWs *see* multi-quantum wells
 multi-quantum wells (MQWs) 91,
 97–101, 159, 193, 196–199,
 220–223, 226, 246, 264, 271,
 327, 328, 337, 339
- nanocavities 23, 81, 125, 212, 214,
 224, 237
 nano-pillar array 319, 322, 324,
 326, 328, 331, 344
 air-spaced 321
 metal-clad 322
 nanopillar lasers 475, 478, 481,
 483
 metal-clad 477, 478
 nanoring 477, 478, 483, 486
 nano-ring arrays 322, 337–341,
 344
 nanoring cavity 480, 483
 nanoring laser 474, 475, 478, 481,
 483, 486, 490
 nanoring lasers 475, 477, 479,
 481, 483, 490
 nanosphere lithography (NSL)
 197, 243, 317, 319–322, 330,
 337, 344, 346, 347
 nanospheres 317, 319, 323, 344
 nanostripe 117, 119, 121–123,
 125
 nanowires 361, 443, 445, 468, 469
 NBE *see* near band edge
 near band edge (NBE) 447, 450,
 465
 nitride DBRs 160, 161, 163, 165,
 167, 169, 171, 173
 nitride materials 83, 84, 131, 147,
 221, 225, 320, 375
 nitride nanopillars 204, 348, 467
 nitride PCs 214, 221, 226, 227
 NSL *see* nanosphere lithography
- optical cavities 23, 88, 152, 262,
 316, 317, 322, 327, 339, 388,
 392, 408, 421, 459, 474
 high-finesse 317
 nanosphere-patterned 317
 natural 259
 sphere-patterned 330
 surface-emitting 316
 optical confinement 84, 335, 411,
 443, 474, 475
 optical energy 382, 384, 386, 419,
 421, 430, 477
 optical field 60, 84, 91, 122, 157,
 455, 457
 optical gain 190, 452, 474–476,
 485, 489
 optical losses 119, 124, 336, 385,
 386, 411, 413, 437, 442, 457,
 459, 474, 475, 478, 482, 483
 optical modes 119, 121, 123, 125,
 132, 264, 272, 273, 382, 384,
 386, 389, 474, 475, 477, 481,
 482, 487
 optical performance 158, 160, 163,
 190, 196, 197, 201, 248
 optical power 186, 229, 397, 402,
 416, 430, 431, 435
 optical properties 146, 149, 151,
 152, 155, 311, 317, 323, 376,
 377, 383, 407, 409, 445, 447,
 469, 471
 optical pumping 86, 93, 97, 186,
 198, 200, 214, 220
 optical reflection 285, 286
 optical resonances 412, 418, 420,
 422, 428, 430
 optical resonators 28, 43, 131,
 152, 386, 388, 469, 470
 optoelectronic devices 28, 51, 364,
 365, 372, 377, 443, 462, 471

- optomechanical coupling 382, 383, 409, 421, 424, 426–429, 431, 432
 experimental 431
 finite 427
 simulated 428, 431
 vacuum 382, 421
- patterns 111, 117, 221, 226, 249, 254, 259, 308–310, 320, 321, 323, 328, 332, 457, 485
 diffraction-limited far-field 105
 far field 103
 in-plane angular emission 336
 inverse 322
 nanosphere 331
 near-field 193, 195
 near field beam 105
 pillar 319
 triangular lattice 220
- PBG *see* photonic bandgap
- PCs *see* photonic crystals
- PECVD *see* plasma-enhanced chemical vapor deposition
- perfectly matched layer (PML) 42, 79, 393–395, 435
- periodicity 40, 41, 44, 53, 54, 137, 214, 219, 220, 224, 225, 230, 233, 268, 337
- PhCC *see* photonic crystal cavity
- photolithography 249, 265, 269, 282, 329, 330
- photoluminescence 93, 146, 152, 214, 299, 322, 460, 486
- photon energy 150, 152, 181, 182, 354, 355, 357, 458
- photonic bandgap (PBG) 43, 44, 51, 53–55, 57, 213, 220, 225, 234, 316, 320, 321, 328
- photonic bands 57, 58, 214, 322
- photonic crystal cavity (PhCC) 27, 28, 43, 50, 53, 56, 57, 69, 70, 72, 73, 75, 81
- photonic crystal microcavities 152
- photonic crystal microcavities 23, 436
- photonic crystals (PCs) 23–25, 50, 80, 81, 127, 128, 211–215, 219–237, 239, 241–244, 264, 290, 346, 431, 442
- photonic devices 51, 75, 213, 238, 351, 365, 372
- plasma-enhanced chemical vapor deposition (PECVD) 111, 117
- PML *see* perfectly matched layer
- process 92, 111, 117, 147, 166, 178, 181, 185, 218, 259, 308, 315, 316, 351, 352, 386, 395, 396
- anodic 185
- chemical undercut 110
- dimension-adjusting 321
- dissipation 235
- electrodeposition 486
- laser irradiation 352
- lithographic 318
- nanofabrication 384, 404, 417
- non-radiative recombination 296
- packaging 302
- polishing 98
- pre-oxidation 185
- reaction-limited 356
- resonant 443
- temperature ramping 177
- temperature-ramping 177
- thermal annealing 300
- thermal cleaning 91, 116
- top-down 248, 253
- wafer-bonding 195
- propagation 47, 51, 54, 132, 135, 151, 353
- azimuthal phase 387
- crack 169
- lateral 225
- optical-mode 342
- single mode 136

- pumped lasing 159, 190, 317
 pumping energy 93–96, 99
 pump power 479, 487–490
- QCSE *see* quantum-confined Stark effect
 QDs *see* quantum dots
 QDs
 embedded 72
 identical 72–74
 self-assembled 59
 well-separated 75
 QE *see* quantum efficiency
 quality factors 23, 49, 88, 89, 116,
 119, 124, 141, 144, 147–152,
 225, 295, 324, 384–386, 388,
 395
 cold-cavity 337
 high cavity 100
 loaded 415
 optical 432
 radiative 393
 quantum-confined Stark effect
 (QCSE) 196
 quantum dots (QDs) 27, 59–75, 77,
 81, 132, 146, 153, 155
 quantum efficiency (QE) 94, 95,
 212
 quantum wells (QWs) 64, 83, 84,
 94, 95, 124–126, 144, 219,
 220, 223, 237, 244, 293, 294,
 296, 297, 299, 303, 304, 307,
 308, 310–312
 QWs *see* quantum wells
- radial numbers 139, 143, 150, 151,
 391, 396, 412
 radiating dipole 293, 295, 296,
 298, 299, 304, 310, 311
 radiation losses 386, 395, 412,
 420, 429, 430, 474, 475
- RC *see* resonant-cavity
 RCLEDs *see* resonant cavity light emitting diodes
 RCWA *see* rigorous coupled-wave analysis
 reactive ion etching (RIE) 111,
 254, 338, 464
 reflectance spectra 108, 247, 252,
 253, 257, 258, 262, 263, 285
 reflectivity 86–89, 94, 95, 98, 161,
 163, 164, 166, 172–175, 187,
 189, 190, 197, 199, 273, 285,
 460, 462
 reflectivity spectrum 92, 107, 109,
 115, 168, 172–174, 179, 183
 refractive index 104, 107, 109,
 161, 162, 178, 180, 187, 189,
 235, 268, 271, 302, 304, 387,
 389
 regimes 27, 359, 401, 414, 415,
 452, 459
 high-density 452
 intermediate density 452
 nanosecond 70
 reaction-limited 358
 strong confinement 322
 strong-coupling 131, 153, 439
 resonances 38–41, 45, 54, 57, 86,
 247, 248, 304, 305, 327, 397,
 400, 401, 409, 412, 415, 416,
 427
 asymmetric 417
 guided mode 259, 262, 263
 isolated 70
 leaky 225
 mechanical 424, 427–429
 ring 412
 resonant-cavity (RC) 200
 resonant cavity light emitting diodes (RCLEDs) 160, 200,
 201
 resonant peaks 202, 248, 252, 253,
 342, 465
 dense 330

- polarized 449
- resonators 27, 47, 48, 75, 149, 150, 212, 329, 343, 382, 383, 386, 409, 414, 425, 426, 438, 442, 443, 449
- circular 38
- optomechanical 382, 421, 434
- quantum mechanical 28, 382, 421, 433
- traveling-wave 342
- RIE *see* reactive ion etching
- rigorous coupled-wave analysis (RCWA) 246, 247

- sacrificial layer 144, 180, 182, 351, 354–356, 359–361, 363, 364, 404
- SAG *see* selective-area growth
- sapphire substrates 88, 98, 116, 171, 172, 186, 188, 206, 209, 226, 228, 351, 353, 354, 358, 359, 371, 373, 374
- c-plane 299, 308, 323, 337
- insulating 215
- transparent 351
- scanning electron microscopy (SEM) 92, 102, 107, 147, 172, 220, 249, 299, 360, 405, 407, 423, 426, 430
- scattering losses 89, 137, 143, 148, 149, 251, 253, 279, 336, 476
- selective-area growth (SAG) 290
- SEM *see* scanning electron microscopy
- semiconductor materials 59, 214, 245, 294, 375, 459, 463
- semiconductors 81, 213, 219, 225, 238–240, 243, 307, 309, 358, 443, 446, 474, 475, 482, 485, 491
- low-dimensional 460
- nitride-based 315, 345
- nitride-based 349
- n-type 356
- organic 216
- p-type 356
- SEM images 108, 182, 184, 187, 226, 227, 230, 250, 251, 266, 267, 270, 280, 283, 284, 300, 302, 303, 361, 363
- silicon substrate 144–146, 152, 155, 201, 254, 256, 264, 265, 267, 269, 271–275, 277, 281, 282, 284, 370, 372
- flat 285–288
- nanostructured 283, 285–288
- patterned 170
- simulation 28, 37, 40, 48, 50, 56, 73, 79, 114, 172, 173, 175, 246, 327, 488, 491
- numerical 426, 427, 431
- theoretical 109
- solid-state lighting (SSL) 236, 239, 378
- solutions 47, 52, 55, 79, 84, 134, 135, 137–139, 179, 185, 214, 220, 354, 390, 391, 422, 430
- analytical 135
- antisymmetric 46
- aqueous 354
- chemical 180
- concentrated 364
- decaying 46
- hydrofluoric acid 405
- spurious mode 394
- steady-state 402
- spectral peaks 301, 332, 339, 340
- spectral region 158, 159, 177, 196, 202, 291, 443, 458
- blue 179, 321
- deep UV 238
- green 159, 171, 195
- long wavelength 158
- violet-blue 158, 172
- spectrum 99, 100, 113, 119, 173, 174, 231, 237, 309, 330, 335,

- 339, 409, 411–413, 420, 427, 465
- converged 76
- discrete Fourier 49
- doublet resonance 403
- mechanical 427, 431
- motional noise 423
- optical 396
- optical resonance 413
- simulated 114, 454
- symmetrical 173
- SPP *see* surface plasmon polariton
- SPs *see* surface plasmons
- SSL *see* solid-state lighting
- structure 84, 86–89, 91, 92, 121, 122, 124, 125, 134, 184–186, 201, 220, 221, 225, 226, 235, 236, 298, 299, 307, 308, 364–366, 442, 443
- air-gap 183
- cell 342, 343
- circular 38, 39, 330
- clover-shaped PBG 321
- compound 59
- curved 38, 39
- cylindrical 38
- dielectric 39
- flat pyramidal 59, 338
- hybrid 89, 460
- hybrid-type cavity 87
- inverted cone 362
- layered 368
- metal-clad 479
- metal-clad nanolasers 477
- metal-grating 295
- microcavity 349
- micrometer-sized pillar 317
- multi-coupled rings 343
- multi-twisted looped 408
- nanolaser 475, 477
- nanophotonic 212
- nanopillar 197, 478, 480
- nano-pillar 323
- nitride emitter 213
- optical 415
- pillar 404
- resonant 44
- ridge waveguide 122
- sphere-patterned 322
- triangular lattice 223
- whispering gallery 426
- substrates 143, 145, 159–161, 188, 189, 245, 288, 290, 318, 350–353, 360, 365, 367, 368, 370–372, 408, 444
- flexible 351, 368, 372, 466
- lattice-matched 245
- patterned 272, 290
- plastic 368
- receptor 353
- stretchable 370
- unpatterned 262, 276
- surface plasmon polariton (SPP) 294–296
- surface plasmons (SPs) 122, 244, 293–298, 300, 302, 304, 306, 308, 310–312, 322, 475–477, 493
- technology 59, 86, 180, 202, 208, 216, 236, 282, 317, 434
- epitaxial growth 192
- flip-chip 219
- homoepitaxy 195
- laser printing 86
- micro-fabrication 317
- nanophotonic 212
- nitride laser 344
- semiconductor patterning 473
- silicon backside 254
- threshold 85, 88, 94, 95, 103, 104, 106, 120, 124, 186, 190–196, 198, 332, 333, 336, 339, 450, 451, 479
- optical 186, 190, 198
- TIR *see* total internal reflection

- TLS *see* two-level system
 TMM *see* transfer matrix method
 total internal reflection (TIR)
 43–45, 49, 56, 133, 238, 264,
 269, 272, 273, 329, 384, 455,
 460, 467
 transfer matrix method (TMM)
 396–398
 two-level system (TLS) 60, 68
- UPB *see* upper polariton branch
 upper polariton branch (UPB) 199,
 460
- vapor phase transport (VPT) 444
 VCSEL *see* vertical-cavity
 surface-emitting lasers
 vertical-cavity surface-emitting
 lasers (VCSEL) 86, 88–90,
 93, 95, 100, 104, 127,
 157–159, 187–189, 192–195,
 197, 199, 204, 209
 VPT *see* vapor phase transport
- wafer 85, 91, 119, 169, 170, 177,
 185, 188, 289, 318, 319, 323,
- 330, 331, 337, 338, 344, 352,
 353
 epitaxial 404
 semi-insulating GaAs 404
 waveguide 134, 135, 137, 212,
 386, 396, 401, 474, 483, 485
 circular 473
 fiber-taper 417
 planar 132
 ridge 486
 waves 37, 45, 57, 397
 electromagnetic 51, 54, 79, 459
 optical 189
 spherical 66
 WGM cavity 447, 448, 455, 457,
 460, 462, 465, 466
 WGM lasing 441, 443, 447, 450,
 456–458, 462, 465, 466
 WGMs *see* whispering gallery
 modes
 WGMs resonances 420, 427
 whispering gallery modes (WGMs)
 49, 50, 149, 150, 152, 329,
 383–385, 387, 388, 391–393,
 395, 396, 398–400, 409–414,
 416, 418–421, 441–444, 455,
 456, 470
- X-ray diffraction (XRD) 108, 164
 XRD *see* X-ray diffraction

